

Name of Product CHARCOAL LIGHTER DISTILLATE

Chevron Phillips Chemical Company LP 10001 Six Pines Drive The Woodlands, TX 77380 800-858-4327 Technical Service: 832-813-4862

Revision Date 9/15/2008

Chevron Phillips Chemical International N.V. Chevron Phillips Chemicals Asia PTE Ltd. Airport Plaza - Stockholm Building 1 Harbour Front Avenue Leonardo Da Vincilaan 19 #09-01 Keppel Bay Tower Singapore, 098632 +65 6517 3100

Test	Units	Method	Typical	Minimum	Maximum	Qualitative	Note
Saybolt Color	SAY	ASTM D-6045		30			
Corrosion (3 hrs @212F)		ASTM D-130					1B Max
Flash Point, TCC	FAH	ASTM D-56		100			
Odor		Smell				Pass	
Distillation - IBP	FAH	ASTM D-86		300			
Distillation - DP	FAH	ASTM D-86			350		
Acidity of Dist Residue		ASTM D-1093				Neutral	

1831 Diegem, Belgium

+32 2 689 1211

Printed Versions of this document are uncontrolled

Notice: Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific applicable to the connection with the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, tort or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user. Additional information on the health and safety aspects of our product is listed in the SDS of the product.