

Chevron Phillips Chemical Company Issued Sales Specification

Name of Product

Revision Date

SCENTINEL*O-10

2/15/2011

Chevron Phillips Chemical Company LP

10001 Six Pines Drive The Woodlands, TX 77380

800-858-4327

Technical Service: 832-813-4862

Chevron Phillips Chemical International N.V. Chevron Phillips Chemicals Asia PTE Ltd.

Airport Plaza - Stockholm Building

Leonardo Da Vincilaan 19

1831 Diegem, Belgium +32 2 689 1211

1 Harbour Front Avenue

#09-01 Keppel Bay Tower

Singapore, 098632

+65 6517 3100

Test	Units	Method	Typical	Minimum	Maximum	Qualitative	Note
APHA Color		ASTM D-5386	8		30		
Appearance		Visual	Clear with no particulate matter			Clear with no particulate matter	
Cloud Point	FAH	ASTM D-2386 mod	< -50		-50		
Dimethyl Sulfide	WT%	Chromatography	10	8.0	12.0		
Distillation - EP	FAH	ASTM D-86	143		170		
Distillation - IBP	FAH	ASTM D-86	123	115			
Freezing Point	FAH	ASTM D-2386	< -50		-50		
Isopropyl Mercaptan	WT%	Chromatography	70	68.0	72.0		
n-Propyl Mercaptan	WT%	Chromatography	10	8.0	12.0		
Other Mercaptans	WT%	Chromatography	0.1		5.0		
Specific Gravity 60/60		ASTM D-4052	0.8250	0.8200	0.8300		
t-Butyl Mercaptan	WT%	Chromatography	10	8.0	12.0		
Other	Units	Method	Typical	Minimum	Maximum	Qualitative	Note
Calculated Sulfur	WT%	Chromatography	42				
Density @ 60 F	LB/GAL	ASTM D-4052	6.86				
Distillation - 50%	FAH	ASTM D-86	128				
Distillation - 90%	FAH	ASTM D-86	134				
Flash Point, PM	FAH	ASTM D-93	< 0				
Half Doctor Test		ASTM D-235	Pass				
Reid Vapor Pressure at 100F	PSI	Calculated	9.0				

Printed Versions of this document are uncontrolled

Notice: Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. Chevron Phillips Chemical Company LP does not make, and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, tort or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user. Additional information on the health and safety aspects of our product is listed in the SDS of the product.