

## Marlex® HMN 6060UV Polyethylene

Version 1.5

Revision Date 2019-08-19

TION 1: Identification of t	he substance/mixture and of the company/undertaking
Product information	
Product Name Material	<ul> <li>Marlex® HMN 6060UV Polyethylene</li> <li>1119892, 1119881, 1119880, 1119879, 1119878, 1119830, 1119829, 1119828, 1119827, 1119826, 1109065, 1109066, 1109069, 1109067, 1109068, 1109064, 1109063</li> </ul>
Company	: Chevron Phillips Chemical Company LP 10001 Six Pines Drive The Woodlands, TX 77380
Emergency telephone:	
Asia: CHEMWATCH (+ EUROPE: BIG +32.14. Mexico CHEMTREC 01	ational) 300 or 703.527.3887(int'l) 612 9186 1132) China: 0532 8388 9090 584545 (phone) or +32.14583516 (telefax) -800-681-9531 (24 hours) otec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600
Responsible Department E-mail address Website	<ul> <li>Product Safety and Toxicology Group</li> <li>SDS@CPChem.com</li> <li>www.CPChem.com</li> </ul>

MEDICAL APPLICATION CAUTION: Do not use this material in medical applications involving permanent implantation in the human body or permanent contact with internal body fluids or tissues fluids or tissues.

Do not use this material in medical applications involving brief or temporary implantation in the human body or contact with internal body fluids or tissues unless the material has been provided directly from Chevron Phillips Chemical Company LP or its legal affiliates under an agreement which expressly acknowledges the contemplated use.

Chevron Phillips Chemical Company LP and its legal affiliates makes no representation, promise, express warranty or implied warranty concerning the suitability of this material for use in implantation in the human body or in contact with internal body fluids or tissues.

SDS Number:10000000041

# Marlex® HMN 6060UV Polyethylene

### Version 1.5

Revision Date 2019-08-19

## **SECTION 2: Hazards identification**

<ul> <li>Combustible dust</li> <li>Warning <ul> <li>May form combustible dust concentrations in air.</li> <li>While this product may not be a combustible dust as sold, further processing or handling may form combustible dust concentration in air.</li> </ul> </li> <li>Pellets may cause a slip hazard on hard surfaces. Mechanical processing may form combustible dust concentrations in air and thermal processing at elevated temperatures may generate formaldehyde.</li> <li>Repeated exposure to dust from this material may cause respiratory irritation.</li> </ul>
<ul> <li>May form combustible dust concentrations in air. While this product may not be a combustible dust as sold, further processing or handling may form combustible dust concentration in air.</li> <li>Pellets may cause a slip hazard on hard surfaces. Mechanical processing may form combustible dust concentrations in air and thermal processing at elevated temperatures may generate formaldehyde.</li> <li>Repeated exposure to dust from this material may cause respiratory irritation.</li> </ul>
<ul> <li>May form combustible dust concentrations in air. While this product may not be a combustible dust as sold, further processing or handling may form combustible dust concentration in air.</li> <li>Pellets may cause a slip hazard on hard surfaces. Mechanical processing may form combustible dust concentrations in air and thermal processing at elevated temperatures may generate formaldehyde.</li> <li>Repeated exposure to dust from this material may cause respiratory irritation.</li> </ul>
<ul> <li>While this product may not be a combustible dust as sold, further processing or handling may form combustible dust concentration in air.</li> <li>Pellets may cause a slip hazard on hard surfaces. Mechanical processing may form combustible dust concentrations in air and thermal processing at elevated temperatures may generate formaldehyde.</li> <li>Repeated exposure to dust from this material may cause respiratory irritation.</li> </ul>
<ul> <li>Mechanical processing may form combustible dust concentrations in air and thermal processing at elevated temperatures may generate formaldehyde.</li> <li>Repeated exposure to dust from this material may cause respiratory irritation.</li> </ul>
<ul> <li>Mechanical processing may form combustible dust concentrations in air and thermal processing at elevated temperatures may generate formaldehyde.</li> <li>Repeated exposure to dust from this material may cause respiratory irritation.</li> </ul>
respiratory irritation.
Fumes generated during thermal processing may cause irritation of the upper respiratory tract.
<ul> <li>Contact with the skin is not expected to cause prolonged or significant irritation.</li> <li>Contact with the skin is not expected to cause an allergic response.</li> <li>If this material is heated, thermal burns may result from contact Thermal burns may include pain or feeling of heat, discolorations, swelling, and blistering.</li> </ul>
<ul> <li>Contact with the eyes may cause irritation due to the abrasive action.</li> <li>Not expected to cause prolonged or significant eye irritation.</li> <li>Thermal burns may result if heated material contacts eye.</li> </ul>
: Ingestion of this product is not a likely route of exposure.
No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

# Marlex® HMN 6060UV Polyethylene

Version 1.5

Revision Date 2019-08-19

Component Polyethylene Hexene Copoly	/mer	•	CAS-No. 25213-02-9		Weight % 99 - 100
TION 4: First aid measures					
If inhaled	:	fumes f			dental inhalation of dust or oustion. If symptoms persist,
In case of skin contact	:	If the molten material gets on skin, quickly cool in water. Seek immediate medical attention. Do not try to peel the solidified material from the skin or use solvents or thinners to dissolve it.			
In case of eye contact	:		ase of contact wit r and seek medic		rinse immediately with plenty e.
If swallowed	:	: Do not induce vomiting without medical advice.			
TION 5: Firefighting measu	res				
Flash point	:	No data	a available		
Autoignition temperature	:	No data	available		
Suitable extinguishing media	:	Foam. fogging applicat surface create a extingui	If possible, water nozzle since this tion of high veloci layer. Avoid the a dust cloud and t	should is a sur ty water use of s he risk hat are	al. Carbon dioxide (CO2). be applied as a spray from a face burning material. The will spread the burning straight streams that may of a dust explosion. Use appropriate to local ing environment.
Specific hazards during fire fighting	:	explosio			e propagation or secondary accumulation of dust, e.g. or
Special protective equipment for fire-fighters	:		rsonal protective on apparatus for f		ent. Wear self-contained ng if necessary.
Further information	:	This ma	aterial will burn alt	hough i	t is not easily ignited.
Hazardous decomposition products	:	produce hydroca acids) c	e carbon monoxid arbon oxidation pr lepending on tem	e, other oducts perature	n dioxide, water vapor and ma hydrocarbons and (ketones, aldehydes, organic and air availability. produce formaldehyde.

## Marlex® HMN 6060UV Polyethylene

Version 1.5

Revision Date 2019-08-19

## SECTION 6: Accidental release measures

		Sweep up to prevent slipping hazard. Avoid breathing dust.
		Avoid dust formation.
Environmental precautions	:	Do not contaminate surface water. Prevent product from entering drains.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum.
Additional advice	:	Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
TION 7: Handling and stora	ge	
Handling		
Advice on safe handling		Use good housekeeping for safe handling of the product.
Advice on safe handling	•	Keep out of water sources and sewers.
		Spilled pellets and powders may create a slipping hazard.
		Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient. At elevated temperatures (>350°F, >177°C), polyethylene can release vapors and gases, which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. These substances may include acetaldehyde, acetone, acetic acid, formic acid, formaldehyde and acrolein. Based on animal data and limited epidemiological evidence, formaldehyde has been listed as a carcinogen. Following all recommendations within this SDS should minimize exposure to thermal processing emissions.
Storage		
Requirements for storage areas and containers	:	Keep in a dry place. Keep in a well-ventilated place.
Advice on common storage	:	Do not store together with oxidizing and self-igniting products.
TION 8: Exposure controls/	per	sonal protection

US

Components	Basis	Value	Control parameters	Note
Nuisance Dust	OSHA Z-3	TWA	15 mg/m3	Total dust
	OSHA Z-3	TWA	5 mg/m3	(respirable dust)

SDS Number:100000000041

## Marlex® HMN 6060UV Polyethylene

Version 1.5

for total dust. The OSHA PEL for respirable dust is 5.0 mg/m3 and 15.0 mg/m3 for total dust. \* This value is for inhalable (total) particulate matter containing no asbestos and < 1.0% crystalline silica. Engineering measures Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Personal protective equipment Respiratory protection No respiratory protection is normally required. If heated material generates vapor or fumes that are not adequately controlled by ventilation, wear an appropriate respirator. Use the following elements for air-purifying respirators: Organic Vapor and Formaldehyde. Use a positive pressure, airsupplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection. Dust safety masks are recommended when the dust concentration is excessive. Eye protection Use of safety glasses with side shields for solid handling is good industrial practice. If this material is heated, wear chemical goggles or safety glasses with side shields or a face shield. If there is potential for dust, use chemical goggles. Skin and body protection At ambient temperatures use of clean and protective clothing is • good industrial practice. If the material is heated or molten, wear thermally insulated, heat-resistant gloves that are able to withstand the temperature of the molten product. If this material is heated, wear insulated clothing to prevent skin contact if engineering controls or work practices are not adequate. **SECTION 9: Physical and chemical properties** Information on basic physical and chemical properties Appearance : Pellets Form Physical state Solid ٠ Color : Opaque Odor Mild to no odor : Odor Threshold No data available · Safety data : No data available Flash point Lower explosion limit : Not applicable Upper explosion limit : Not applicable SDS Number:10000000041 5/12

Control as Particulate Not Otherwise Classified (PNOC). The ACGIH Guideline\* for respirable dust is 3.0 mg/m3 and 10.0 mg/m3

# Marlex® HMN 6060UV Polyethylene

sion 1.5	Revision Date 2019-08
Autoignition temperature	: No data available
Thermal decomposition	: Low molecular weight hydrocarbons, alcohols, aldehydes, acids and ketones can be formed during thermal processing.
рН	: Not applicable
Melting point/range	: 90 - 140 °C (194 - 284 °F)
Freezing point	Not applicable
Initial boiling point and boiling range	: Not applicable
Vapor pressure	: Not applicable
Relative density	: Not applicable
Density	: 0.91 - 0.97 g/cm3 Please refer to the Technical Data Sheet (TDS) for more detailed information relating to the nominal physical properties, including density, of this polyethylene resin grade.
Water solubility	: Negligible
Partition coefficient: n- octanol/water	: No data available
Solubility in other solvents	: No data available
Viscosity, dynamic	: Not applicable
Viscosity, kinematic	: Not applicable
Relative vapor density	: Not applicable
Evaporation rate	: Not applicable
TION 10: Stability and reactiv	ity
Reactivity	: This material is considered non-reactive under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous read	tions
Conditions to avoid	: Avoid prolonged storage at elevated temperature.

# Marlex® HMN 6060UV Polyethylene

rsion 1.5	Revision Date 2019-08-1
Materials to avoid	: Avoid contact with strong oxidizing agents.
Thermal decomposition	: Low molecular weight hydrocarbons, alcohols, aldehydes, acids and ketones can be formed during thermal processing.
Hazardous decomposition products	: Normal combustion forms carbon dioxide, water vapor and may produce carbon monoxide, other hydrocarbons and hydrocarbon oxidation products (ketones, aldehydes, organic acids) depending on temperature and air availability. Incomplete combustion can also produce formaldehyde.
Other data	: No decomposition if stored and applied as directed.
CTION 11: Toxicological infor	mation
Marlex® HMN 6060UV Polye Acute oral toxicity	
Marlex® HMN 6060UV Polye Acute inhalation toxicity	
Marlex® HMN 6060UV Polye Acute dermal toxicity	
Marlex® HMN 6060UV Polye Skin irritation	thylene : No skin irritation
Marlex® HMN 6060UV Polye Eye irritation	thylene : No eye irritation
Marlex® HMN 6060UV Polye Sensitization	thylene : Did not cause sensitization on laboratory animals.
Marlex® HMN 6060UV Polye Further information	<ul> <li>thylene</li> <li>This product contains POLYMERIZED OLEFINS. During thermal processing (&gt;350°F, &gt;177°C) polyolefins can release vapors and gases (aldehydes,ketones and organic acids) which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. Generally these irritant effects are all transitory. However, prolonged exposure to irritating off-gases can lead to pulmonary edema. Formaldehyde (an aldehyde) has been classified as a carcinogen based on animal data and limited epidemiological evidence.</li> </ul>
CTION 12: Ecological informa	tion
Ecotoxicity effects	
S Number:100000000041	7/12

## Marlex® HMN 6060UV Polyethylene

Version 1.5

Revision Date 2019-08-19

Biodegradability	: This material is not expected to be readily biodegradable.
Elimination information (persisted	ence and degradability)
Bioaccumulation	: Does not bioaccumulate.
Mobility	: The product is insoluble and floats on water.
Additional ecological information	: This material is not expected to be harmful to aquatic organisms., Fish or birds may eat pellets which may obstruct their digestive tracts.
Ecotoxicology Assessment	
SECTION 13: Disposal considerat	ions

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

### **SECTION 14: Transport information**

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION) NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS) NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION) NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE)) NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

SDS Number:10000000041

8/12

# Marlex® HMN 6060UV Polyethylene

Version 1.5

Revision Date 2019-08-19

DANGEROUS GOODS (EU	HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR
OF DANGEROUS GOODS	MENT CONCERNING THE INTERNATIONAL CARRIAGE BY INLAND WATERWAYS) HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR THIS AGENCY.
Fransport in bulk according to SECTION 15: Regulatory inform	Annex II of MARPOL 73/78 and the IBC Code
National legislation	
SARA 311/312 Hazards	: Combustible dust
CERCLA Reportable Quantity	: This material does not contain any components with a CERCLA RQ.
SARA 302 Reportable Quantity	: This material does not contain any components with a SARA 302 RQ.
SARA 302 Threshold Planning Quantity	: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 304 Reportable Quantity	: This material does not contain any components with a section 304 EHS RQ.
SARA 313 Components	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
Clean Air Act	
Potential Class	roduct neither contains, nor was manufactured with a Class I or II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR ubpt. A, App.A + B).

### Marlex<sup>®</sup> HMN 6060UV Polyethylene

Revision Date 2019-08-19

Version 1.5 This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61). This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F). This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489). **US State Regulations** Pennsylvania Right To Know : No components are subject to the Pennsylvania Right to Know Act. : This product, as shipped, does not contain any carcinogens or California Prop. 65 reproductive toxins presently known by the State of California to Components cause cancer or reproductive toxicity at a level of exposure subject to the requirements of California Proposition 65. Notification status Europe REACH On the inventory, or in compliance with the inventory 5 United States of America (USA) On or in compliance with the active portion of the **TSCA** inventory TSCA Canada DSL 2 All components of this product are on the Canadian DSL Australia AICS On the inventory, or in compliance with the inventory New Zealand NZIoC On the inventory, or in compliance with the inventory 1 On the inventory, or in compliance with the inventory Japan ENCS 2 A substance(s) in this product was not registered, Korea KECI 2 notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance. Philippines PICCS On the inventory, or in compliance with the inventory 2 China IECSC On the inventory, or in compliance with the inventory 2 Taiwan TCSI On the inventory, or in compliance with the inventory 5

## Marlex® HMN 6060UV Polyethylene

Version 1.5

Revision Date 2019-08-19

### **SECTION 16: Other information**

NFPA Classification	: Health Hazard: 0 Fire Hazard: 1 Reactivity Hazard: 0	
Further information		

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

ACGIH	American Conference of	LD50	Lethal Dose 50%
	Government Industrial Hygienists		
AICS	Australia, Inventory of Chemical	LOAEL	Lowest Observed Adverse Effe
	Substances		Level
DSL	Canada, Domestic Substances	NFPA	National Fire Protection Agence
	List		
NDSL	Canada, Non-Domestic	NIOSH	National Institute for Occupation
	Substances List		Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of
			Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect
			Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentra
EGEST	EOSCA Generic Exposure	OSHA	Occupational Safety & Health
	Scenario Tool		Administration
EOSCA	European Oilfield Specialty	PEL	Permissible Exposure Limit
	Chemicals Association		
EINECS	European Inventory of Existing	PICCS	Philippines Inventory of
	Chemical Substances		Commercial Chemical Substar
MAK	Germany Maximum Concentration	PRNT	Presumed Not Toxic
	Values		
GHS	Globally Harmonized System	RCRA	Resource Conservation Recov
			Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and
			Reauthorization Act.
IARC	International Agency for Research	TLV	Threshold Limit Value
	on Cancer		
IECSC	Inventory of Existing Chemical	TWA	Time Weighted Average
	Substances in China		
ENCS	Japan, Inventory of Existing and	TSCA	Toxic Substance Control Act
	New Chemical Substances		
KECI	Korea, Existing Chemical	UVCB	Unknown or Variable Compos
	Inventory		Complex Reaction Products, a

# Marlex® HMN 6060UV Polyethylene

Version 1.5

Revision Date 2019-08-19

			Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

SDS Number:10000000041