

Marlex® 7308DK Polyethylene

Version 3.4

Revision Date 2019-10-10

ECTION 1: Identification of the second	ubstance/mixture and of the company/undertaking
Product information	
Product Name : Material :	Marlex® 7308DK Polyethylene 1068781, 1068784, 1068785, 1068786, 1068787, 1068789, 1068788
Company :	Chevron Phillips Chemical Company LP 10001 Six Pines Drive The Woodlands, TX 77380
Emergency telephone:	
EUROPE: BIG +32.14.58454 Mexico CHEMTREC 01-800	al) or 703.527.3887(int'l) 9186 1132) China: 0532 8388 9090 45 (phone) or +32.14583516 (telefax) -681-9531 (24 hours) nside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600
E-mail address :	Product Safety and Toxicology Group SDS@CPChem.com www.CPChem.com
	TION: Do not use this material in medical applications involving numan body or permanent contact with internal body fluids or tissues
human body or contact with inte	ical applications involving brief or temporary implantation in the ernal body fluids or tissues unless the material has been provided chemical Company LP or its legal affiliates under an agreement which ntemplated use.
express warranty or implied war	npany LP and its legal affiliates makes no representation, promise, rranty concerning the suitability of this material for use in implantation t with internal body fluids or tissues.
S Number:100000000581	1/12

Marlex® 7308DK Polyethylene

Version 3.4

Revision Date 2019-10-10

SECTION 2: Hazards identification

Classification	: Combustible dust
Labeling	
Signal Word	: Warning
Hazard Statements	: May form combustible dust concentrations in air. While this product may not be a combustible dust as sold, further processing or handling may form combustible dust concentration in air.
Potential Health Effects	
Physical Hazards	: Pellets may cause a slip hazard on hard surfaces. Mechanical processing may form combustible dust concentrations in air and thermal processing at elevated temperatures may generate formaldehyde.
Inhalation	 Repeated exposure to dust from this material may cause respiratory irritation. Fumes generated during thermal processing may cause irritation of the upper respiratory tract.
Skin	 Contact with the skin is not expected to cause prolonged or significant irritation. Contact with the skin is not expected to cause an allergic response. If this material is heated, thermal burns may result from contact Thermal burns may include pain or feeling of heat, discolorations, swelling, and blistering.
Eyes	 Contact with the eyes may cause irritation due to the abrasive action. Not expected to cause prolonged or significant eye irritation. Thermal burns may result if heated material contacts eye.
Ingestion	: Ingestion of this product is not a likely route of exposure.
Carcinogenicity:	
IARC NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen
	by NTP.

SAFETY DATA SHEET

Version 3.4

Revision Date 2019-10-10

TION 3: Composition/inform			.9.00.0110		
Component			CAS-No.	Weight %	
Polyethylene Hexene Copoly	mer		25213-02-9	99 - 100	
				<u> </u>	
TION 4: First aid measures					
If inhaled	f	umes f		f accidental inhalation combustion. If sympt	
In case of skin contact	i	mmedi	ate medical attention	on skin, quickly cool in on. Do not try to peel t se solvents or thinners	he solidified
In case of eye contact			ase of contact with r and seek medica	eyes, rinse immediate advice.	ely with plenty
If swallowed	: [Do not	induce vomiting wi	hout medical advice.	
TION 5: Firefighting measu	res				
Flash point	: 1	lo data	available		
Autoignition temperature	: N	lo data	available		
Suitable extinguishing media	F f s c e	Foam. ogging applica surface create a extingu	If possible, water so nozzle since this is tion of high velocity layer. Avoid the u a dust cloud and th ishing measures th	nemical. Carbon dioxi hould be applied as a s a surface burning ma water will spread the se of straight streams e risk of a dust explosi at are appropriate to k rounding environment	spray from a aterial. The burning that may on. Use ocal
Specific hazards during fire fighting	e	explosi		by flame propagation o by the accumulation o	
Special protective equipment for fire-fighters				quipment. Wear self-c efighting if necessary.	ontained
Further information	: 1	This ma	aterial will burn alth	ough it is not easily igr	nited.
Fire and explosion protection	c F	lispers	ed in air in sufficier ce of an ignition so	urn. Avoid generating it concentrations, and urce is a potential dust	in the
Hazardous decomposition products	F	oroduce	e carbon monoxide	carbon dioxide, water , other hydrocarbons a ducts (ketones, aldeh)	ind

SAFETY DATA SHEET

Version 3.4

Revision Date 2019-10-10

acids) depending on temperature and air availability. Incomplete combustion can also produce formaldehyde.

SECTION 6: Accidental release measures

Personal precautions	:	Sweep up to prevent slipping hazard. Avoid breathing dust. Avoid dust formation.
Environmental precautions	:	Do not contaminate surface water. Prevent product from entering drains.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum.
Additional advice	:	Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).

SECTION 7: Handling and storage

Handling

Advice on safe handling	:	Use good housekeeping for safe handling of the product. Keep out of water sources and sewers.
		Spilled pellets and powders may create a slipping hazard.
		Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient. At elevated temperatures (>350°F, >177°C), polyethylene can release vapors and gases, which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. These substances may include acetaldehyde, acetone, acetic acid, formic acid, formaldehyde and acrolein. Based on animal data and limited epidemiological evidence, formaldehyde has been listed as a carcinogen. Following all recommendations within this SDS should minimize exposure to thermal processing emissions.
Advice on protection against fire and explosion	:	Treat as a solid that can burn. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Storage		
Requirements for storage areas and containers	:	Keep in a dry place. Keep in a well-ventilated place.
Advice on common storage	:	Do not store together with oxidizing and self-igniting products.
SDS Number:10000000581		4/12

Marlex® 7308DK Polyethylene

Version 3.4

Revision Date 2019-10-10

SECTION 8: Exposure controls/personal protection

Ingredients with workplace control parameters

US

Components	Basis	Value	Control parameters	Note
Nuisance Dust	OSHA Z-3	TWA	15 mg/m3	Total dust
	OSHA Z-3	TWA	5 mg/m3	(respirable dust)

Control as Particulate Not Otherwise Classified (PNOC). The ACGIH Guideline* for respirable dust is 3.0 mg/m3 and 10.0 mg/m3 for total dust. The OSHA PEL for respirable dust is 5.0 mg/m3 and 15.0 mg/m3 for total dust. * This value is for inhalable (total) particulate matter containing no asbestos and < 1.0% crystalline silica.

Engineering measures

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection	:	No respiratory protection is normally required. If heated material generates vapor or fumes that are not adequately controlled by ventilation, wear an appropriate respirator. Use the following elements for air-purifying respirators: Organic Vapor and Formaldehyde. Use a positive pressure, air- supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection. Dust safety masks are recommended when the dust concentration is excessive.
Eye protection	:	Use of safety glasses with side shields for solid handling is good industrial practice. If this material is heated, wear chemical goggles or safety glasses with side shields or a face shield. If there is potential for dust, use chemical goggles.
Skin and body protection	:	At ambient temperatures use of clean and protective clothing is good industrial practice. If the material is heated or molten, wear thermally insulated, heat-resistant gloves that are able to withstand the temperature of the molten product. If this material is heated, wear insulated clothing to prevent skin contact if engineering controls or work practices are not adequate.
SECTION 9: Physical and cher	nica	I properties

Appearance	
Form Physical state Color Odor Odor Threshold	 Pellets Solid Opaque Mild to no odor No data available
Safety data	

sion 3.4	Revision Date 2019-10-
Flash point	: No data available
Lower explosion limit	: Not applicable
Upper explosion limit	: Not applicable
Autoignition temperature	: No data available
Thermal decomposition	: Low molecular weight hydrocarbons, alcohols, aldehydes, acids and ketones can be formed during thermal processing.
рН	: Not applicable
Melting point/range	: 90 - 140 °C (194 - 284 °F)
Freezing point	Not applicable
Initial boiling point and boiling	: Not applicable
range Vapor pressure	: Not applicable
Relative density	: Not applicable
Density	 0.91 - 0.97 g/cm3 Please refer to the Technical Data Sheet (TDS) for more detailed information relating to the nominal physical properties, including density, of this polyethylene resin grade.
Water solubility	: Negligible
Partition coefficient: n-	: No data available
octanol/water Solubility in other solvents	: No data available
Viscosity, dynamic	: Not applicable
Viscosity, kinematic	: Not applicable
Relative vapor density	: Not applicable
Evaporation rate	: Not applicable
CTION 10: Stability and reactiv	/ity
Reactivity	: This material is considered non-reactive under normal ambient and anticipated storage and handling conditions of

: This material is considered non-reactive under normal ambient and anticipated storage and handling conditions of temperature and pressure.

SDS Number:10000000581

hylene
Revision Date 2019-10-1
: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
tions
: Avoid prolonged storage at elevated temperature.
: Avoid contact with strong oxidizing agents.
: Low molecular weight hydrocarbons, alcohols, aldehydes, acids and ketones can be formed during thermal processing.
: Normal combustion forms carbon dioxide, water vapor and may produce carbon monoxide, other hydrocarbons and hydrocarbon oxidation products (ketones, aldehydes, organic acids) depending on temperature and air availability. Incomplete combustion can also produce formaldehyde.
: No decomposition if stored and applied as directed.
nation
e : Presumed Not Toxic
e : Presumed Not Toxic
e : Presumed Not Toxic
e : No skin irritation
e : No eye irritation
e : Did not cause sensitization on laboratory animals.
 This product contains POLYMERIZED OLEFINS. During thermal processing (>350°F, >177°C) polyolefins can release vapors and gases (aldehydes,ketones and organic acids) which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. Generally these irritant effects are all transitory. However, prolonged exposure to irritating off-gases can lead to pulmonary edema. Formaldehyde (an aldehyde) has been classified as a carcinogen based on animal data and limited epidemiological evidence.
which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. Generally these irritant effects are a transitory. However, prolonged exposure to irritating off-gases can lead to pulmonary edema. Formaldehyde (an aldehyde) has been classified as a carcinogen based on animal data and

Version 3.4

SECTION 12: Ecological information

Ecotoxicity effects

Biodegradability: This material is not expected to be readily biodegradable.Elimination information (persistence and degradability)Bioaccumulation: Does not bioaccumulate.Mobility: The product is insoluble and floats on water.Additional ecological
information: This material is not expected to be harmful to aquatic
organisms., Fish or birds may eat pellets which may obstruct

their digestive tracts.

Ecotoxicology Assessment

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

SDS Number:10000000581

8/12

rlex® 7308DK Poly	SAFETY DATA SHI ethviene
sion 3.4	Revision Date 2019-10
NOT REGULATED AS A	A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR THIS AGENCY.
	ANGEROUS GOODS BY ROAD (EUROPE)) A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR THIS AGENCY.
DANGEROUS GOODS (EL	A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR
OF DANGEROUS GOODS	MENT CONCERNING THE INTERNATIONAL CARRIAGE BY INLAND WATERWAYS) A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR THIS AGENCY.
TION 15: Regulatory inform	Annex II of MARPOL 73/78 and the IBC Code
National legislation SARA 311/312 Hazards	: Combustible dust
CERCLA Reportable Quantity	: This material does not contain any components with a CERCLA RQ.
SARA 302 Reportable Quantity	: This material does not contain any components with a SARA 302 RQ.
SARA 302 Threshold Planning Quantity	: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 304 Reportable Quantity	: This material does not contain any components with a section 304 EHS RQ.
SARA 313 Components	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
	reporting levels established by SARA Title III, Section 313.

SAFETY DATA SHEET

Version 3.4

Revision Date 2019-10-10

Clean Air Act	
Potential Class I	oduct neither contains, nor was manufactured with a Class I or I ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR opt. A, App.A + B).
This product does not contain Act Section 112 (40 CFR 61).	any hazardous air pollutants (HAP), as defined by the U.S. Clean A
	any chemicals listed under the U.S. Clean Air Act Section 112(r) for n (40 CFR 68.130, Subpart F).
This product does not contain Intermediate or Final VOC's (4	any chemicals listed under the U.S. Clean Air Act Section 111 SOC 40 CFR 60.489).
US State Regulations	
Pennsylvania Right To Know	: No components are subject to the Pennsylvania Right to Know Act.
New Jersey Right To Know	: No components are subject to the New Jersey Right to Know Act.
California Prop. 65 Components	: This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.
Notification status Europe REACH	: A substance or substances in this product is not registered or notified to be registered. Importation or manufacture of this product is still permitted provided that it does not exceed the REACH minimum threshold
Switzerland CH INV United States of America (US TSCA Canada DSL	 quantity of the non-regulated substances. On the inventory, or in compliance with the inventory A) On or in compliance with the active portion of the TSCA inventory All components of this product are on the Canadian DSL
Australia AICS New Zealand NZIoC Japan ENCS Korea KECI	 On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations.

SAFETY DATA SHEET Marlex® 7308DK Polyethylene Version 3.4 Revision Date 2019-10-10 Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance. Philippines PICCS On the inventory, or in compliance with the inventory ÷ On the inventory, or in compliance with the inventory China IECSC ÷ Taiwan TCSI On the inventory, or in compliance with the inventory **SECTION 16: Other information NFPA Classification** : Health Hazard: 0 Fire Hazard: 1 Reactivity Hazard: 0 0 0

Further information

Legacy SDS Number : 240370

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

ACGIH	American Conference of	LD50	Lethal Dose 50%
	Government Industrial Hygienists		
AICS	Australia, Inventory of Chemical	LOAEL	Lowest Observed Adverse Effe
	Substances		Level
DSL	Canada, Domestic Substances	NFPA	National Fire Protection Agenc
	List		
NDSL	Canada, Non-Domestic	NIOSH	National Institute for Occupatio
	Substances List		Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of
			Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect
			Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentra
EGEST	EOSCA Generic Exposure	OSHA	Occupational Safety & Health
	Scenario Tool		Administration
EOSCA	European Oilfield Specialty	PEL	Permissible Exposure Limit
	Chemicals Association		
EINECS	European Inventory of Existing	PICCS	Philippines Inventory of
	Chemical Substances		Commercial Chemical Substan
MAK	Germany Maximum Concentration	PRNT	Presumed Not Toxic
	Values		
GHS	Globally Harmonized System	RCRA	Resource Conservation Recov
		•	•

Marlex® 7308DK Polyethylene

Version 3.4

Revision Date 2019-10-10

			Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

12/12