



# Chevron Phillips Chemical Company Issued Sales Specification

**Name of Product**  
**DIESEL 2007 ULS FUEL**

**Revision Date**  
**7/1/2020**

Chevron Phillips Chemical Company LP  
10001 Six Pines Drive  
The Woodlands, TX 77380  
800-858-4327  
Technical Service: 832-813-4862

Chevron Phillips Chemicals International N.V.  
Airport Plaza - Stockholm Building  
Leonardo Da Vincilaan 19  
1831 Diegem, Belgium  
+32 6891211

Chevron Phillips Chemicals Asia PTE Ltd.  
1 Harbour Front Avenue  
#09-01 Keppel Bay Tower  
Singapore 098632  
+65 6517 3100

Test	Units	Method	Typical	Minimum	Maximum	Qualitative	Note
API Gravity	---	ASTM D-4052	---	34.0	37.0	---	---
Aromatics	LV%	ASTM D-1319	---	---	---	---	REPORT
Biodiesel Content, wtpct	WT%	ASTM D-7371	---	---	---	---	REPORT
Carbon	WT%	ASTM D-5291	---	---	---	---	REPORT
Carbon	WT%	Calculated	---	---	---	---	REPORT
Cetane Index	---	ASTM D-976	---	42.0	48.0	---	---
Cetane Number	---	ASTM D-613	---	43	47	---	---
Cloud Point	FAH	ASTM D-2500	---	---	---	---	REPORT
Distillation - 5%	FAH	ASTM D-86	---	---	---	---	REPORT
Distillation - 10%	FAH	ASTM D-86	---	400	460	---	---
Distillation - 20%	FAH	ASTM D-86	---	---	---	---	REPORT
Distillation - 30%	FAH	ASTM D-86	---	---	---	---	REPORT
Distillation - 40%	FAH	ASTM D-86	---	---	---	---	REPORT
Distillation - 50%	FAH	ASTM D-86	---	470	540	---	---
Distillation - 60%	FAH	ASTM D-86	---	---	---	---	REPORT
Distillation - 70%	FAH	ASTM D-86	---	---	---	---	REPORT
Distillation - 80%	FAH	ASTM D-86	---	---	---	---	REPORT
Distillation - 90%	FAH	ASTM D-86	---	560	630	---	---
Distillation - 95%	FAH	ASTM D-86	---	---	---	---	REPORT
Distillation - EP	FAH	ASTM D-86	---	610	690	---	---
Distillation - IBP	FAH	ASTM D-86	---	340	400	---	---
Distillation - Loss	ML	ASTM D-86	---	---	---	---	REPORT
Distillation - Residue	ML	ASTM D-86	---	---	---	---	REPORT
Flash Point, PM	FAH	ASTM D-93	---	130	---	---	---
HFRR Lubricity 3Dec	mm	ASTM D-6079	---	---	---	---	REPORT
Hydrogen	WT%	ASTM D-3343	---	---	---	---	REPORT
Hydrogen	WT%	ASTM D-5291	---	---	---	---	REPORT
Net Heat of Combustion	BTU/LB	ASTM D-3338	---	---	---	---	REPORT
Net Heat of Combustion_D4809	BTU/LB	ASTM D-4809	---	---	---	---	REPORT
Nitrogen	WT%	ASTM D-5291	---	---	---	---	REPORT
Olefins	LV%	ASTM D-1319	---	---	---	---	REPORT
Particulate Matter	mg/l	ASTM D-6217	---	---	15.0	---	---
Polynuclear Aromatics	WT%	ASTM D-5186	---	---	---	---	REPORT
Pour Point	FAH	ASTM D-97	---	---	---	---	REPORT

## Printed versions of this document are uncontrolled

Notice: Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. Chevron Phillips Chemical Company LP does not make and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user.

Saturates	LV%	ASTM D-1319	---	---	---	---	REPORT
SFC Aromatics	WT%	ASTM D-5186	---	28.0	32.0	---	---
Specific Gravity 60/60	---	ASTM D-4052	---	0.8400	0.8550	---	---
Sulfur	ppm	ASTM D-5453	---	7.0	15.0	---	---
Sulfur	ppm	ASTM D-7039	---	---	---	---	REPORT
Viscosity @ 40C	cSt	ASTM D-445	---	2.0	2.6	---	---

## Printed versions of this document are uncontrolled

Notice: Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. Chevron Phillips Chemical Company LP does not make and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user.