

**Sulfur Calibration Standard**

Version 2.6

Revision Date 2021-08-12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : Sulfur Calibration Standard
Material : 1101143, 1024585, 1024589, 1024588, 1024587, 1024586

Company : Chevron Phillips Chemical Company LP
Specialty Chemicals
10001 Six Pines Drive
The Woodlands, TX 77380

Emergency telephone:**Health:**

866.442.9628 (North America)
1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)
Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Mexico CHEMTREC 01-800-681-9531 (24 hours)
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600
Argentina: +(54)-1159839431

Responsible Department : Product Safety and Toxicology Group
E-mail address : SDS@CPChem.com
Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Classification

: Flammable liquids, Category 4
Acute toxicity, Category 3, Inhalation
Skin irritation, Category 2
Eye irritation, Category 2A
Specific target organ toxicity - single exposure, Category 3,
Central nervous system

Sulfur Calibration Standard

Version 2.6

Revision Date 2021-08-12

Labeling

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H227: Combustible liquid.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H331: Toxic if inhaled.
 H336: May cause drowsiness or dizziness.

Precautionary Statements

: **Prevention:**
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
 P264 Wash skin thoroughly after handling.
 P280 Wear protective gloves/ eye protection/ face protection.
Response:
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity:**IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Sulfur Calibration Standard

Version 2.6

Revision Date 2021-08-12

SECTION 3: Composition/information on ingredients

Synonyms : Dinormal Butyl Sulfide
normal-Butyl Sulfide
5-Thianonane
DNBS
n-Butyl Sulfide
1,1-Thiobisbutane

Molecular formula : C8H18S

Component	CAS-No.	Weight %
n-Butyl Sulfide	544-40-1	95 - 100

May contain Di-sec-butyl sulfide up to 5 wt%.

SECTION 4: First aid measures

General advice : Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Call a physician or poison control center immediately. If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5: Firefighting measures

Flash point : 65.56°C (150.01°F)
Method: ASTM D 93

Autoignition temperature : 216°C (421°F)

Suitable extinguishing media : Carbon dioxide (CO₂).

Unsuitable extinguishing media : High volume water jet.

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Special protective : Wear self-contained breathing apparatus for firefighting if

Sulfur Calibration Standard

Version 2.6

Revision Date 2021-08-12

- equipment for fire-fighters : necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.
- Hazardous decomposition products : Carbon oxides. Sulfur oxides.

SECTION 6: Accidental release measures

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage**Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.

Storage

- Requirements for storage areas and containers : Prevent unauthorized access. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Sulfur Calibration Standard

Version 2.6

Revision Date 2021-08-12

SECTION 8: Exposure controls/personal protection**Engineering measures**

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

- Respiratory protection : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Full-Face Supplied-Air Respirator. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Flame retardant protective clothing. Personal protection through wearing a tightly closed chemical protection suit and a self-contained breathing apparatus. Footwear protecting against chemicals.
- Hygiene measures : Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- Form : liquid
Physical state : liquid

Sulfur Calibration Standard

Version 2.6

Revision Date 2021-08-12

Color : Clear
Odor : Repulsive

Safety data

Flash point : 65.56°C (150.01°F)
Method: ASTM D 93

Lower explosion limit : 0.8 %(V)
Upper explosion limit : 6.8 %(V)

Oxidizing properties : No

Autoignition temperature : 216°C (421°F)

Molecular formula : C8H18S

Molecular weight : 146.32 g/mol

pH : No data available

Freezing point : -75°C (-103°F)

Boiling point/boiling range : 180-191°C (356-376°F)

Vapor pressure : 0.10 PSI
at 38°C (100°F)

Relative density : 0.84
at 15.6 °C (60.1 °F)

Density : 841.2 g/l
at 16°C (60°F)

Water solubility : negligible

Viscosity, dynamic : 1.05 cP
at 20°C (68°F)

Relative vapor density : 5.07
(Air = 1.0)

Evaporation rate : 1

Percent volatile : > 99 %

SECTION 10: Stability and reactivity

Reactivity : Stable under recommended storage conditions.

Sulfur Calibration Standard

Version 2.6

Revision Date 2021-08-12

- Chemical stability** : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
- Possibility of hazardous reactions**
- Hazardous reactions** : Hazardous reactions: Hazardous polymerization does not occur.
- Further information: No decomposition if stored and applied as directed.
- Hazardous reactions: Vapors may form explosive mixture with air.
- Conditions to avoid** : Heat, flames and sparks.
- Materials to avoid** : Avoid oxidizing agents.
- Hazardous decomposition products** : Carbon oxides
Sulfur oxides
- Other data** : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Acute oral toxicity**

n-Butyl Sulfide : LD50: 2,220 mg/kg
Species: Rat

Acute inhalation toxicity

n-Butyl Sulfide : LC50: 3.7 mg/l
Exposure time: 4 h
Species: Mouse
Test atmosphere: vapor

Acute dermal toxicity

n-Butyl Sulfide : LD50: > 5,000 mg/kg
Species: Rabbit

Skin irritation

n-Butyl Sulfide : Skin irritation

Eye irritation

n-Butyl Sulfide : Eye irritation

Sensitization

Sulfur Calibration Standard

Version 2.6

Revision Date 2021-08-12

n-Butyl Sulfide : Not a skin sensitizer.

**Sulfur Calibration Standard
Aspiration toxicity** : May be harmful if swallowed and enters airways.

**Sulfur Calibration Standard
Further information** : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

SECTION 12: Ecological information**Toxicity to fish**

n-Butyl Sulfide : 3.5 mg/l
Exposure time: 96 h
Species: Fish
Method: QSAR modeled data

Toxicity to daphnia and other aquatic invertebrates

n-Butyl Sulfide : 1.71 mg/l
Exposure time: 48 h
Species: Daphnia
Method: QSAR modeled data

Biodegradability

n-Butyl Sulfide : This material is not expected to be readily biodegradable.

Bioaccumulation

n-Butyl Sulfide : This material is not expected to bioaccumulate.

Mobility

n-Butyl Sulfide : No data available

Additional ecological information : Toxic to aquatic life with long lasting effects.

Ecotoxicology Assessment**Short-term (acute) aquatic hazard**

n-Butyl Sulfide : Toxic to aquatic life.

Long-term (chronic) aquatic hazard

n-Butyl Sulfide : Toxic to aquatic life with long lasting effects.

Sulfur Calibration Standard

Version 2.6

Revision Date 2021-08-12

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

- Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

NA1993, COMBUSTIBLE LIQUID, N.O.S., (N-BUTYL SULFIDE, DI-SEC-BUTYL SULFIDE), III

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (N-BUTYL SULFIDE), 9, III, (65.56°C), MARINE POLLUTANT, (N-BUTYL SULFIDE)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN3334, AVIATION REGULATED LIQUID, N.O.S., (N-BUTYL SULFIDE), 9, III

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (N-BUTYL SULFIDE), 9, III, (-)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (N-BUTYL SULFIDE), 9, III

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (N-BUTYL

Sulfur Calibration Standard

Version 2.6

Revision Date 2021-08-12

SULFIDE), 9, III

Maritime transport in bulk according to IMO instruments**SECTION 15: Regulatory information****National legislation**

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Serious eye damage or eye irritation

CERCLA Reportable Quantity : This material does not contain any components with a CERCLA RQ.

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : This material does not contain any components with a section 302 EHS TPQ.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Components : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

Sulfur Calibration Standard

Version 2.6

Revision Date 2021-08-12

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

US State Regulations

Pennsylvania Right To Know


: n-Butyl Sulfide - 544-40-1
sec-Butyl Sulfide - 626-26-6

Notification status

Europe REACH	:	A substance or substances in this product is not registered or notified to be registered. Importation or manufacture of this product is still permitted provided that it does not exceed the REACH minimum threshold quantity of the non-regulated substances.
Switzerland CH INV	:	On the inventory, or in compliance with the inventory
United States of America (USA) TSCA	:	On or in compliance with the active portion of the TSCA inventory
Canada DSL	:	All components of this product are on the Canadian DSL
Other AIIC	:	Not in compliance with the inventory
New Zealand NZIoC	:	On the inventory, or in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECI	:	A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s).
Philippines PICCS	:	On the inventory, or in compliance with the inventory
Taiwan TCSI	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 2
Fire Hazard: 2
Reactivity Hazard: 0



Sulfur Calibration Standard

Version 2.6

Revision Date 2021-08-12

Further information

Legacy SDS Number : 42960

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		