

**Diesel No. 2 Test Fuel**

Version 1.11

Revision Date 2021-12-07

MSDS number: AA00974-0000000124

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product Name : Diesel No. 2 Test Fuel
Material : 1126733, 1126729, 1126732, 1126728, 1126711, 1126727,
1126710, 1126726, 1126205, 1125693, 1124271, 1101406,
1117144, 1114932, 1114380, 1114379, 1111796, 1111792,
1111793, 1111721, 1108397, 1097307, 1096433, 1083233,
1096612, 1084817, 1097324, 1097322, 1097310, 1089768,
1079939, 1097309, 1090864, 1077073, 1077061, 1090863,
1069145, 1100027, 1099634, 1090866, 1099603, 1090314,
1097785, 1087561, 1092489, 1076410, 1102501, 1097387,
1090432, 1090433, 1100452, 1097386, 1078955, 1100842,
1077075, 1097308, 1100531, 1069147, 1090862, 1078060,
1077077, 1068920, 1078988, 1017963, 1017962, 1036152,
1024299, 1024300, 1017964, 1024301, 1017977, 1024303,
1017981, 1017980, 1017965, 1017978, 1017967, 1017966,
1017979, 1024297, 1024293, 1029744, 1024292, 1017982,
1024294, 1024296, 1024302, 1024304, 1024309, 1024308,
1024307, 1024306, 1024295, 1024305, 1024298, 1029490,
1104964, 1104939, 1104952, 1104938, 1104941, 1104963,
1104956, 1104955, 1104953

Recommended use of the product : Fuel
Restrictions on use : None known.

Address : Chevron Phillips Chemical Company LP
Specialty Chemicals
10001 Six Pines Drive
The Woodlands, TX 77380

Address : CHEVRON PHILLIPS CHEMICALS ASIA PTE. LTD.
C/O DONG WOO CORPORATION
#B-2601, JEONGJAIL-RO,
BUNDANG-GU, SEONGNAMI-SI,
GYEONGGI-DO, 13557
SOUTH KOREA

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

Telephone no.: +612-9186-1132

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

Responsible Department : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com
 Appointees : 회사명: 리이치 24 시코리아(주).

주소: 서울시 서초구 헌릉로 7,

외국기업창업지원연구센터

(IKP) 908-909호

전화: + 82-1067838981

SECTION 2: Hazards identification**Hazard classification**

**Standards for classification and labeling of chemical substances and material safety data sheet
 (ministry of employment and labor public notice No. 2020-130)**

Classification





: Flammable liquids, Category 3
 Acute toxicity, Category 4, Inhalation
 Skin corrosion/irritation, Category 2
 Carcinogenicity, Category 2
 Specific target organ toxicity - repeated exposure, Category 2,
 Liver, Blood, thymus
 Aspiration hazard, Category 1
 Long-term (chronic) aquatic hazard, Category 2

Warning label elements including precautionary statements

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

Symbol(s)	:	   
Signal Word	:	Danger
Hazard Statements	:	H226: Flammable liquid and vapor. H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation. H332: Harmful if inhaled. H351: Suspected of causing cancer. H373: May cause damage to organs (Liver, Blood, thymus) through prolonged or repeated exposure. H411: Toxic to aquatic life with long lasting effects.
Precautionary Statements	:	Prevention: P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P210: Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P240: Ground/bond container and receiving equipment. P241: Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242: Use only non-sparking tools. P243: Take precautionary measures against static discharge. P260: Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. P264: Wash the contact area thoroughly after handling. P273: Avoid release to the environment. P280: Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P308 + P313: IF exposed or concerned: Get medical advice/ attention. P321: Specific treatment (see supplemental first aid instructions on this label). P331: Do NOT induce vomiting. P362 + P364: Take off contaminated clothing and wash it before reuse. P370 + P378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P391: Collect spillage. Storage: P403 + P235: Store in a well-ventilated place. Keep cool. Disposal: P501: Dispose of contents and container according to wastes control act.

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

Other hazards which do not result in classification : None

SECTION 3: Composition/information on ingredients

Synonyms : Diesel 0.05 LS Emiss Cert Test Fuel- Cummins
 Diesel CEC (RF-73-T-90)
 Diesel Reference Fuels, Diesel Cert Fuel, Oil Classification
 Diesel
 Diesel 2007 Emission Certification Fuel
 Diesel Euro-II Cert Fuel
 Diesel Euro-IV Cert Fuel
 Diesel 0.05 LS Emiss Cert Test Fuel- ITE
 PC-10 Diesel Test Fuel
 Locomotive Diesel Certification Fuel
 Diesel Euro-III Cert Fuel
 Diesel Special Test Fuel
 Diesel CEC (RF-03-A-84)
 Ultra High Cetane Check Fuel (ASTM) Diesel
 Diesel 2004 Tier 2 Fuel
 0.05% Sulfur Diesel Fuel - JASO
 No Sulfur (less than 3 PPM) Diesel Test Fuel
 Diesel Caterpillar F173
 Diesel Caterpillar 1E2973
 Caterpillar China Certification Diesel Fuel Stage III

Molecular formula : UVCB

Common name	Synonyms	CAS-No.	Concentration	KECI Number
Diesel fuel, no. 2	Fuels, diesel, no. 2	68476-34-6	100%	KE-17287
Naphthalene	naphthalene	91-20-3	0 % - 1%	KE-25545

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

Number:100000013879

4/19

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
- If swallowed : Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

Other cautions for Doctors

- Symptoms : No information available.
- Risks : No information available.
- Treatment : No information available.

SECTION 5: Firefighting measures

- Flash point : 47°C (117°F)
minimum
- Autoignition temperature : No data available
- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
- Do not spray on a naked flame or any incandescent material.

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

Hazardous decomposition products : Hydrocarbons. Carbon oxides.

SECTION 6: Accidental release measures

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition. Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

Secure storage

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Uses advised against : None known.

Specific Use : Fuel

SECTION 8: Exposure controls/personal protection**KR**

Components	Basis	Value	Control parameters	Note
Naphthalene	KR OEL	TWA	10 ppm,	carc 2, Skin,
	KR OEL	STEL	15 ppm,	carc 2, Skin,

carc 2 Limited evidence of carcinogenicity in humans or animals, which is not sufficiently convincing to place the substance in Category 1
 Skin Substances designated by 'Skin' may be absorbed into the bloodstream through the skin, mucous membrane and eye and contribute to the overall effect. (Skin notation does not apply to the skin irritant)

Chemical exposure standards, biological exposure standards, etc.

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties**

Appearance

Physical state	: liquid
Color	: Pale yellow to brown (if undyed), red to purple (dyed)
Odor	: Mild
Odor Threshold	: No data available
pH	: Not applicable
Pour point	: No data available
Melting point/freezing point	No data available
Boiling point/boiling range	: 191-343°C (376-649°F)
Flash point	: 47°C (117°F) minimum
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Vapor pressure	: No data available
Solubility	: negligible
Relative density	: 0.87 at 16 °C (61 °F)
Density	: 0.75 - 0.90 g/cm ³
Vapor density	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available

Number:100000013879

8/19

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

Decomposition temperature : No data available

Viscosity, kinematic : 2.55 cSt
at 40°C (104°F)

Molecular weight : Not applicable

SECTION 10: Stability and reactivity

Reactivity : Stable under recommended storage conditions.

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Possibility of hazardous reactions

Hazardous reactions : Hazardous reactions: Hazardous polymerization does not occur.

Hazardous reactions: Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Thermal decomposition : No data available

Hazardous decomposition products : Hydrocarbons
Carbon oxides

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Information on exposure routes****Acute oral toxicity**

Diesel fuel, no. 2 : LD50: > 5,000 mg/kg
Species: Rat
Sex: male and female
Method: OECD Test Guideline 401

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

Naphthalene

LD50: 500 mg/kg
Method: Converted acute toxicity point estimate**Acute inhalation toxicity**

Diesel fuel, no. 2

: LC50: 4.1 mg/l
Exposure time: 4 h
Species: Rat
Sex: male and female
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Test substance: yes**Acute dermal toxicity**

Diesel fuel, no. 2

: LD50 Dermal: > 4,300 mg/kg
Species: Rabbit
Sex: male and female
Test substance: yes**Diesel No. 2 Test Fuel****Skin corrosion or irritation**

: Skin irritation

Diesel No. 2 Test Fuel**Eye corrosion or irritation**

: Vapors may cause irritation to the eyes, respiratory system and the skin.

Diesel No. 2 Test Fuel**Respiratory Sensitization**

: No data available

Diesel No. 2 Test Fuel**Skin sensitization**

Did not cause sensitization on laboratory animals.

Carcinogenicity

Diesel fuel, no. 2

: Species: Mouse
Sex: male
Dose: 0, 25 ul
Exposure time: lifetime
Number of exposures: 3 times/wk
Remarks: Moderate dermal carcinogen

Naphthalene

Species: Mouse
Sex: male
Dose: 10, 30 ppm
Exposure time: 105 weeks
Number of exposures: 6 hours/day, 5 days/week
Test substance: yes
Print Date: No information available.
Remarks: No evidence of carcinogenicity

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

Species: Mouse
 Sex: female
 Dose: 10, 30 ppm
 Exposure time: 105 weeks
 Number of exposures: 6 hours/day, 5 days/week
 Test substance: yes
 Print Date: No information available.
 Remarks: increased incidence of alveolar/bronchiolar adenomas

Species: Rat
 Sex: male and female
 Dose: 10, 30, 60 ppm
 Exposure time: 105 weeks
 Number of exposures: 6 hours/day, 5 days/week
 Test substance: yes
 Print Date: No information available.
 Remarks: nose respiratory epithelial adenoma, increased incidence of olfactory neuroblastomas

Repeated dose toxicity

Diesel fuel, no. 2 : Species: Rat, Male and female
 Sex: Male and female
 Application Route: Dermal
 Dose: 0, 30, 125, 500 mg/kg
 Exposure time: 13 wks
 Number of exposures: daily, 5 days/week
 NOEL: 30 mg/kg
 Method: OECD Guideline 411
 Target Organs: Thymus, Liver, Bone marrow
 Information given is based on data obtained from similar substances.

Species: Rat, Male and female
 Sex: Male and female
 Application Route: inhalation (dust/mist/fume)
 Dose: 0, 0.35, 0.88, 1.71 mg/l
 Exposure time: 13 wks
 Number of exposures: Twice/wk
 NOEL: > 1.71 mg/l
 Method: OECD Guideline 413

Germ cell mutagenicity (in vitro)

Diesel fuel, no. 2 : Test Type: Ames test
 Result: positive
 Test Type: Mouse lymphoma assay
 Result: negative

Naphthalene Test Type: Ames test

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

Result: negative

Test Type: Sister Chromatid Exchange Assay

Result: negative

Test Type: Unscheduled DNA synthesis assay

Result: negative

Germ cell mutagenicity (in vivo)

Diesel fuel, no. 2 : Test Type: Dominant lethal assay
 Species: Mouse
 Dose: 100 or 400 ppm
 Result: negative

Naphthalene Test Type: Mouse micronucleus assay
 Result: negative

Developmental Toxicity

Diesel fuel, no. 2 : Species: Rat
 Application Route: Inhalation
 Dose: 0, 86.9, 408.8 ppm
 Number of exposures: 6 h/d
 Test period: GD 6-15
 Method: OECD Guideline 414
 NOAEL Teratogenicity: 408.8 ppm
 NOAEL Maternal: 408.8 ppm
 Information given is based on data obtained from similar substances.

Species: Rat
 Application Route: Dermal
 Dose: 30, 125, 500, 1000 mg/kg
 Exposure time: daily
 Test period: GD 0-20
 Method: OECD Guideline 414
 NOAEL Teratogenicity: 125 mg/kg
 Information given is based on data obtained from similar substances.

Naphthalene Species: Rabbit
 Application Route: oral gavage
 Dose: 40, 200, 400 mg/kg
 Test period: 29 d, GD 6-18
 NOAEL Teratogenicity: 400 mg/kg

**Specific Target Organ
Toxicity (Single Exposure)**

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

	Not classified due to data which are conclusive although insufficient for classification.
Specific Target Organ Toxicity (Repeated Exposure)	May cause damage to organs through prolonged or repeated exposure.
Diesel No. 2 Test Fuel Aspiration toxicity	: May be fatal if swallowed and enters airways.
CMR effects	
Diesel fuel, no. 2	: Carcinogenicity: Limited evidence of carcinogenicity in animal studies Teratogenicity: Animal testing did not show any effects on fetal development.
Naphthalene	Carcinogenicity: Limited evidence of carcinogenicity in animal studies
Diesel No. 2 Test Fuel Further information	: Solvents may degrease the skin.

SECTION 12: Ecological information

Ecological Toxicity

Toxicity to fish

Diesel fuel, no. 2 : LL50: 21 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)
semi-static test Method: OECD Test Guideline 203

Naphthalene LC50: 3.2 mg/l
Exposure time: 96 h
Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates

Diesel fuel, no. 2 : EC50: 2 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 202

Naphthalene LC50: 2.16 mg/l
Exposure time: 48 h

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

Species: Daphnia magna (Water flea)

Toxicity to algae

Diesel fuel, no. 2 : ErL50: 22 mg/l
 Exposure time: 72 h
 Species: Raphidocellus subcapitata (algae)
 static test Analytical monitoring: no
 Method: OECD Test Guideline 201

Naphthalene EC50: 2.96 mg/l
 Exposure time: 48 h
 Species: Selenastrum capricornutum (algae)

Persistence and degradability

Diesel fuel, no. 2 : aerobic
 Result: Not readily biodegradable.
 57.5 %
 Testing period: 28 d
 Method: OECD Test Guideline 301F

Bioaccumulative

Diesel fuel, no. 2 : Accumulation in aquatic organisms is expected.

Mobility

Diesel fuel, no. 2 : No data available

Results of PBT assessment

Diesel fuel, no. 2 : Non-classified PBT substance, Non-classified vPvB substance

Other adverse effects : Toxic to aquatic life with long lasting effects.

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Toxic to aquatic life.

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

- Disposal method : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
- Disposal precaution : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

UN Number	:	UN1202
UN Product Shipping Name	:	DIESEL FUEL
Hazard Class	:	3
Packing Group	:	III - Less Hazardous Properties
Marine Pollutant	:	Yes
Special Safety Measures on Mode of Transport	:	No data available

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1202, DIESEL FUEL, 3, III

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1202, DIESEL FUEL, 3, III, (47°C), MARINE POLLUTANT, (DIESEL FUEL)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1202, DIESEL FUEL, 3, III

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

UN1202, DIESEL FUEL, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN1202, DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1202, DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

Maritime transport in bulk according to IMO instruments**SECTION 15: Regulatory information****National legislation****Regulation under the Occupational Safety and Health Act**

A Material Safety Datasheet (MSDS) for this product is not required according to article 41 of the ISHA.

Regulation	Chemical name	Threshold limits
Harmful Substances Prohibited from Manufacturing	:	Not applicable
Harmful Substances Required Permission for Manufacture	:	Not applicable

Act on the Registration and Evaluation, etc. of Chemical Substances, Chemicals Control Act

Regulation	Chemical name	Threshold limits
Toxic Chemicals	:	Not applicable
Prohibited Chemicals	:	Not applicable
Restricted Chemicals	:	Not applicable

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

Toxic Release Inventory	:	naphthalene	>= 0.1 %
-------------------------	---	-------------	----------

Dangerous Substances Safety Management Act

Dangerous Substances : Flammable liquids, Type 2 petroleums, Water insoluble liquid
 Safety Management Act

Regulations by the Waste Management Act : Not applicable

Regulations by other domestic and foreign laws

Europe REACH : This product is in full compliance according to REACH regulation 1907/2006/EC.
 Switzerland CH INV : On the inventory, or in compliance with the inventory
 United States of America (USA) TSCA : On or in compliance with the active portion of the TSCA inventory
 Canada DSL : All components of this product are on the Canadian DSL
 Other AIIC : On the inventory, or in compliance with the inventory
 New Zealand NZIoC : This substance may be used as a single component chemical under an appropriate group standard
 Japan ENCS : On the inventory, or in compliance with the inventory
 Korea KECI : All substances in this product were registered, notified to be registered, or exempted from registration by CPChem through an Only Representative according to K-REACH regulations. Importation of this product is permitted if the Korean Importer of Record was included on CPChem's notifications or if the Importer of Record themselves notified the substances.
 Philippines PICCS : On the inventory, or in compliance with the inventory
 Taiwan TCSI : On the inventory, or in compliance with the inventory
 China IECSC : On the inventory, or in compliance with the inventory

Other regulations : No data available

Diesel No. 2 Test Fuel


Version 1.11

Revision Date 2021-12-07

SECTION 16: Other information

Source of data	:	Korea. GHS based classification
Date of initial writing	:	2021-07-16
Revision number	:	1
Last revision date	:	2021-10-27

NFPA Classification : Health Hazard: 2
Fire Hazard: 2
Reactivity Hazard: 0

**Other information**

None.

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level

Diesel No. 2 Test Fuel

Version 1.11

Revision Date 2021-12-07

EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		