

**SOLTROL® 130 Isoparaffin Solvent**

Version 1.11

Revision Date 2022-07-15

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****Product information**

Product Name : SOLTROL® 130 Isoparaffin Solvent  
Material : 1017343, 1017344, 1017345, 1017346, 1017348, 1017349,  
1017350, 1017351, 1017347

**Company** : Chevron Phillips Chemical Company LP  
Specialty Chemicals  
10001 Six Pines Drive  
The Woodlands, TX 77380

**Emergency telephone:****Health:**

866.442.9628 (North America)  
1.832.813.4984 (International)

**Transport:**

CHEMTREC 800.424.9300 or 703.527.3887(int'l)  
Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090  
Mexico CHEMTREC 01-800-681-9531 (24 hours)  
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600  
Argentina: +(54)-1159839431  
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)  
Belgium: 070 245 245 (24 hours/day, 7 days/week)  
Bulgaria: +359 2 9154 233  
Croatia: +3851 2348 342 (24 hours/day, 7 days/week)  
Cyprus: 1401  
Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402  
Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212  
Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
Finland: 0800 147 111 09 471 977 (24 hours/day)  
France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)  
Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
Greece: (0030) 2107793777 (24 hours/day, 7 days/week)  
Hungary: +36-80-201-199 (24 hours/day, 7 days/week)  
Iceland: 543 2222 (24 hours/day, 7 days/week)  
Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
Italy: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic  
Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371  
67042473. (24 hours.)

**SOLTROL® 130 Isoparaffin Solvent**

Version 1.11

Revision Date 2022-07-15

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
 Lithuania: +370 (85) 2362052  
 Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)  
 Malta: +356 2395 2000  
 The Netherlands: NVIC: +31 (0)88 755 8000  
 Norway: 22 59 13 00 (24 hours/day, 7 days/week)  
 Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)  
 Portugal: CIAV phone number: +351 800 250 250  
 Romania: +40213183606  
 Slovakia: +421 2 5477 4166  
 Slovenia: Phone number: 112  
 Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)  
 Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group  
 E-mail address : SDS@CPChem.com  
 Website : www.CPChem.com

**SECTION 2: Hazards identification****Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

**Classification**

: Flammable liquids, Category 4  
 Aspiration hazard, Category 1

**Labeling**

Symbol(s)

:



Signal Word

: Danger

Hazard Statements

: H227: Combustible liquid.  
 H304: May be fatal if swallowed and enters airways.

Precautionary Statements

: **Prevention:**  
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
 P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P331 Do NOT induce vomiting.  
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
**Storage:**  
 P403 + P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.  
**Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

**SOLTROL® 130 Isoparaffin Solvent**

Version 1.11

Revision Date 2022-07-15

**Carcinogenicity:****IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**NTP**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SECTION 3: Composition/information on ingredients**

Molecular formula : UVCB

Component	CAS-No.	Weight %
C12-C14 Isoalkanes	68551-19-9	100

**SECTION 4: First aid measures**

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
- If inhaled : If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

**SECTION 5: Firefighting measures**

- Flash point : 61°C (142°F)  
Method: Tag closed cup
- Autoignition temperature : 244°C (471°F)
- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>).
- Unsuitable extinguishing media : High volume water jet.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SOLTROL® 130 Isoparaffin Solvent**

Version 1.11

Revision Date 2022-07-15

- Further information : For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.
- Hazardous decomposition products : Carbon oxides.

**SECTION 6: Accidental release measures**

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

**SECTION 7: Handling and storage****Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.

**Storage**

- Requirements for storage areas and containers : No smoking. Keep in a well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8: Exposure controls/personal protection****Ingredients with workplace control parameters****Chevron Phillips Chemical Company LP**

Components	Basis	Value	Control parameters	Note
C12-C14 Isoalkanes	Manufacturer	TWA	1,200 mg/m <sup>3</sup>	RCP,
RCP Reciprocal Calculation Procedure				

SDS Number:100000068462

4/14

**SOLTROL® 130 Isoparaffin Solvent**

Version 1.11

Revision Date 2022-07-15

**US**

Components	Basis	Value	Control parameters	Note
------------	-------	-------	--------------------	------

**Engineering measures**

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**Personal protective equipment**

- Respiratory protection : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant protective clothing. Footwear protecting against chemicals.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**SECTION 9: Physical and chemical properties****Information on basic physical and chemical properties****Appearance**

- Form : liquid  
 Physical state : liquid  
 Color : Colorless at room temperature  
 Odor : Mild, Hydrocarbon

**Safety data**

- Flash point : 61°C (142°F)

**SOLTROL® 130 Isoparaffin Solvent**

Version 1.11

Revision Date 2022-07-15

	Method: Tag closed cup
Lower explosion limit	: 0.68 %(V)
Upper explosion limit	: 5.4 %(V)
Oxidizing properties	: no
Autoignition temperature	: 244°C (471°F)
Thermal decomposition	: No data available
Molecular formula	: UVCB
Molecular weight	: Not applicable
pH	: 7
Pour point	: No data available
Boiling point/boiling range	: 179-210°C (354-410°F)
Vapor pressure	: 2.60 MMHG at 38°C (100°F)
Relative density	: 0.76 at 15.6 °C (60.1 °F)
Water solubility	: negligible
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: 1.5 cSt at 38°C (100°F)
Relative vapor density	: 3 (Air = 1.0)
Evaporation rate	: 1
Percent volatile	: > 99 %

**SECTION 10: Stability and reactivity**

**Reactivity** : Stable under recommended storage conditions.

**Chemical stability** : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**Possibility of hazardous reactions**

**SOLTROL® 130 Isoparaffin Solvent**

Version 1.11

Revision Date 2022-07-15

<b>Hazardous reactions</b>	: Hazardous reactions: Hazardous polymerization does not occur.  Hazardous reactions: Vapors may form explosive mixture with air.
<b>Conditions to avoid</b>	: Heat, flames and sparks.
<b>Materials to avoid</b>	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
<b>Thermal decomposition</b>	: No data available
<b>Hazardous decomposition products</b>	: Carbon oxides
<b>Other data</b>	: No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information****Acute oral toxicity**

C12-C14 Isoalkanes : LD50: > 5,000 mg/kg  
Species: Rat  
Sex: male and female  
Method: OECD Test Guideline 401  
Information given is based on data obtained from similar substances.

**Skin irritation**

C12-C14 Isoalkanes : Repeated exposure may cause skin dryness or cracking.  
May irritate skin. Information given is based on data obtained from similar substances.

**Eye irritation**

C12-C14 Isoalkanes : No eye irritation  
Information given is based on data obtained from similar substances.

**Sensitization**

C12-C14 Isoalkanes : Did not cause sensitization on laboratory animals.  
Information given is based on data obtained from similar substances.

**Repeated dose toxicity**

C12-C14 Isoalkanes : Species: Rat, male and female  
Sex: male and female  
Application Route: oral gavage  
Dose: 100, 500, 1000 mg/kg/d  
Exposure time: 13 wk  
Number of exposures: daily  
NOEL: > 1000 mg/kg/d  
Method: OECD Test Guideline 408  
No adverse effects expected

**SOLTROL® 130 Isoparaffin Solvent**

Version 1.11

Revision Date 2022-07-15

Information given is based on data obtained from similar substances.

Species: Rat, male and female  
Sex: male and female  
Application Route: Inhalation  
Dose: 2600, 5200, 10400 mg/m<sup>3</sup>  
Exposure time: 90 d  
Number of exposures: 6 h/d; 5d/wk  
NOEL: > 10400 mg/m<sup>3</sup>  
Method: OECD Test Guideline 413  
No adverse effects expected  
Information given is based on data obtained from similar substances.

**Genotoxicity in vitro**

C12-C14 Isoalkanes

: Test Type: Ames test  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Mouse lymphoma assay  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Sister Chromatid Exchange Assay  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 479  
Result: negative

**Genotoxicity in vivo**

C12-C14 Isoalkanes

: Test Type: dominant lethal test  
Species: Rat  
Route of Application: Intraperitoneal injection  
Dose: 300, 900 ppm  
Method: OECD Test Guideline 478  
Remarks: Information given is based on data obtained from similar substances.

**Developmental Toxicity**

C12-C14 Isoalkanes

: Species: Rat  
Application Route: Inhalation  
Dose: 0, 400, 1200 ppm  
Exposure time: 6h  
Test period: GD 6-15  
NOAEL Teratogenicity: 1200 ppm  
NOAEL Maternal: 1200 ppm  
Information given is based on data obtained from similar substances.



**SOLTROL® 130 Isoparaffin Solvent**

Version 1.11

Revision Date 2022-07-15

Species: Rat  
 Application Route: Inhalation  
 Dose: 300, 900 ppm  
 Exposure time: 6h  
 Test period: GD 6-15  
 NOAEL Teratogenicity:  $\geq$  900 ppm  
 NOAEL Maternal:  $\geq$  900 ppm  
 Information given is based on data obtained from similar substances.

**Aspiration toxicity**

C12-C14 Isoalkanes : May be fatal if swallowed and enters airways.

**CMR effects**

C12-C14 Isoalkanes : Carcinogenicity: Not available  
 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show mutagenic effects  
 Teratogenicity: Animal testing did not show any effects on fetal development.  
 Reproductive toxicity: Animal testing did not show any effects on fertility.

**SOLTROL® 130 Isoparaffin Solvent**

**Further information** : Solvents may degrease the skin.

**SECTION 12: Ecological information****Toxicity to fish**

C12-C14 Isoalkanes : LL50:  $>$  1,000 mg/l  
 Exposure time: 96 h  
 Species: Oncorhynchus mykiss (rainbow trout)  
 semi-static test Method: OECD Test Guideline 203  
 Information given is based on data obtained from similar substances.

**Toxicity to daphnia and other aquatic invertebrates**

C12-C14 Isoalkanes : EL50:  $>$  1,000 mg/l  
 Exposure time: 48 h  
 Species: Daphnia magna (Water flea)  
 static test Method: OECD Test Guideline 202  
 Information given is based on data obtained from similar substances.

**Toxicity to algae**

C12-C14 Isoalkanes : EL50:  $>$  1,000 mg/l  
 Exposure time: 72 h  
 Species: Pseudokirchneriella subcapitata (green algae)  
 Growth inhibition Method: OECD Test Guideline 201  
 Information given is based on data obtained from similar

**SOLTROL® 130 Isoparaffin Solvent**

Version 1.11

Revision Date 2022-07-15

substances.

**Toxicity to fish (Chronic toxicity)**

C12-C14 Isoalkanes : No data available:

**Biodegradability**

C12-C14 Isoalkanes : aerobic  
 Result: Readily biodegradable.  
 89.8 %  
 Testing period: 28 d  
 Method: OECD Test Guideline 301F  
 Information given is based on data obtained from similar substances.

**Bioaccumulation**

C12-C14 Isoalkanes : The product may be accumulated in organisms.

**Mobility**

C12-C14 Isoalkanes : immobile

**Results of PBT assessment**

C12-C14 Isoalkanes : Non-classified PBT substance, Non-classified vPvB substance

**Additional ecological information**

: This material is not expected to be harmful to aquatic organisms.

**Ecotoxicology Assessment****Short-term (acute) aquatic hazard**

C12-C14 Isoalkanes : This material is not expected to be harmful to aquatic organisms.

**Long-term (chronic) aquatic hazard**

C12-C14 Isoalkanes : This material is not expected to be harmful to aquatic organisms.

**SECTION 13: Disposal considerations**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

**SOLTROL® 130 Isoparaffin Solvent**

Version 1.11

Revision Date 2022-07-15

- Product : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14: Transport information**

**The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Testing (ASTM D4206) has shown product does not sustain combustion.

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**SOLTROL® 130 Isoparaffin Solvent**

Version 1.11

Revision Date 2022-07-15

<b>Other information</b>	<b>:</b> <b>Noxious Liquid, NF, (7), N.O.S. (Soltrol 130 contains iso and cyclo- alkanes (C10-C11)) S.T.3, Cat. Y</b>
--------------------------	---

**Maritime transport in bulk according to IMO instruments**

**SECTION 15: Regulatory information****National legislation**

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Aspiration hazard

CERCLA Reportable Quantity : This material does not contain any components with a CERCLA RQ.

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : This material does not contain any components with a section 302 EHS TPQ.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Components : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

**SOLTROL® 130 Isoparaffin Solvent**

Version 1.11

Revision Date 2022-07-15

**US State Regulations**

Pennsylvania Right To Know


: C12-C14 Isoalkanes - 68551-19-9

**Notification status**

Europe REACH	:	This product is in full compliance according to REACH regulation 1907/2006/EC.
Switzerland CH INV	:	On the inventory, or in compliance with the inventory
United States of America (USA) TSCA	:	All substances listed as active on the TSCA inventory
Canada DSL	:	All components of this product are on the Canadian DSL
Other AIIIC	:	On the inventory, or in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	This substance may be used as a component in a product covered by a group standard but it is not approved for use as a chemical in its own right
Philippines PICCS	:	Not in compliance with the inventory
Taiwan TCSI	:	On the inventory, or in compliance with the inventory
Korea KECI	:	A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s).
China IECSC	:	On the inventory, or in compliance with the inventory

**SECTION 16: Other information**

**NFPA Classification** : Health Hazard: 1  
Fire Hazard: 2  
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 29020

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

**SOLTROL® 130 Isoparaffin Solvent**

Version 1.11

Revision Date 2022-07-15

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Key or legend to abbreviations and acronyms used in the safety data sheet**

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		