

## Tertiary Butyl Mercaptan

Version 1.3

Revision Date 2022-12-22

MSDS number: AA00974-000000281

	the substance/mixture and of the company/undertaking
Product Name Material	<ul> <li>Tertiary Butyl Mercaptan</li> <li>1069500, 1086416, 1086415, 1070007, 1064730, 1021473, 1021470, 1017940, 1036143, 1024807, 1021472, 1021471, 1024806, 1021469, 1028495, 1021474, 1027458, 1029711, 1017329, 1021468</li> </ul>
Recommended use of the	e : Chemical intermediate, Odorant
Restrictions on use	: None known.
Address	: Chevron Phillips Chemical Company LP Specialty Chemicals 10001 Six Pines Drive The Woodlands, TX 77380
Address	: CHEVRON PHILLIPS CHEMICALS ASIA PTE. LTD. C/O DONG WOO CORPORATION #B-2601,JEONGJAIL-RO, BUNDANG-GU,SEONGNAMI-SI, GYEONGGI-DO,13557 SOUTH KOREA Telephone no.: +612-9186-1132
Emergency telephone:	
Asia: CHEMWATCH ( Mexico CHEMTREC (	

### Version 1.3

Revision Date 2022-12-22

Argentina: +(54)-1159839431 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week) Belgium: 070 245 245 (24 hours/day, 7 days/week) Bulgaria: +359 2 9154 233 Croatia: +3851 2348 342 (24 hours/day, 7 days/week) Cyprus: 1401 Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402 Denmark: Danish Poison Center (Giftlinien): +45 8212 1212 Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Finland: 0800 147 111 09 471 977 (24 hours/day) France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week) Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Greece: (0030) 2107793777 (24 hours/day, 7 days/week) Hungary: +36-80-201-199 (24 hours/day, 7 days/week) Iceland: 543 2222 (24 hours/day, 7 days/week) Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Italy: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.) Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Lithuania: +370 (85) 2362052 Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week) Malta: +356 2395 2000 The Netherlands: NVIC: +31 (0)88 755 8000 Norway: 22 59 13 00 (24 hours/day, 7 days/week) Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Portugal: CIAV phone number: +351 800 250 250 Romania: +40213183606 Slovakia: +421 2 5477 4166 Slovenia: Phone number: 112 Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week) Sweden: 112 - ask for Poisons Information : Product Safety and Toxicology Group Responsible Department E-mail address : SDS@CPChem.com Website : www.CPChem.com : 회사명: 리이치 24 시코리아㈜. Appointees 주소: 서울시 서초구 헌릉로 7, 외국기업창업지원연구센터 (IKP) 908-909호 전화: +82-1067838981 **SECTION 2: Hazards identification Hazard classification** Number:100000013356 2/19

# Tertiary Butyl Mercaptan

Version 1.3

Standards for classification and labeling of chemical substances and material safety data sheet (ministry of employment and labor public notice No. 2020-130)	
Classification	
	<ul> <li>Flammable liquids, Category 2</li> <li>Skin corrosion/irritation, Category 2</li> <li>Serious eye damage/eye irritation, Category 2</li> <li>Skin sensitization, Category 1</li> <li>Specific target organ toxicity - single exposure, Category 3, Respiratory system</li> <li>Aspiration hazard, Category 2</li> <li>Short-term (acute) aquatic hazard, Category 1</li> <li>Long-term (chronic) aquatic hazard, Category 2</li> </ul>
Warning label elements incluc	ding precautionary statements
Symbol(s)	
Signal Word	: Danger
Hazard Statements	<ul> <li>H225: Highly flammable liquid and vapor.</li> <li>H305: May be harmful if swallowed and enters airways.</li> <li>H315: Causes skin irritation.</li> <li>H317: May cause an allergic skin reaction.</li> <li>H319: Causes serious eye irritation.</li> <li>H335: May cause respiratory irritation.</li> <li>H400: Very toxic to aquatic life.</li> <li>H411: Toxic to aquatic life with long lasting effects.</li> </ul>
Precautionary Statements	<ul> <li>Prevention:</li> <li>P210: Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.</li> <li>P233: Keep container tightly closed.</li> <li>P240: Ground/bond container and receiving equipment.</li> <li>P241: Use explosion-proof electrical/ ventilating/ lighting/ equipment.</li> <li>P242: Use only non-sparking tools.</li> <li>P243: Take precautionary measures against static discharge.</li> <li>P261: Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.</li> <li>P264: Wash the contact area thoroughly after handling.</li> <li>P271: Use only outdoors or in a well-ventilated area.</li> <li>P272: Contaminated work clothing should not be allowed out of the workplace.</li> <li>P273: Avoid release to the environment.</li> <li>P280: Wear protective gloves/ eye protection/ face protection.</li> <li>Response:</li> <li>P301 + P310: IF SWALLOWED: Immediately call a POISON</li> </ul>
mber:100000013356	3/19

### **Tertiary Butyl Mercaptan**

Version 1.3 Revision Date 2022-12-22 CENTER or doctor/ physician. P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P321: Specific treatment (see supplemental first aid instructions on this label). P331: Do NOT induce vomiting. P333 + P313: If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313: If eye irritation persists: Get medical advice/ attention. P362 + P364: Take off contaminated clothing and wash it before reuse. P370 + P378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P391: Collect spillage. Storage: P403 + P233: Store in a well-ventilated place. Keep container tightly closed. P403 + P235: Store in a well-ventilated place. Keep cool. P405: Store locked up. Disposal: P501: Dispose of contents and container according to wastes control act. Other hazards which do : None not result in classification **SECTION 3: Composition/information on ingredients** t-Butyl Mercaptan Synonyms 2 tert-Butanethiol 2-Methyl Propane-2-Thiol TBM TC4SH tert-Butyl Mercaptan Molecular formula C4H10S Common name Synonyms CAS-No. Concentration KECI Number Number:100000013356 4/19

	5					
tiary Butyl Mercapta	10			D.		2022 4
sion 1.3				Ke	vision Date	2022-1
t-Butyl Mercaptan	2-me 2-thi	thylpropane- ol	75-66-1	99 % - 10	00% KE	-24873
TION 4: First aid measure	es					
General advice	:	sheet to the de	octor in attend	a. Show this ma lance. Material r eumonia if swallo	may produc	ce a
In case of eye contact	:	lenses. Prote	ct unharmed e	th plenty of wate eye. Keep eye w ists, consult a sp	/ide open w	
In case of skin contact	:	If on skin, rins	e well with wa	ter. If on clothes	s, remove o	clothes.
If inhaled	:			overy position ar		dical
If swallowed	:		is person. If s	Never give any symptoms persis nospital.		
Other cautions for Doctor	'S					
Symptoms	:	No data availa	ıble.			
Risks	:	No data availa	ıble.			
Treatment	:	No data availa	ıble.			
Treatment TION 5: Firefighting mea	sures	NO data avalla	ble.			
	: sures :	-26°C (-15°F) estimated				
TION 5: Firefighting mea	: sures :	-26°C (-15°F)				
TION 5: Firefighting mea	:	-26°C (-15°F) estimated No data availa	ble	bon dioxide (CC	2). Dry ch	emical.
TION 5: Firefighting mea Flash point Autoignition temperature Suitable extinguishing	:	-26°C (-15°F) estimated No data availa	ble ant foam. Car	bon dioxide (CC	2). Dry ch	emical.
TION 5: Firefighting mea Flash point Autoignition temperature Suitable extinguishing media Unsuitable extinguishing	: :	-26°C (-15°F) estimated No data availa Alcohol-resista High volume v	ble ant foam. Car vater jet.	bon dioxide (CC		
TION 5: Firefighting mea Flash point Autoignition temperature Suitable extinguishing media Unsuitable extinguishing media Specific hazards during fire	: :	-26°C (-15°F) estimated No data availa Alcohol-resista High volume v Do not allow r courses.	ble ant foam. Car vater jet. un-off from fire		r drains or	water

Version 1.3

Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Fire and explosion protection	: Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
Hazardous decomposition products	: Carbon oxides. Sulfur oxides.
TION 6: Accidental release	emeasures
Personal precautions	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
TION 7: Handling and stor	age
Handling	
Advice on safe handling	: Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Advice on protection	: Do not spray on a naked flame or any incandescent material.

ersion 1.3       Revision Date 2022-12         against fire and explosion       Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.         Secure storage       Requirements for storage areas and containers       No smoking. Keep container tightly closed in a dry and well-carefully resealed and kept upright to prevent leakage. Observe leabel precautions. Electrical installations / working materials must comply with the technological safety standards.         Uses advised against       None known.         Specific Use       Chemical intermediate, Odorant         erron Philips Chemical Company LP       Ontrol parameters         omponents       Basis       Value       Control parameters         Observe Unities of this material (see Section 2), applicable exposure initis, jo activities, and other substances in the work place when designing engineering controls are not adequate to personal protection is usually provided for a limited time or under certain circumstance provides are not adequate to for maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-ari NOSH approved respirator may be appropriate, if exposure levels are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-ari NOSH approved respirator may be appropriate, such as: Air-Purifying respirators may not provide adequate protection, and pure substance and understand all instructions and initiation supplied with the equipment. If engineering controls are not adequate to maintain minimimal oxygen conten	against fire and explosion       Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.         Secure storage       Requirements for storage areas and containers       No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.         Uses advised against       :       None known.         Specific Use       :       Chemical intermediate, Odorant         ECTION 8: Exposure controls/personal protection       Note         Nome known.       Specific Use       intermediate, Odorant         Ection 8: Exposure controls/personal protection       Note         Neuron Phillips Chemical Company LP       Control parameters       Note         Componentis       Basis       Value       Control parameters       Note         Require ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selet personal protective equipment. If engineering controls are not adequate to pre exposure to harmful levels of this material, the personal and initiations supplied wi the equipment since protection is usually provided for a limited t		n			
against fire and explosion       Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.         Secure storage       Equirements for storage : No smoking. Keep container tightly closed in a dry and well-ventilated pice. Containers which are opened must be carefully resealed and kept unpith to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.         Uses advised against       : None known.         Specific Use       : Chemical intermediate, Odorant         CTON 8: Exposure controls/personal protection         automotive ventilation of upsameters       Note         Observe tabel precautions.       Note         Chemical Company LP       Control parameters         omponents       Basis       Value       Control parameters         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances whold read and understand all instructions and limitation supplied with the equipment supported. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstance recommended. The user should read and understand all instructions and limitations supplied with the equipment is potential normal atmospheric pressure, a supplice-air NIOSH approved respirator may be ap	against fire and explosion       Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.         Secure storage       Requirements for storage areas and containers       : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label proceautions. Electrical installations / working materials must comply with the technological safety standards.         Uses advised against       : None known.         Specific Use       : Chemical intermediate, Odorant         CTION 8: Exposure controls/personal protection         evron Phillips Chemical Company LP         omponents       Basis         Duty Mencaptan       Note         Manufacturer       Twix         Obs.prom.       Itage show the work place when designing engineening controls and selet personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied wit the equipment area and understand all instructions and limitations supplied wit the equipment since protection is usually provided for a limited time or under certain circumstance or maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of this material, the personal content of 19.5% by volume under normal atmospheric pressure.	rsion 1.3				
(which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.         Secure storage         Requirements for storage areas and containers       : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.         Uses advised against       : None known.         Specific Use       : Chemical intermediate, Odorant         CTION 8: Exposure controls/personal protection         wron Phillips Chemical Company LP         amponents       Basis         Basis       Value       Control parameters         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Ocorial exposure standards, biological exposure squites of this material. (see Section 2), applicable exposure Imits, sob activities, and other substances in the work place when designing engineering controls are not adequate to prevapoure to harmful levels of this material. The personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provide for a limited time or under certain circumstance or responsure to harmful levels of this material. The personal protective equipment listed below is recommended. The user should read and understand all instructions and limitation supplied with the equipment since protection is usually provide for a limited time or under certain circu	(which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.         Secure storage         Requirements for storage areas and containers         :       No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.         Uses advised against       :         Specific Use       :         CTION 8: Exposure controls/personal protection         amponents       Basis         Dual Manufacturer       TWA         0.5 ppm.         amponents       Basis         Chemical exposure standards, biological exposure standards, etc.         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure finits, job activities, and other substances in the work place who designing engineering controls and seque to presponal protective equipment. If engineering controls are not adequate to presonal protective equipment         Personal protective equipment       If ventilation or other engineering controls are not adequate to maintain minimal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of this material, the personal protective equipment levels of the presonal protective equipment is the below is recommended.				Re	vision Date 2022-12
Requirements for storage areas and containers       No smoking. Keep container tightly closed in a dry and well- ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.         Uses advised against       : None known.         Specific Use       : Chemical intermediate, Odorant         CTION 8: Exposure controls/personal protection         evron Phillips Chemical Company LP         omponents       Basis         Busis       Value         Control parameters       Note         omponents       Basis         Chemical exposure standards, biological exposure standards, etc.         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and seleci personal protective equipment. If engineering controls or work practices are not adequate to pre exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understrand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstance aread and understrand all instructions and proved respirator for dynamical may occur, all NOSH approved respirator for Organic Vapors. A positive pressure, air- supplying respirator may be appropriate, such as:. Air-Purifying Respirator for Organic Vapo	Requirements for storage areas and containers       :       No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.         Uses advised against       :       None known.         Specific Use       :       Chemical intermediate, Odorant         CTION 8: Exposure controls/personal protection	against fire and explosion	(which explos	might cause ig ion-proof equip	nition of organic vapor ment. Keep away fror	rs). Use only
areas and containers       ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.         Uses advised against       :         None known.       :         Specific Use       :         CTION 8: Exposure controls/personal protection         evron Phillips Chemical Company LP         omponents       Basis         Walue       Control parameters         Menufacturer       TWA         O.5 ppm,         emponents       Basis         Quyl Mercaptan       Manufacturer         Chemical exposure standards, biological exposure standards, etc.         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selec personal protective equipment. If engineering controls or work practices are not adequate to prevexposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied wilt the equipment since protection is usually provided for a limited time or under certain circumstance normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occure, a NIOSH approved respirator that provides	areas and containers       ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precations. Electrical installations / working materials must comply with the technological safety standards.         Uses advised against       :         None known.       Specific Use         Specific Use       :         CTION 8: Exposure controls/personal protection         evron Phillips Chemical Company LP         omponents       Basis         Butyl Mercaptan       Manufacturer         TWA       0.5 ppm,         omponents       Basis         Chemical exposure standards, biological exposure standards, etc.         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selev personal protective equipment. If engineering controls or work practices are not adequate to pre exposure to harmful levels of this material, the personal protective equipment below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstance mormal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of	Secure storage				
Uses advised against       :       None known.         Specific Use       :       Chemical intermediate, Odorant         cron Phillips Chemical Company LP       ongnonents       Basis       Value       Control parameters       Note         anyl Mercaptan       Manufacturer       TWA       0.5 ppm.       Note         components       Basis       Value       Control parameters       Note         Chemical exposure standards, biological exposure standards, etc.       Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selec personal protective equipment. If engineering controls or work practices are not adequate to pree exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstance or market and and oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If the	Uses advised against       :       None known.         Specific Use       :       Chemical intermediate, Odorant         CTION 8: Exposure controls/personal protection         evron Phillips Chemical Company LP         omponents       Basis       Value       Control parameters       Note         Butyl Mercaptan       Manufacturer       TWA       0.5 ppm,       Note         Omponents       Basis       Value       Control parameters       Note         Chemical exposure standards, biological exposure standards, etc.       Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and select personal protective equipment. If engineering controls or work practices are not adequate to pre exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied wit the equipment since protection is usually provided for a limited time or under certain circumstance Personal protective equipment         Respiratory protection       :       If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of the substance in the pressure in the pressure in the pressure in the paproved respirator may be appropriate.		ventila carefu Obser	ted place. Con lly resealed and ve label precau	tainers which are open kept upright to preventions. Electrical install	ned must be nt leakage. lations / working
CTION 8: Exposure controls/personal protection         evron Phillips Chemical Company LP         omponents       Basis       Value       Control parameters       Note         omponents       Basis       Value       Control parameters       Note         components       Basis       Value       Control parameters       Note         Chemical exposure standards, biological exposure standards, etc.         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. job activities, and other substances in the work place when designing engineering controls and selec personal protective equipment. If engineering controls or work practices are not adequate to prevexposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstance on maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate. If exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.	CTION 8: Exposure controls/personal protection         evron Phillips Chemical Company LP         omponents       Basis       Value       Control parameters       Note         omponents       Basis       Value       Control parameters       Note         omponents       Basis       Value       Control parameters       Note         Chemical exposure standards, biological exposure standards, etc.         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and select personal protective equipment. If engineering controls or work practices are not adequate to pre exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied wit the equipment since protection is usually provided for a limited time or under certain circumstance         Personal protective equipment         Respiratory protection         If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of	Uses advised against	:		/ with the technologica	al safety standards.
evron Phillips Chemical Company LP           omponents         Basis         Value         Control parameters         Note           autyl Mercaptan         Manufacturer         TWA         0.5 ppm,         Note           omponents         Basis         Value         Control parameters         Note           omponents         Basis         Value         Control parameters         Note           Chemical exposure standards, biological exposure standards, etc.         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits, job activities, and other substances in the work place when designing engineering controls and select personal protective equipment. If engineering controls or work practices are not adequate to prevexposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstance           Personal protective equipment         If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purify	evron Phillips Chemical Company LP           omponents         Basis         Value         Control parameters         Note           Butyl Mercaptan         Manufacturer         TWA         0.5 ppm,           omponents         Basis         Value         Control parameters         Note           omponents         Basis         Value         Control parameters         Note           Chemical exposure standards, biological exposure standards, etc.         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and select personal protective equipment. If engineering controls or work practices are not adequate to pre exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied wit the equipment since protection is usually provided for a limited time or under certain circumstance Personal protective equipment           Respiratory protection         :         If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of	Specific Use	: Chemi	cal intermediate	e, Odorant	
Evron Phillips Chemical Company LP           omponents         Basis         Value         Control parameters         Note           autyl Mercaptan         Manufacturer         TWA         0.5 ppm,         Note           omponents         Basis         Value         Control parameters         Note           Chemical exposure standards, biological exposure standards, etc.         Note         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits, job activities, and other substances in the work place when designing engineering controls and select personal protective equipment. If engineering controls or work practices are not adequate to prevexposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstance Personal protective equipment           Respiratory protection         :         If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, are supplying respirators may not provide adequate protection.	Evron Phillips Chemical Company LP           omponents         Basis         Value         Control parameters         Note           Butyl Mercaptan         Manufacturer         TWA         0.5 ppm,           omponents         Basis         Value         Control parameters         Note           omponents         Basis         Value         Control parameters         Note           Chemical exposure standards, biological exposure standards, etc.         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and select personal protective equipment. If engineering controls or work practices are not adequate to pre exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied wit the equipment since protection is usually provided for a limited time or under certain circumstance Personal protective equipment           Respiratory protection         :         If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of					
omponents         Basis         Value         Control parameters         Note           Chemical exposure standards, biological exposure standards, etc.         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and select personal protective equipment. If engineering controls or work practices are not adequate to prevexposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstance.           Personal protective equipment         If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure that provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator for Organic Vapors. A positive pressure, air-supplying respirator for Organic vapors. A positive pressure, air-supplying respirator for orden capter protection.	omponents         Basis         Value         Control parameters         Note           Chemical exposure standards, biological exposure standards, etc.         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and select personal protective equipment. If engineering controls or work practices are not adequate to pre exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstance or under certain circumstance is usually provided for a limited time or under certain circumstance or maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of					ers Note
Chemical exposure standards, biological exposure standards, etc. Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selece personal protective equipment. If engineering controls or work practices are not adequate to prev- exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstance <b>Personal protective equipment</b> Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.	Chemical exposure standards, biological exposure standards, etc.         Adequate ventilation to control airborned concentrations below the exposure guidelines/limits.         Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and select personal protective equipment. If engineering controls or work practices are not adequate to pre exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstance         Personal protective equipment       If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of		Decie			
Respiratory protection If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.	Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of				<b>-</b>	ers Note
maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, air- supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.	maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of	Chemical exposure stand Adequate ventilation to cor Consider the potential haza activities, and other substa personal protective equipm exposure to harmful levels recommended. The user s	dards, biolog htrol airborned ards of this m nces in the w hent. If engine of this materi should read an	ical exposure d concentrations aterial (see Sec ork place when eering controls al, the personal nd understand a	standards, etc. below the exposure tion 2), applicable exp designing engineering or work practices are protective equipment all instructions and lim	guidelines/limits. oosure limits, job g controls and select not adequate to prev listed below is itations supplied with
	provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, air- supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators	Chemical exposure stand Adequate ventilation to cor Consider the potential haza activities, and other substa personal protective equipm exposure to harmful levels recommended. The user so the equipment since protect	dards, biolog ntrol airborned ards of this m nces in the w nent. If engine of this materi should read an ction is usually	ical exposure d concentrations aterial (see Sec ork place when eering controls al, the personal nd understand a	standards, etc. below the exposure tion 2), applicable exp designing engineering or work practices are protective equipment all instructions and lim	guidelines/limits. oosure limits, job g controls and select not adequate to prev listed below is itations supplied with
mber:10000013356 7/19		Chemical exposure stand Adequate ventilation to cor Consider the potential haza activities, and other substa personal protective equipm exposure to harmful levels recommended. The user s the equipment since protective Personal protective equip	dards, biolog htrol airborned ards of this m nces in the w hent. If engine of this materi should read ar tion is usually pment : If venti- mainta norma respira airborr provide Respir supply uncont- known	ical exposure d concentrations aterial (see Sec ork place when eering controls al, the personal nd understand a y provided for a ilation or other e in minimal oxyg I atmospheric p ator may be app ne material may es protection m rator for Organic ring respirator m trolled release, , or other circur	standards, etc. s below the exposure tion 2), applicable exp designing engineering or work practices are in protective equipment all instructions and lim limited time or under engineering controls a gen content of 19.5% H ressure, a supplied-ai ropriate. If exposure occur, a NIOSH appr ay be appropriate, suc vapors. A positive p hay be appropriate if th aerosolization, exposu- nstances where air-pu	guidelines/limits. posure limits, job g controls and select not adequate to prev- listed below is itations supplied with certain circumstance re not adequate to by volume under r NIOSH approved to harmful levels of oved respirator that ch as:. Air-Purifying ressure, air- nere is potential for ure levels are not

Version 1.3

Eye protection	: Eye wash bottle with pure water. Tightly fitting safety goggles.
Hand protection	: The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Remove and wash contaminated clothing before re-use. Skin should be washed after contact. Footwear protecting against chemicals.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
CTION 9: Physical and chem	ical properties
Information on basis physic	ical and chamical properties
	cal and chemical properties
Appearance	. limited
Physical state	
-	: liquid : clear
Color Odor	: clear : Repulsive
Color	: clear
Color Odor	: clear : Repulsive
Color Odor Odor Threshold	: clear : Repulsive : No data available
Color Odor Odor Threshold pH	: clear : Repulsive : No data available : Not applicable
Color Odor Odor Threshold pH Pour point	<ul> <li>: clear</li> <li>: Repulsive</li> <li>: No data available</li> <li>: Not applicable</li> <li>: No data available</li> </ul>
Color Odor Odor Threshold pH Pour point Melting point/freezing point	<ul> <li>: clear</li> <li>: Repulsive</li> <li>: No data available</li> <li>: Not applicable</li> <li>: No data available</li> <li>No data available</li> </ul>
Color Odor Odor Threshold pH Pour point Melting point/freezing point Boiling point/boiling range	<ul> <li>: clear</li> <li>: Repulsive</li> <li>: No data available</li> <li>: Not applicable</li> <li>: No data available</li> <li>No data available</li> <li>: 63-65°C (145-149°F)</li> <li>: -26°C (-15°F)</li> </ul>
Color Odor Odor Threshold pH Pour point Melting point/freezing point Boiling point/boiling range Flash point	<ul> <li>: clear</li> <li>: Repulsive</li> <li>: No data available</li> <li>: Not applicable</li> <li>: No data available</li> <li>No data available</li> <li>: 63-65°C (145-149°F)</li> <li>: -26°C (-15°F) estimated</li> </ul>
Color Odor Threshold pH Pour point Melting point/freezing point Boiling point/boiling range Flash point Evaporation rate	<ul> <li>: clear</li> <li>: Repulsive</li> <li>: No data available</li> <li>: Not applicable</li> <li>: No data available</li> <li>No data available</li> <li>: 63-65°C (145-149°F)</li> <li>: -26°C (-15°F) estimated</li> <li>: 1</li> </ul>
Color Odor Threshold pH Pour point Melting point/freezing point Boiling point/boiling range Flash point Evaporation rate Flammability (solid, gas)	<ul> <li>: clear</li> <li>: Repulsive</li> <li>: No data available</li> <li>: Not applicable</li> <li>: No data available</li> <li>No data available</li> <li>: 63-65°C (145-149°F)</li> <li>: -26°C (-15°F) estimated</li> <li>: 1</li> <li>: No data available</li> </ul>

# Tertiary Butyl Mercaptan

## Version 1.3

Solubility Relative density Vapor density Partition coefficient: n- octanol/water Autoignition temperature Molecular weight	<ul> <li>at 38°C (100°F)</li> <li>negligible</li> <li>0.81 at 16 °C (61 °F)</li> <li>3 (Air = 1.0)</li> <li>No data available</li> <li>No data available</li> <li>90.2 g/mol</li> </ul>
Relative density Vapor density Partition coefficient: n- octanol/water Autoignition temperature Molecular weight	<ul> <li>: 0.81 at 16 °C (61 °F)</li> <li>: 3 (Air = 1.0)</li> <li>: No data available</li> <li>: No data available</li> <li>: 90.2 g/mol</li> </ul>
Vapor density Partition coefficient: n- octanol/water Autoignition temperature Molecular weight	at 16 °C (61 °F) : 3 (Air = 1.0) : No data available : No data available : 90.2 g/mol
Partition coefficient: n- octanol/water Autoignition temperature Molecular weight	<ul> <li>(Air = 1.0)</li> <li>No data available</li> <li>No data available</li> <li>90.2 g/mol</li> </ul>
octanol/water Autoignition temperature Molecular weight	: No data available : 90.2 g/mol
Autoignition temperature Molecular weight	: 90.2 g/mol
Molecular weight	
TION 10: Stability and reactiv	
	vity
Reactivity	: Stable under recommended storage conditions.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous read	ctions
Hazardous reactions	: Hazardous reactions: Hazardous polymerization does not occur.
	Hazardous reactions: Vapors may form explosive mixture with air.
Conditions to avoid Hazardous decomposition products	<ul> <li>Heat, flames and sparks.</li> <li>Carbon oxides Sulfur oxides</li> </ul>
Other data	: No decomposition if stored and applied as directed.
TION 11: Toxicological inform	mation
Information on exposure rou	ites
Acute oral toxicity	
t-Butyl Mercaptan	: LD50: 4,729 mg/kg Species: Rat
nber:100000013356	9/19

# Tertiary Butyl Mercaptan

## Version 1.3

	Sex: male
Acute inhalation toxicity	
t-Butyl Mercaptan	: LC50: 98.3 mg/l Exposure time: 4 h Species: Rat Sex: male and female Test atmosphere: vapor Method: OECD Test Guideline 403
	LC50: 81.9 mg/l Exposure time: 4 h Species: Rat Sex: male Test atmosphere: vapor Method: OECD Test Guideline 403
	LC50: 60.9 mg/l Exposure time: 4 h Species: Mouse Sex: male Test atmosphere: vapor Method: OECD Test Guideline 403
Acute dermal toxicity	
t-Butyl Mercaptan	: LD50: > 2,000 mg/kg Species: Rabbit
Skin corrosion or irritation	
t-Butyl Mercaptan	: No skin irritation
Secure storage t-Butyl Mercaptan	: Mild eye irritation
Tertiary Butyl Mercaptan Respiratory Sensitization	: No data available
Tertiary Butyl Mercaptan Skin sensitization	The product is a skin sensitizer, sub-category 1B.
Repeated dose toxicity	
t-Butyl Mercaptan	<ul> <li>Species: Rat, Male and female Sex: Male and female Application Route: Inhalation Dose: 9, 97, 196 ppm Exposure time: 13 wks</li> </ul>
ber:100000013356	10/19

# Tertiary Butyl Mercaptan

Version 1.3

	Number of exposures: 6 hrs/d, 5 d/wk NOEL: > 196 ppm
	Species: Rat, Male and female Sex: Male and female Application Route: oral gavage Dose: 10, 50, 200 mg/kg bw/day Exposure time: 42-53 days Number of exposures: Daily NOEL: 50 mg/kg bw/day Lowest observable effect level: 200 mg/kg bw/day Method: OECD Guideline 422
	Species: Rat, Male and female Sex: Male and female Application Route: Inhalation Dose: 25.1, 99.6, 403.4 ppm Exposure time: 13 wks Number of exposures: 6 hrs/d, 5 d/wk NOEL: 99.6 ppm Lowest observable effect level: 403.4 ppm Method: OECD Guideline 413 Target Organs: Liver, Kidney, Blood, Upper respiratory tract Information given is based on data obtained from similar substances.
Germ cell mutagenicity (in vitro)	)
t-Butyl Mercaptan :	Test Type: Ames test Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative
	Test Type: Mouse lymphoma assay Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476 Result: negative
	Test Type: Sister Chromatid Exchange Assay Metabolic activation: with and without metabolic activation Result: negative
Germ cell mutagenicity (in vivo)	
t-Butyl Mercaptan :	Test Type: Mouse micronucleus assay Species: Mouse Dose: 1250, 2500, 5000 mg/kg Method: OECD Test Guideline 474 Result: negative
Developmental Toxicity	
Number:100000013356	11/19

Version 1.3

t-Butyl Mercaptan	: Species: Mouse Application Route: Inhalation Dose: 11, 99, 195 ppm Exposure time: GD 6-16 Number of exposures: 6 hrs/d NOAEL Teratogenicity: > = 195 ppm NOAEL Maternal: > = 195 ppm
	Species: Rat Application Route: Inhalation Dose: 11, 99, 195 ppm Exposure time: GD6-19 Number of exposures: 6 hrs/d NOAEL Teratogenicity: > =195 ppm NOAEL Maternal: > = 195 ppm
	Species: Rat Application Route: oral gavage Dose: 10, 50, 200 mg/kg bw/day Exposure time: 42-53 days Number of exposures: Daily NOAEL Teratogenicity: 50 mg/kg bw /day NOAEL Maternal: 200 mg/kg bw /day
Specific Target Organ Toxicity (Single Exposure)	
Specific Target Organ Toxicity (Repeated Exposure)	Not classified due to data which are conclusive although insufficient for classification.
	Not classified due to data which are conclusive although insufficient for classification.
Tertiary Butyl Mercaptan Aspiration toxicity Toxicology Assessment	: May be harmful if swallowed and enters airways.
Tertiary Butyl Mercaptan CMR effects	<ul> <li>Carcinogenicity: Not available Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects. Teratogenicity: Animal testing did not show any effects on fetal development. Reproductive toxicity:</li> </ul>
Number:100000013356	12/19
	,

SAFETY	DATA	SHEET
JAILII		JULLI

Version 1.3

	Animal testing did not show any effects on fertility.
Reproductive toxicity	
t-Butyl Mercaptan	Species: Rat Sex: male and female Application Route: oral gavage Dose: 10, 50, 200 mg/kg bw/day Number of exposures: Daily Test period: 42 -53 days Method: OECD Guideline 422 NOAEL Parent: 200 mg/kg bw/day NOAEL F1: 50 mg/kg bw/day No adverse effects expected
Tertiary Butyl Mercaptan Further information :	Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Solvents may degrease the skin.
CTION 12: Ecological information	n
Ecological Toxicity	
Toxicity to fish	
t-Butyl Mercaptan	LC50: 34 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203
Toxicity to daphnia and other a	aquatic invertebrates
t-Butyl Mercaptan	EC50: 6.7 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea) static test Method: OECD Test Guideline 202
Toxicity to algae	
t-Butyl Mercaptan	EC50: 24 mg/l Exposure time: 72 h Species: Pseudokirchneriella subcapitata (green algae) Method: OECD Test Guideline 201
Persistence and degradability t-Butyl Mercaptan	aerobic Result: Not readily biodegradable. 6 % Testing period: 63 d
mber:100000013356	13/19

	Revision Date 2022-12-2
	Method: OECD Test Guideline 301
Bioaccumulative	
t-Butyl Mercaptan	: Bioconcentration factor (BCF): 12 Method: QSAR modeled data This material is not expected to bioaccumulate.
Mobility	
t-Butyl Mercaptan	: Method: Calculation, Mackay Level III Fugacity Model The product will be dispersed amongst the various environmental compartments (soil/ water/ air).
Results of PBT assessment t-Butyl Mercaptan	t : Non-classified PBT substance, Non-classified vPvB substance
Other adverse effects	: Toxic to aquatic life with long lasting effects.
Ecotoxicology Assessme	nt
Short-term (acute) aquatic h t-Butyl Mercaptan	
Contraction and a second second	
Long-term (chronic) aquatic t-Butyl Mercaptan	c hazard
Long-term (chronic) aquatic	e hazard : Toxic to aquatic life with long lasting effects.
Long-term (chronic) aquatic t-Butyl Mercaptan CTION 13: Disposal conside	e hazard : Toxic to aquatic life with long lasting effects.
Long-term (chronic) aquatic t-Butyl Mercaptan CTION 13: Disposal conside The information in this SDS Use material for its intended may meet the criteria of a h other State and local regula regulated components may	e hazard : Toxic to aquatic life with long lasting effects. erations
Long-term (chronic) aquatic t-Butyl Mercaptan CTION 13: Disposal conside The information in this SDS Use material for its intended may meet the criteria of a h other State and local regula regulated components may classified as a hazardous w	<ul> <li>c hazard <ul> <li>Toxic to aquatic life with long lasting effects.</li> </ul> </li> <li>erations <ul> <li>erations</li> </ul> </li> <li>B pertains only to the product as shipped.</li> <li>d purpose or recycle if possible. This material, if it must be discarded, hazardous waste as defined by US EPA under RCRA (40 CFR 261) or ations. Measurement of certain physical properties and analysis for the necessary to make a correct determination. If this material is</li> </ul>
Long-term (chronic) aquatic t-Butyl Mercaptan CTION 13: Disposal conside The information in this SDS Use material for its intended may meet the criteria of a h other State and local regula regulated components may classified as a hazardous w disposal facility.	<ul> <li>c hazard <ul> <li>Toxic to aquatic life with long lasting effects.</li> </ul> </li> <li>erations Sections only to the product as shipped. G pertains only to the product as shipped. G purpose or recycle if possible. This material, if it must be discarded, hazardous waste as defined by US EPA under RCRA (40 CFR 261) or ations. Measurement of certain physical properties and analysis for the necessary to make a correct determination. If this material is waste, federal law requires disposal at a licensed hazardous waste C The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed</li></ul>

### Version 1.3

Revision Date 2022-12-22

### **SECTION 14: Transport information**

# The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

UN Number	:	UN2347
UN Product Shipping Name	:	Butyl Mercaptan
Hazard Class	:	3
Packing Group	:	II - Hazardous Properties
Marine Pollutant	:	Yes
Special Safety Measures on Mode of Transport	:	No data available

### US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN2347, BUTYL MERCAPTAN, 3, II

### IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN2347, BUTYL MERCAPTAN, 3, II, (-26°C), MARINE POLLUTANT, (TERTIARY BUTYL MERCAPTAN)

### IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN2347, BUTYL MERCAPTAN, 3, II

### ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN2347, BUTYL MERCAPTAN, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN2347, BUTYL MERCAPTAN, 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL

Number:100000013356

15/19

### Version 1.3

Revision Date 2022-12-22

MERCAPTAN)

# ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN2347, BUTYL MERCAPTAN, 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

Maritime transport in bulk according to IMO instruments

### **SECTION 15: Regulatory information**

### National legislation

### Regulation under the Occupational Safety and Health Act

A Material Safety Datasheet (MSDS) has to be prepared and provided for this product according to article 41 of ISHA.

Regulation		Chemical name	Threshold limits
Harmful Substances Prohibited from Manufacturing	:	Not applicable	
Harmful Substances Required Permission for Manufacture	••	Not applicable	

#### Act on the Registration and Evaluation, etc. of Chemical Substances, Chemicals Control Act

Regulation		Chemical name	Threshold limits
Toxic Chemicals	:	Not applicable	
Prohibited Chemicals	:	Not applicable	
Restricted Chemicals	:	Not applicable	
Toxic Release Inventory	:	Not applicable	

### Dangerous Substances Safety Management Act

Dangerous Substances : Flammable liquids, Type 1 petroleums, Water insoluble liquid Safety Management Act

Number:10000013356

Version 1.3

Regulations by the Waste : Management Act		: Not applicable
Regulations by other dome Europe REACH Switzerland CH INV United States of America (US TSCA Australia AIIC New Zealand NZIoC Japan ENCS Korea KECI		<ul> <li>This product is in full compliance according to REACH regulation 1907/2006/EC.</li> <li>On the inventory, or in compliance with the inventory</li> </ul>
Philippines PICCS Taiwan TCSI China IECSC		<ul> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> </ul>
Other regulations		: No data available
ECTION 16: Other information	١	
Source of data	:	Korea. GHS based classification
Date of initial writing	: 2022-07-19	
Revision number	:	1
Last revision date	:	2022-12-22
NFPA Classification	:	Health Hazard: 2 Fire Hazard: 3 Reactivity Hazard: 0
Other information None.		
umber:100000013356		17/19

Version 1.3

Revision Date 2022-12-22

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

	Key or legend to abbreviations and a		
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate

Number:100000013356

Version 1.3

Revision Date 2022-12-22

Number:100000013356