



## Soltrol® 170 Isoparaffin

Version 1.11

Revision Date 2023-07-19

According to Regulation (EC) No. 1907/2006, Regulation (EC) No. 2020/878

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

##### Product information

Product Name : Soltrol® 170 Isoparaffin  
 Material : 1017358, 1017353, 1017352, 1017355, 1017357, 1017359,  
 1017354, 1017356

##### EC-No.Registration number

Chemical name	CAS-No. EC-No. Index No.	Legal Entity Registration number
C12-C14 Isoalkanes	68551-19-9 271-369-5	Chevron Phillips Chemicals International NV 01-2119491311-45-0000
C12-C14 Isoalkanes	68551-19-9 271-369-5	Chevron Phillips Chemical Company LP 01-2119491311-45-0001

#### 1.2

##### Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified Uses : Formulation  
 Supported Industrial  
 Professional  
 Consumer

#### 1.3

##### Details of the supplier of the safety data sheet

Company : Chevron Phillips Chemical Company LP  
 Specialty Chemicals  
 10001 Six Pines Drive  
 The Woodlands, TX 77380

Local : Chevron Phillips Chemicals International N.V.  
 Airport Plaza (Stockholm Building)  
 Leonardo Da Vincilaan 19  
 1831 Diegem  
 Belgium

**Soltrol® 170 Isoparaffin**

Version 1.11

Revision Date 2023-07-19

SDS Requests: (800) 852-5530  
 Responsible Party: Product Safety Group  
 Email:sds@cpchem.com

**1.4****Emergency telephone:****Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

**Transport:**

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Gifftlinjen): +45 8212 1212

Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week)

Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Italy: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic

Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000

Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606

Slovakia: +421 2 5477 4166

Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group  
 E-mail address : SDS@CPChem.com  
 Website : www.CPChem.com

**SECTION 2: Hazards identification****2.1**

SDS Number:100000068456

2/16

**Soltrol® 170 Isoparaffin**

Version 1.11

Revision Date 2023-07-19

**Classification of the substance or mixture  
REGULATION (EC) No 1272/2008**

Aspiration hazard, Category 1

H304:

May be fatal if swallowed and enters airways.

**2.2****Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H304

May be fatal if swallowed and enters airways.

Precautionary Statements

: **Response:**  
P301 + P310IF SWALLOWED: Immediately call a  
POISON CENTER/ doctor.  
Do NOT induce vomiting.

P331

**Storage:**

P403

Store in a well-ventilated place.

**Disposal:**

P501

Dispose of contents/ container to an  
approved waste disposal plant.

Hazardous ingredients which must be listed on the label:

- 68551-19-9 C12-C14 Isoalkanes

**2.3****Other hazards**Results of PBT and vPvB  
assessment: This substance/mixture contains no components considered to  
be either persistent, bioaccumulative and toxic (PBT), or very  
persistent and very bioaccumulative (vPvB) at levels of 0.1%  
or higher.Endocrine disrupting  
properties: The substance/mixture does not contain components  
considered to have endocrine disrupting properties according  
to REACH Article 57(f) or Commission Delegated regulation  
(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at  
levels of 0.1% or higher.**SECTION 3: Composition/information on ingredients****3.1 - 3.2****Substance or Mixture**

Synonyms

: None established

Molecular formula

: UVCB

**Soltrol® 170 Isoparaffin**

Version 1.11

Revision Date 2023-07-19

**Hazardous ingredients**

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]	Specific Conc. Limits, M-factors and ATEs
C12-C14 Isoalkanes	68551-19-9 271-369-5	Asp. Tox. 1; H304	100	

For the full text of the H-Statements mentioned in this Section, see Section 16.

**SECTION 4: First aid measures****4.1****Description of first-aid measures**

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
- If inhaled : If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

**4.2 Most important symptoms and effects, both acute and delayed****Notes to physician**

- Symptoms : No data available.
- Risks : No data available.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Treatment : No data available.

**SECTION 5: Firefighting measures**

- Flash point : >79,4°C (>174,9°F)  
Method: Tag closed cup

- Autoignition temperature : No data available

**5.1****Extinguishing media**

- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical.  
Carbon dioxide (CO<sub>2</sub>).
- Unsuitable extinguishing media : High volume water jet.

**Soltrol® 170 Isoparaffin**

Version 1.11

Revision Date 2023-07-19

**5.3****Advice for firefighters**

- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.
- Hazardous decomposition products : Carbon Dioxide. Carbon oxides.

**SECTION 6: Accidental release measures****6.1****Personal precautions, protective equipment and emergency procedures**

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation.

**6.2****Environmental precautions**

- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

**6.3****Methods and materials for containment and cleaning up**

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

**6.4****Reference to other sections**

- Reference to other sections : For personal protection see section 8. For disposal considerations see section 13.

**SECTION 7: Handling and storage****7.1****Precautions for safe handling  
Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.

**Soltrol® 170 Isoparaffin**

Version 1.11

Revision Date 2023-07-19

**7.2****Conditions for safe storage, including any incompatibilities****Storage**

Requirements for storage areas and containers : No smoking. Keep in a well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8: Exposure controls/personal protection****8.1****Control parameters****Ingredients with workplace control parameters****Chevron Phillips Chemical Company LP**

Components	Basis	Value	Control parameters	Note
C12-C14 Isoalkanes	Manufacturer	TWA	1.200 mg/m3	RCP,

**SI**

Sestavine	Osnova	Vrednost	Parametri nadzora	Pripomba
C12-C14 Isoalkanes	SI OEL	MV	300 mg/m3	

**8.2****Exposure controls****Engineering measures**

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**Personal protective equipment**

Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Organic Vapors, Dusts and Mists. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the

**Soltrol® 170 Isoparaffin**

Version 1.11

Revision Date 2023-07-19

	contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Eye protection	: Eye wash bottle with pure water. Tightly fitting safety goggles.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Flame retardant protective clothing. Footwear protecting against chemicals.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**SECTION 9: Physical and chemical properties****9.1****Information on basic physical and chemical properties****Appearance**

Form	: liquid
Physical state	: liquid
Color	: Colorless at room temperature
Odor	: Mild, Hydrocarbon

**Safety data**

Flash point	: >79,4°C (>174,9°F) Method: Tag closed cup
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Oxidizing properties	: No
Autoignition temperature	: No data available
Thermal decomposition	: No data available
Molecular formula	: UVCB
Molecular weight	: Not applicable
pH	: 7
Pour point	: No data available
Boiling point/boiling range	: 217-246°C (423-475°F)
Vapor pressure	: 0,70 MMHG at 37,8°C (100,0°F)
Relative density	: 0,78 at 15,6 °C (60,1 °F)
Water solubility	: negligible

**Soltrol® 170 Isoparaffin**

Version 1.11

Revision Date 2023-07-19

Partition coefficient: n-octanol/water : No data available  
 Viscosity, kinematic : 2,6 cSt  
 at 38°C (100°F)

Relative vapor density : 3  
 (Air = 1.0)

Evaporation rate : 0,01

**9.2****Other information**

Conductivity : No data available

**SECTION 10: Stability and reactivity****10.1**

**Reactivity** : Stable under recommended storage conditions.

**10.2**

**Chemical stability** : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**10.3****Possibility of hazardous reactions**

**Hazardous reactions** : Hazardous reactions: Vapors may form explosive mixture with air.

**10.4**

**Conditions to avoid** : Heat, flames and sparks.

**10.5**

**Materials to avoid** : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

**Thermal decomposition** : No data available

**10.6**

**Hazardous decomposition products** : Carbon Dioxide  
 Carbon oxides

**Other data** : No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information****11.1****Information on toxicological effects****Acute oral toxicity**



**Soltrol® 170 Isoparaffin**

Version 1.11

Revision Date 2023-07-19

C12-C14 Isoalkanes : LD50: > 5.000 mg/kg  
Species: Rat  
Sex: male and female  
Method: OECD Test Guideline 401  
Information given is based on data obtained from similar substances.

**Acute inhalation toxicity**

C12-C14 Isoalkanes : LC50: > 4,9 mg/l  
Exposure time: 4 h  
Species: Rat  
Sex: male and female  
Test atmosphere: vapor  
Method: OECD Test Guideline 403  
An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.  
Information given is based on data obtained from similar substances.

**Acute dermal toxicity**

C12-C14 Isoalkanes : LD50: > 2.000 - 2.500 mg/kg  
Species: Rabbit  
Sex: male and female  
Method: OECD Test Guideline 402  
Information given is based on data obtained from similar substances.

**Skin irritation**

C12-C14 Isoalkanes : May irritate skin. Information given is based on data obtained from similar substances.

**Eye irritation**

C12-C14 Isoalkanes : No eye irritation  
Information given is based on data obtained from similar substances.

**Sensitization**

C12-C14 Isoalkanes : Did not cause sensitization on laboratory animals.  
Information given is based on data obtained from similar substances.

**Repeated dose toxicity**

C12-C14 Isoalkanes : Species: Rat, male and female  
Sex: male and female  
Application Route: oral gavage  
Dose: 100, 500, 1000 mg/kg/d  
Exposure time: 13 wk  
Number of exposures: daily  
NOEL: > 1000 mg/kg/d  
Method: OECD Test Guideline 408  
No adverse effects expected  
Information given is based on data obtained from similar substances.

**Soltrol® 170 Isoparaffin**

Version 1.11

Revision Date 2023-07-19

Species: Rat, male and female  
Sex: male and female  
Application Route: Inhalation  
Dose: 2600, 5200, 10400 mg/m<sup>3</sup>  
Exposure time: 90 d  
Number of exposures: 6 h/d; 5d/wk  
NOEL: > 10400 mg/m<sup>3</sup>  
Method: OECD Test Guideline 413  
No adverse effects expected  
Information given is based on data obtained from similar substances.

**Genotoxicity in vitro**

C12-C14 Isoalkanes

: Test Type: Ames test  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Mouse lymphoma assay  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Sister Chromatid Exchange Assay  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 479  
Result: negative

**Genotoxicity in vivo**

C12-C14 Isoalkanes

: Test Type: dominant lethal test  
Species: Rat  
Route of Application: Intraperitoneal injection  
Dose: 300, 900 ppm  
Method: OECD Test Guideline 478  
Remarks: Information given is based on data obtained from similar substances.

**Developmental Toxicity**

C12-C14 Isoalkanes

: Species: Rat  
Application Route: Inhalation  
Dose: 0, 400, 1200 ppm  
Exposure time: 6h  
Test period: GD 6-15  
NOAEL Teratogenicity: 1200 ppm  
NOAEL Maternal: 1200 ppm  
Information given is based on data obtained from similar substances.

**Soltrol® 170 Isoparaffin**

Version 1.11

Revision Date 2023-07-19

Species: Rat  
 Application Route: Inhalation  
 Dose: 300, 900 ppm  
 Exposure time: 6h  
 Test period: GD 6-15  
 NOAEL Teratogenicity:  $\geq$  900 ppm  
 NOAEL Maternal:  $\geq$  900 ppm  
 Information given is based on data obtained from similar substances.

**Soltrol® 170 Isoparaffin  
Aspiration toxicity**

: May be fatal if swallowed and enters airways.

**CMR effects**

C12-C14 Isoalkanes

: Carcinogenicity: Not available  
 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show mutagenic effects  
 Teratogenicity: Animal testing did not show any effects on fetal development.  
 Reproductive toxicity: Animal testing did not show any effects on fertility.

**11.2****Information on other hazards****Soltrol® 170 Isoparaffin****Further information**

Endocrine disrupting properties

: Solvents may degrease the skin.  
 : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 12: Ecological information****12.1****Toxicity****Toxicity to fish**

C12-C14 Isoalkanes

: LL50:  $>$  1.000 mg/l  
 Exposure time: 96 h  
 Species: Oncorhynchus mykiss (rainbow trout)  
 semi-static test Method: OECD Test Guideline 203  
 Information given is based on data obtained from similar substances.

**Toxicity to daphnia and other aquatic invertebrates**

C12-C14 Isoalkanes

: EL50:  $>$  1.000 mg/l  
 Exposure time: 48 h  
 Species: Daphnia magna (Water flea)  
 static test Method: OECD Test Guideline 202  
 Information given is based on data obtained from similar

**Soltrol® 170 Isoparaffin**

Version 1.11

Revision Date 2023-07-19

substances.

**Toxicity to algae**

C12-C14 Isoalkanes : EL50: > 1.000 mg/l  
 Exposure time: 72 h  
 Species: Pseudokirchneriella subcapitata (green algae)  
 Growth inhibition Method: OECD Test Guideline 201  
 Information given is based on data obtained from similar substances.

**Toxicity to fish (Chronic toxicity)**

C12-C14 Isoalkanes : No data available:

**12.2****Persistence and degradability**

Biodegradability : Expected to be biodegradable

**12.3****Bioaccumulative potential**

Elimination information (persistence and degradability)

Bioaccumulation

C12-C14 Isoalkanes : The product may be accumulated in organisms.

**12.4****Mobility in soil**

Mobility

C12-C14 Isoalkanes : immobile

**12.5****Results of PBT and vPvB assessment**

Results of PBT assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6****Endocrine disrupting properties**

Endocrine disrupting properties : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**12.7****Other adverse effects**

Additional ecological information : This material is not expected to be harmful to aquatic organisms.

**Soltrol® 170 Isoparaffin**

Version 1.11

Revision Date 2023-07-19

**12.8****Additional Information****Ecotoxicology Assessment**

Short-term (acute) aquatic hazard

C12-C14 Isoalkanes : This material is not expected to be harmful to aquatic organisms.

Long-term (chronic) aquatic hazard

C12-C14 Isoalkanes : This material is not expected to be harmful to aquatic organisms.

**SECTION 13: Disposal considerations****13.1****Waste treatment methods**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14: Transport information****14.1 - 14.7****Transport information**

**The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Testing (ASTM D4206) has shown product does not sustain combustion.

**Soltrol® 170 Isoparaffin**

Version 1.11

Revision Date 2023-07-19

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**Maritime transport in bulk according to IMO instruments**

**SECTION 15: Regulatory information****15.1****Safety, health and environmental regulations/legislation specific for the substance or mixture  
National legislation**

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

**Water hazard class (Germany)** : WGK 1 slightly water endangering  
Classification according VwVwS, Annex 3.

**15.2****Chemical Safety Assessment**

**Components** : Alkanes, C12-14-iso-  
A Chemical Safety Assessment has been carried out for this substance. A quantitative risk assessment is not required for human health. A quantitative risk assessment is not required for the environment. 271-369-5

**Major Accident Hazard Legislation** : 96/82/EC Update: 2003  
Directive 96/82/EC does not apply

**Soltrol® 170 Isoparaffin**

Version 1.11


Revision Date 2023-07-19

**Notification status**

Europe REACH	:	This product is in full compliance according to REACH regulation 1907/2006/EC.
Switzerland CH INV	:	On the inventory, or in compliance with the inventory
United States of America (USA) TSCA	:	On or in compliance with the active portion of the TSCA inventory
Canada DSL	:	All components of this product are on the Canadian DSL
Other AICS	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	This substance may be used as a component in a product covered by a group standard but it is not approved for use as a chemical in its own right
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECI	:	A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s).
Philippines PICCS	:	Not in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory
Taiwan TCSI	:	On the inventory, or in compliance with the inventory

**SECTION 16: Other information**

**NFPA Classification** : Health Hazard: 1  
Fire Hazard: 1  
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 47800

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

**Soltrol® 170 Isoparaffin**

Version 1.11

Revision Date 2023-07-19

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate

**Full text of H-Statements referred to under sections 2 and 3.**

H304

May be fatal if swallowed and enters airways.