


TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

according to GB/T 16483 and GB/T 17519

SECTION 1: Identification of the substance/mixture and of the company/undertaking
Product information

Product Name : TrusTec™ PRF Octane Blend No.80
 Material : 1024376, 1024372, 1024375, 1024374, 1093788, 1024377

Use : Reference Fuel

Company : Chevron Phillips Chemical Company LP
 Specialty Chemicals
 10001 Six Pines Drive
 The Woodlands, TX 77380

Local : Chevron Phillips Chemicals (Shanghai) Corporation
 Room 1810-1812, Shanghai Mart,
 2299 Yan An Road (W),
 Shanghai, PRC 200336
 Tel: (86-21) 22157200

Emergency telephone:
Health:

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212

Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

Greece: (0030) 2107793777 (24 hours/day, 7 days/week)
 Hungary: +36-80-201-199 (24 hours/day, 7 days/week)
 Iceland: 543 2222 (24 hours/day, 7 days/week)
 Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Italy: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic
 Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371
 67042473. (24 hours.)
 Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Lithuania: +370 (85) 2362052
 Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)
 Malta: +356 2395 2000
 The Netherlands: NVIC: +31 (0)88 755 8000
 Norway: 22 59 13 00 (24 hours/day, 7 days/week)
 Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Portugal: CIAV phone number: +351 800 250 250
 Romania: +40213183606
 Slovakia: +421 2 5477 4166
 Slovenia: Phone number: 112
 Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24
 hours/day, 7 days/week)
 Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

GHS Classification and Labeling: Follow GB 13690, GB 15258 and GB 30000.2 to GB 30000.29 (GHS 2011)

Emergency Overview**Danger**

Physical state: liquid **Color:** Colorless **Odor:** gasoline-like

Hazards : Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Classification





: Flammable liquids, Category 2
 Skin corrosion/irritation, Category 2
 Specific target organ toxicity - single exposure, Category 3,
 Narcotic effects
 Aspiration hazard, Category 1
 Short-term (acute) aquatic hazard, Category 1
 Long-term (chronic) aquatic hazard, Category 1

Labeling

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

Symbol(s)	:	   
Signal Word	:	Danger
Hazard Statements	:	H225: Highly flammable liquid and vapor. H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation. H336: May cause drowsiness or dizziness. H410: Very toxic to aquatic life with long lasting effects.
Precautionary Statements	:	Prevention: P210: Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P233: Keep container tightly closed. P240: Ground/bond container and receiving equipment. P241: Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242: Use only non-sparking tools. P243: Take precautionary measures against static discharge. P261: Avoid breathing dust/fume/gas/mist/vapors/spray. P273: Avoid release to the environment. P280: Wear protective gloves/ eye protection/ face protection. Response: P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor. P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P312: Call a POISON CENTER/doctor if you feel unwell. P331: Do NOT induce vomiting. P332 + P313: If skin irritation occurs: Get medical advice/ attention. P362+P364: Take off contaminated clothing and wash it before reuse. P370+P378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. P391: Collect spillage. Storage: P403 + P233: Store in a well-ventilated place. Keep container tightly closed. P403 + P235: Store in a well-ventilated place. Keep cool. Disposal: P501: Dispose of contents/ container to an approved waste disposal plant.

SECTION 3: Composition/information on ingredients

Synonyms	:	Primary Reference Fuel PRF (ASTM) Octane Blend No.80 Octane Reference Fuel
----------	---	--

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

Molecular formula : Mixture

Chemical name	CAS-No. / EINECS-No.	Concentration [wt%]
2,2,4-Trimethylpentane (Isooctane)	540-84-1	79.9 - 80.1
n-Heptane	142-82-5	19.7 - 20.3

SECTION 4: First aid measures

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
- If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

Notes to physician

- Symptoms : No data available.
- Risks : No data available.
- Treatment : No data available.

SECTION 5: Firefighting measures

- Flash point : -8°C (18°F)
Method: Tag closed cup
- Autoignition temperature : No data available
- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.
- Unsuitable extinguishing media : High volume water jet.
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hazardous decomposition products : Carbon oxides.

SECTION 6: Accidental release measures

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

Requirements for storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Use : Reference Fuel

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****CN**

Components	Basis	Value	Control parameters	Note
n-Heptane	CN OEL	PC-TWA	500 mg/m ³	
	CN OEL	PC-STEL	1,000 mg/m ³	

Not applicableNot applicable

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Organic Vapors. Full-Face Air-Purifying Respirator for Organic Vapors, Dusts and Mists. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Flame retardant antistatic protective clothing. Workers should wear antistatic

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

footwear.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

Physical state : liquid
Color : Colorless
Odor : gasoline-like

Safety data

Flash point : -8°C (18°F)
Method: Tag closed cup

Lower explosion limit : 1 %(V)

Upper explosion limit : 7 %(V)

Oxidizing properties : No

Autoignition temperature : No data available

Molecular formula : Mixture

Molecular weight : Not applicable

pH : Not applicable

Freezing point : No data available

Pour point : No data available

Boiling point/boiling range : 96-103°C (205-217°F)

Vapor pressure : 1.70 PSI
at 37.8°C (100.0°F)

Relative density : 0.693
at 15.6 °C (60.1 °F)

Water solubility : negligible

Partition coefficient: n-
octanol/water : No data available

Viscosity, kinematic : No data available

Relative vapor density : 3
(Air = 1.0)

Evaporation rate : 1

Percent volatile : > 99 %

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

Conductivity : No data available

SECTION 10: Stability and reactivity**Reactivity** : Stable under recommended storage conditions.**Chemical stability** : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.**Possibility of hazardous reactions****Hazardous reactions** : Hazardous reactions: Hazardous polymerization does not occur.
Hazardous reactions: Vapors may form explosive mixture with air.**Conditions to avoid** : Heat, flames and sparks.**Materials to avoid** : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.**Hazardous decomposition products** : Carbon oxides**Other data** : No decomposition if stored and applied as directed.**SECTION 11: Toxicological information****TrusTec™ PRF Octane Blend No.80****Acute oral toxicity** : LD50: > 5,000 mg/kg
Species: Rat
Method: Acute toxicity estimate**TrusTec™ PRF Octane Blend No.80****Acute inhalation toxicity** : LC50: > 20 mg/l
Species: Rat
Test atmosphere: dust/mist
Method: Acute toxicity estimateAcute toxicity estimate: > 40 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method**TrusTec™ PRF Octane Blend No.80****Acute dermal toxicity** : LD50: > 2,000 mg/kg
Species: Rabbit

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

Method: Acute toxicity estimate

TrusTec™ PRF Octane Blend No.80

Skin irritation : Skin irritation
largely based on animal evidence.
May cause skin irritation in susceptible persons.

TrusTec™ PRF Octane Blend No.80

Eye irritation : No eye irritation
largely based on animal evidence.
Vapors may cause irritation to the eyes, respiratory system
and the skin.

TrusTec™ PRF Octane Blend No.80

Sensitization : Did not cause sensitization on laboratory animals.

Repeated dose toxicity

2,2,4-Trimethylpentane
(Isooctane) : Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 0, 668, 2220, 6646 ppm
Exposure time: 13 weeks
Number of exposures: 6 hr/day 5 d/wk
NOEL: 8.117 mg/l 2220 ppm
Method: OECD Guideline 413
Information given is based on data obtained from similar
substances.

n-Heptane : Species: Rat, male
Sex: male
Application Route: Inhalation
Dose: 12.47 mg/l
Exposure time: 16 wk
Number of exposures: 12 h/d, 7 d/wk
NOEL: 12.47 mg/l
No adverse effect has been observed in chronic toxicity tests.

Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 12.35 mg/l
Exposure time: 26 wk
Number of exposures: 6 h/d, 5 d/wk
Method: OECD Test Guideline 413
No adverse effect has been observed in chronic toxicity tests.

Genotoxicity in vitro

2,2,4-Trimethylpentane
(Isooctane) : Test Type: Ames test
Method: Mutagenicity (Escherichia coli - reverse mutation
assay)
Result: negative

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

n-Heptane

Test Type: Mouse lymphoma assay
Method: OECD Guideline 476
Result: negative

Test Type: Sister Chromatid Exchange Assay
Result: negative

Test Type: Unscheduled DNA synthesis assay
Result: negative

Test Type: Ames test
Method: Mutagenicity (Escherichia coli - reverse mutation assay)
Result: negative

Test Type: Mammalian cell gene mutation assay
Method: OECD Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Guideline 473
Result: negative

Test Type: Mitotic recombination
Result: negative

Genotoxicity in vivo

2,2,4-Trimethylpentane (Isooctane) : Test Type: Unscheduled DNA synthesis assay
Species: Mouse
Dose: 500 mg/kg
Result: negative

Test Type: Unscheduled DNA synthesis assay
Species: Rat
Dose: 500 mg/kg
Result: negative

Reproductive toxicity

2,2,4-Trimethylpentane (Isooctane) : Species: Rat
Sex: male and female
Application Route: Inhalation
Dose: 0, 900, 3000, 9000 ppm
Number of exposures: 6 h/d 5 d/wk
Method: OECD Test Guideline 416
NOAEL Parent: 3000 ppm
NOAEL F1: 3000 ppm
NOAEL F2: 3000 ppm
Information given is based on data obtained from similar substances.

n-Heptane

Species: Rat
Sex: male and female
Application Route: Inhalation
Dose: 0, 900, 3000, 9000 ppm
Number of exposures: 6 hr/d, 5 d/wk
Test period: 13 wk
Method: OECD Test Guideline 416

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

NOAEL Parent: 3000ppm
 NOAEL F1: 3000 ppm
 NOAEL F2: 3000 ppm
 Information given is based on data obtained from similar substances.

Developmental Toxicity

2,2,4-Trimethylpentane (Isooctane) : Species: Rat
 Application Route: Inhalation
 Dose: 0, 400, 1200 ppm
 Number of exposures: 6h/d
 Test period: GD6-15
 NOAEL Teratogenicity: 1200 ppm
 NOAEL Maternal: 1200 ppm
 Information given is based on data obtained from similar substances.

Species: Rat
 Application Route: Inhalation
 Dose: 0, 900, 3000, 9000 ppm
 Number of exposures: 6h/d
 Test period: GD6-15
 Method: OECD Guideline 414
 NOAEL Teratogenicity: 9000 ppm
 NOAEL Maternal: 3000 ppm
 Information given is based on data obtained from similar substances.

n-Heptane : Species: Rat
 Application Route: Inhalation
 Dose: 0, 900, 3000, 9000 ppm
 Exposure time: GD6-15
 Number of exposures: 6 hrs/d
 NOAEL Teratogenicity: 9000 ppm
 NOAEL Maternal: 3000 ppm

TrusTec™ PRF Octane Blend No.80

Aspiration toxicity : May be fatal if swallowed and enters airways.

CMR effects

2,2,4-Trimethylpentane (Isooctane) : Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
 Teratogenicity: Animal testing did not show any effects on fetal development.
 Reproductive toxicity: Animal testing did not show any effects on fertility.

n-Heptane : Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
 Teratogenicity: Animal testing did not show any effects on fetal development.
 Reproductive toxicity: No toxicity to reproduction

TrusTec™ PRF Octane Blend No.80

Further information : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

above the TLV value may cause narcotic effects. Solvents may decrease the skin.
Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may decrease the skin.

SECTION 12: Ecological information**Toxicity to fish**

2,2,4-Trimethylpentane (Isooctane) : LC50: 0.11 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)
semi-static test Method: OECD Test Guideline 203
Information given is based on data obtained from similar substances.

n-Heptane LL50: 5.738 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)
Method: QSAR modeled data

Toxicity to daphnia and other aquatic invertebrates

2,2,4-Trimethylpentane (Isooctane) : EC50: 0.4 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
static test Information given is based on data obtained from similar substances.

n-Heptane EC50: 1.5 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
static test Toxic to aquatic organisms.

LC50: 0.1 mg/l
Exposure time: 96 h
Species: Mysisidopsis bahia (mysid shrimp)
semi-static test Very toxic to aquatic organisms.

Toxicity to algae

2,2,4-Trimethylpentane (Isooctane) : EL50: 2.943 mg/l
Exposure time: 72 h
Method: QSAR modeled data

n-Heptane EL50: 4.338 mg/l
Exposure time: 72 h
Species: Pseudokirchneriella subcapitata (microalgae)
Method: QSAR

Toxicity to fish (Chronic toxicity)

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

n-Heptane : NOELR: 1.284 mg/l
 Exposure time: 28 d
 Species: Oncorhynchus mykiss (rainbow trout)
 Method: QSAR modeled data

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

2,2,4-Trimethylpentane (Isooctane) : NOEL: 0.17 mg/l
 Exposure time: 21 d
 Species: Daphnia magna (Water flea)
 Method: OECD Test Guideline 211
 Information given is based on data obtained from similar substances.

Biodegradability

2,2,4-Trimethylpentane (Isooctane) : Result: Not readily biodegradable.
 Method: OECD Test Guideline 301
 Expected to be inherently biodegradable.
 Information given is based on data obtained from similar substances.

n-Heptane : Result: Readily biodegradable.
 70 %
 Testing period: 10 d

Bioaccumulation

2,2,4-Trimethylpentane (Isooctane) : Bioconcentration factor (BCF): 231
 Method: QSAR modeled data
 This material is not expected to bioaccumulate.

n-Heptane : Bioconcentration factor (BCF): 552
 Method: QSAR modeled data
 This material is not expected to bioaccumulate.

Mobility

2,2,4-Trimethylpentane (Isooctane) : Medium: Air
 Method: Calculation, Mackay Level I Fugacity Model
 After release, disperses into the air.

n-Heptane : Medium: Air
 Method: Calculation, Mackay Level I Fugacity Model
 Content: 100 %
 After release, disperses into the air.

Results of PBT assessment

2,2,4-Trimethylpentane (Isooctane) : Non-classified PBT substance, Non-classified vPvB substance

n-Heptane : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological information : Very toxic to aquatic life with long lasting effects.

Ecotoxicology Assessment

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

Short-term (acute) aquatic hazard : Very toxic to aquatic life.
 Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), N-HEPTANE), RQ (2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, (-8 °C c.c.), MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), N-HEPTANE)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), N-HEPTANE)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

33,UN1268,PETROLEUM PRODUCTS, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), N-HEPTANE)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), N-HEPTANE)

Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

Classification and Labeling of : Primary label: Combustible Liquid.

Commonly Used Dangerous

Chemical Substances

China. Banned or Severely Restricted Toxic Chemicals Regulation for Environmental Management of the First Import of Chemicals and the Import & Export of Toxic Chemicals, Article 3)

2,2,4-trimethylpentane : Severely restricted.

Notification status

Europe REACH : This mixture contains only ingredients which have been registered according to Regulation (EU) No. 1907/2006 (REACH).

Switzerland CH INV : On the inventory, or in compliance with the inventory

United States of America (USA) : On or in compliance with the active portion of the TSCA inventory

Canada DSL : All components of this product are on the Canadian DSL

Australia AIIC : On the inventory, or in compliance with the inventory

New Zealand NZIoC : Not in compliance with the inventory

Japan ENCS : On the inventory, or in compliance with the inventory

Korea KECI : All substances in this product were registered, notified to be registered, or exempted from registration by CPChem through an Only Representative according to K-REACH regulations. Importation of this product is permitted if the Korean Importer of Record was included on CPChem's notifications or if the Importer of Record themselves notified the substances.

Philippines PICCS : On the inventory, or in compliance with the inventory

Taiwan TCSI : On the inventory, or in compliance with the inventory

China IECSC : On the inventory, or in compliance with the inventory

Other regulations : Law on the Prevention and Control of Occupational Diseases

Other regulations : Law on the Prevention and Control of Occupational Diseases

TrusTec™ PRF Octane Blend No.80

Version 1.2

Revision Date 2023-09-20

SECTION 16: Other information**Further information**

Legacy SDS Number : 28440

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate