

AlphaPlus[®] 1-BUTENE

Version 3.4

Revision Date 2023-11-09

According to Regulation (EC) No. 1907/2006, Regulation (EC) No. 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Product information**

Product Name : AlphaPlus[®] 1-BUTENE
 Material : 1122418, 1036988, 1015419, 1037080, 1037081

EC-No.Registration number

Chemical name	CAS-No. EC-No. Index No.	Legal Entity Registration number
1-Butene	106-98-9 203-449-2 601-012-00-4	Chevron Phillips Chemical Company LP 01-2119456615-34-0003

1.2**Relevant identified uses of the substance or mixture and uses advised against**

Relevant Identified Uses : Manufacture
 Supported : Manufacture and use as an intermediate

1.3**Details of the supplier of the safety data sheet**

Company : Chevron Phillips Chemical Company LP
 Normal Alpha Olefins (NAO)
 10001 Six Pines Drive
 The Woodlands, TX 77380

Local : Chevron Phillips Chemicals International N.V.
 Airport Plaza (Stockholm Building)
 Leonardo Da Vincilaan 19
 1831 Diegem
 Belgium

SDS Requests: (800) 852-5530
 Responsible Party: Product Safety Group
 Email:sds@cpchem.com

1.4**Emergency telephone:**

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

Health:

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212

Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week)

Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Italy: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic

Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371

67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000

Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606

Slovakia: +421 2 5477 4166

Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com

SECTION 2: Hazards identification**2.1****Classification of the substance or mixture
REGULATION (EC) No 1272/2008**

Flammable gases, Category 1A

H220:

Extremely flammable gas.

Gases under pressure, Liquefied gas

H280:

Contains gas under pressure; may explode if heated.

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

2.2**Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H220
H280Extremely flammable gas.
Contains gas under pressure; may explode if heated.

Precautionary Statements

: **Prevention:**
P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response:

P377

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381

In case of leakage, eliminate all ignition sources.

Storage:

P410 + P403

Protect from sunlight. Store in a well-ventilated place.

2.3**Other hazards**

Results of PBT and vPvB assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Endocrine disrupting properties

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.1 - 3.2****Substance or Mixture**

Synonyms

: Ethylethylene
1-Butylene
Alpha-butene
Butene-1 (C4)
Alpha-Butylene
C4H8

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

Molecular formula : C₄H₈**Hazardous ingredients**

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]	Specific Conc. Limits, M-factors and ATEs
1-Butene	106-98-9 203-449-2 601-012-00-4	Flam. Gas 1; H220 Press. Gas Press. Gas Liquefied gas; H280	99 - 99,99	
n-Butane	106-97-8 203-448-7 601-004-00-0	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280 Press. Gas Compr. Gas; H280	0 - 1	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures**4.1****Description of first-aid measures**

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance.
- If inhaled : Call a physician or poison control center immediately. Keep patient warm and at rest. If unconscious, place in recovery position and seek medical advice. Keep respiratory tract clear.
- In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed**Notes to physician**

Symptoms : No data available.

Risks : No data available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No data available.

SECTION 5: Firefighting measures

Flash point : -80°C (-112°F)

Autoignition temperature : 383,89°C (723,00°F)

5.1**Extinguishing media**

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.

Unsuitable extinguishing media : High volume water jet.

5.2**Special hazards arising from the substance or mixture**

Specific hazards during fire fighting : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.3**Advice for firefighters**

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hazardous decomposition products : Carbon oxides.

SECTION 6: Accidental release measures**6.1****Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

6.2**Environmental precautions**

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3**Methods and materials for containment and cleaning up**

Methods for cleaning up : Ventilate the area.

6.4**Reference to other sections**

Reference to other sections : For personal protection see section 8. For disposal considerations see section 13.

SECTION 7: Handling and storage**7.1**

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

**Precautions for safe handling
Handling**

Advice on safe handling : Do not breathe vapors/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation hood. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

7.2**Conditions for safe storage, including any incompatibilities****Storage**

Requirements for storage areas and containers : Prevent unauthorized access. No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

German storage class : Gases

SECTION 8: Exposure controls/personal protection**8.1****Control parameters
Ingredients with workplace control parameters****SI**

Sestavine	Osnova	Vrednost	Parametri nadzora	Pripomba
n-Butane	SI OEL	MV	1.000 ppm, 2.400 mg/m ³	
	SI OEL	KTV	4.000 ppm, 9.600 mg/m ³	

RU

Компоненты	Основа	Величина	Параметры контроля	Заметка
1-бутен	RU OEL	ПДК	100 mg/m ³	4, пары и/или газы
	RU OEL	ПДК разовая	300 mg/m ³	4, пары и/или газы
	RU OEL	ПДК	100 mg/m ³	4, пары и/или газы
	RU OEL	ПДК разовая	300 mg/m ³	4, пары и/или газы
н-бутан	RU OEL	ПДК	300 mg/m ³	4, пары и/или газы
	RU OEL	ПДК разовая	900 mg/m ³	4, пары и/или газы
	RU OEL	ПДК	300 mg/m ³	4, пары и/или газы
	RU OEL	ПДК разовая	900 mg/m ³	4, пары и/или газы

4 4 класс - умеренно опасные

PT

Componentes	Bases	Valor	Parâmetros de controlo	Nota
1-Butene	PT OEL	VLE-MP	250 ppm,	
n-Butane	PT OEL	VLE_CD	1.000 ppm,	

PL

Składniki	Podstawa	Wartość	Parametry dotyczące kontroli	Uwaga

SDS Number:100000068452

6/21

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

n-Butane	PL NDS	NDS	1.900 mg/m ³	
	PL NDS	NDSch	3.000 mg/m ³	

NO

Komponenter	Grunnlag	Verdi	Kontrollparametrer	Nota
n-Butane	FOR-2011-12-06-1358	GV	250 ppm, 600 mg/m ³	

MK

Съставки	Основа	Стойност	Параметри на контрол	Бележка
n-Butane	MK OEL	MV	1.000 ppm, 2.400 mg/m ³	

LV

Sastāvdaļas	Bāze	Vērtība	Pārvaldības parametri	Piezīme
n-Butane	LV OEL	AER 8 st	300 mg/m ³	

IS

Komponenter	Grunnlag	Verdi	Kontrollparametrer	Nota
n-Butane	IS OEL	TWA	500 ppm, 1.200 mg/m ³	

IE

Components	Basis	Value	Control parameters	Note
1-Butene	IE OEL	OELV - 8 hrs (TWA)	250 ppm,	
n-Butane	IE OEL	OELV - 15 min (STEL)	1.000 ppm,	

HU

Komponensek	Bázis	Érték	Ellenőrzési paraméterek	Megjegyzés
n-Butane	HU OEL	AK-érték	2.350 mg/m ³	N,
	HU OEL	CK-érték	9.400 mg/m ³	N,

N Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok. Korrekció NEM szükséges.

HR

Sastojci	Temelj	Vrijednost	Nadzorni parametri	Bilješka
n-Butane	HR OEL	GVI	600 ppm, 1.450 mg/m ³	
	HR OEL	KGVI	750 ppm, 1.810 mg/m ³	
	HR OEL	GVI	10 ppm, 22 mg/m ³	1, 2, T, F+,

- 1 Karc. kat. 1: tvaru za koje je dokazano da su karcinogene za ljude
 2 Muta. kat. 2: tvaru koje su vjerojatno mutagene za ljude
 F+ Vrlo lako zapaljivo
 T Otrovno

GR

Συστατικά	Βάση	Τιμή	Παράμετροι ελέγχου	Σημείωση
n-Butane	GR OEL	TWA	1.000 ppm, 2.350 mg/m ³	

GB

Components	Basis	Value	Control parameters	Note
n-Butane	GB EH40	TWA	600 ppm, 1.450 mg/m ³	Carc,
	GB EH40	STEL	750 ppm, 1.810 mg/m ³	Carc,

Carc Capable of causing cancer and/or heritable genetic damage.

FR

Composants	Base	Valeur	Paramètres de contrôle	Note
n-Butane	FR VLE	VME	800 ppm, 1.900 mg/m ³	Valeurs limites indicatives,

Valeurs limites Valeurs limites indicatives
 indicatives

FI

Aineosat	Peruste	Arvo	Valvontaa koskevat muuttujat	Huomautus
n-Butane	FI OEL	HTP-arvot 8h	800 ppm, 1.900 mg/m ³	Liite 4,
	FI OEL	HTP-arvot 15 min	1.000 ppm, 2.400 mg/m ³	Liite 4,

Liite 4 Happea syrjäyttämällä tukehduttavat kaasut

ES

Componentes	Base	Valor	Parámetros de control	Nota
1-Butene	ES VLA	VLA-ED	1.000 ppm,	gas
n-Butane	ES VLA	VLA-ED	1.000 ppm,	gas

EE

Komponendid, osad	Alused	Väärtus	Kontrolliparameetrid	Märkused
n-Butane	EE OEL	Piirnorm	800 ppm, 1.500 mg/m ³	

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

DK

Komponenter	Basis	Værdi	Kontrolparametre	Note
n-Butane	DK OEL	GV	500 ppm, 1.200 mg/m3	

DE

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
n-Butane	DE TRGS 900	AGW	1.000 ppm, 2.400 mg/m3	

CH

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
n-Butane	CH SUVA	MAK-Wert	800 ppm, 1.900 mg/m3	
	CH SUVA	MAK-Wert	800 ppm, 1.900 mg/m3	
	CH SUVA	KZGW	3.200 ppm, 7.600 mg/m3	

BG

Съставки	Основа	Стойност	Параметри на контрол	Бележка
n-Butane	BG OEL	TWA	1.900 mg/m3	

BE

Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
1-Butene	BE OEL	TGG 8 hr	250 ppm, 583 mg/m3	
n-Butane	BE OEL	TGG 8 hr	1.000 ppm,	
	BE OEL	TGG 15 min	980 ppm, 2.370 mg/m3	

AT

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
n-Butane	AT OEL	MAK-TMW	800 ppm, 1.900 mg/m3	
	AT OEL	MAK-KZW	1.600 ppm, 3.800 mg/m3	

DNEL : End Use: Workers
Routes of exposure: Inhalation
Potential health effects: Chronic effects, Local effects
Value: 1530 mg/m3

DNEL : End Use: Workers
Routes of exposure: Inhalation
Potential health effects: Chronic effects, Systemic effects
Value: 769 mg/m3

8.2**Exposure controls
Engineering measures**

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Organic Vapors. A positive pressure, air-

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Safety glasses.
- Skin and body protection : Choose body protection according to the amount and concentration of the substance and the task performed at the work place. Appropriate PPE may include: Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**9.1****Information on basic physical and chemical properties****Appearance**

- Form : Liquefied gas, Gases under pressure
- Physical state : Gaseous
- Color : Colorless

Safety data

- Flash point : -80°C (-112°F)
- Lower explosion limit : 1,6 %(V)
- Upper explosion limit : 9,3 %(V)
- Oxidizing properties : no
- Autoignition temperature : 383,89°C (723,00°F)
- Molecular formula : C4H8
- Molecular weight : 56,12 g/mol
- pH : Not applicable
- Freezing point : -185°C (-301°F)
- Pour point : No data available

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

Boiling point/boiling range	: -6,26°C (20,73°F)
Vapor pressure	: 1.895,00 MMHG at 20°C (68°F)
Relative density	: 0,6 at 15,6 °C (60,1 °F)
Density	: 600,3 g/l
Water solubility	: Soluble in hydrocarbon solvents; insoluble in water.
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Relative vapor density	: 1,93 (Air = 1.0)
Evaporation rate	: No data available
Percent volatile	: > 99 %

SECTION 10: Stability and reactivity**10.1**

Reactivity : Stable at normal ambient temperature and pressure.

10.2

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3**Possibility of hazardous reactions**

Hazardous reactions : Further information: No decomposition if stored and applied as directed.

Hazardous reactions: Vapors may form explosive mixture with air.

10.4

Conditions to avoid : Heat, flames and sparks.

10.5

Materials to avoid : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

10.6

Hazardous decomposition products : Carbon oxides

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**11.1****Information on toxicological effects****AlphaPlus® 1-BUTENE**

Acute oral toxicity : Negligible or unlikely exposure pathways

AlphaPlus® 1-BUTENE

Acute inhalation toxicity : LC50: > 10000 ppm
 Exposure time: 4 h
 Species: Rat
 Test atmosphere: gas
 Method: OECD Test Guideline 403
 Information given is based on data obtained from similar substances.

AlphaPlus® 1-BUTENE

Acute dermal toxicity : Negligible or unlikely exposure pathways

AlphaPlus® 1-BUTENE

Skin irritation : No skin irritation. Rapid evaporation of the liquid may cause frostbite.

AlphaPlus® 1-BUTENE

Eye irritation : No eye irritation. Contact with liquid or refrigerated gas can cause cold burns and frostbite.

AlphaPlus® 1-BUTENE

Sensitization : No data available.

Repeated dose toxicity

1-Butene : Species: Rat, Male and female
 Sex: Male and female
 Application Route: Inhalation
 Dose: 0, 500, 2000, 8000 ppm
 Exposure time: 28 d
 Number of exposures: 6 hr/d, 7 d/wk
 NOEL: 8000 ppm
 Method: OECD Guideline 422
 No adverse effect has been observed in chronic toxicity tests.

n-Butane

Species: Rat, Male and female
 Sex: Male and female
 Application Route: Inhalation
 Dose: 0, 1017, 4489 ppm
 Exposure time: 90 day
 Number of exposures: 6 hr/d, 5 d/wk
 NOEL: 4489 ppm

Genotoxicity in vitro

1-Butene : Test Type: Ames test

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

n-Butane Metabolic activation: with and without metabolic activation
Result: negative

n-Butane Test Type: Ames test
Result: negative

Genotoxicity in vivo

1-Butene : Test Type: Micronucleus test
Species: Mouse
Dose: 1000, 3260, 10000 ppm
Method: Mutagenicity (micronucleus test)
Result: negative

Carcinogenicity

1-Butene : Species: Rat
Sex: male
Dose: 0, 500, 2000, 8000 ppm
Exposure time: 2 years
Number of exposures: 6 hr/d, 5 d/wk
Remarks: increased incidence of thyroid tumors, Information given is based on data obtained from similar substances.

Species: Rat
Sex: female
Dose: 0, 500, 2000, 8000 ppm
Exposure time: 2 years
Number of exposures: 6 hr/d, 5 d/wk
Remarks: no increase incidence of tumors, Information given is based on data obtained from similar substances.

Species: Mouse
Sex: male
Dose: 0, 500, 2000, 8000 ppm
Exposure time: 2 years
Number of exposures: 6 hr/d, 5 d/wk
Remarks: no increase incidence of tumors, Information given is based on data obtained from similar substances.

Species: Mouse
Sex: female
Dose: 0, 500, 2000, 8000 ppm
Exposure time: 2 years
Number of exposures: 6 hr/d, 5 d/wk
Remarks: no increase incidence of tumors, Information given is based on data obtained from similar substances.

Reproductive toxicity

1-Butene : Species: Rat
Sex: male and female
Application Route: Inhalation
Dose: 0, 500, 2000, 8000 ppm
Method: OECD Guideline 422
NOEL Parent: 8000 ppm
NOEL F1: 8000 ppm

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

CMR effects

1-Butene : Carcinogenicity: Weight of evidence does not support classification as a carcinogen
 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
 Teratogenicity: Animal testing did not show any effects on fetal development.
 Reproductive toxicity: Animal testing did not show any effects on fertility.

n-Butane Carcinogenicity: Weight of evidence does not support classification as a carcinogen
 Mutagenicity: Weight of evidence does not support classification as a germ cell mutagen.
 Teratogenicity: Not available
 Reproductive toxicity: Weight of evidence does not support classification for reproductive toxicity

11.2**Information on other hazards****AlphaPlus® 1-BUTENE**

Further information : No data available.
 Endocrine disrupting properties : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information**12.1****Toxicity****Toxicity to fish**

1-Butene : No data available

Toxicity to daphnia and other aquatic invertebrates

1-Butene : No data available

Toxicity to algae

1-Butene : No data available

12.2**Persistence and degradability**

Biodegradability : This material is expected to be readily biodegradable.

12.3**Bioaccumulative potential**

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

Elimination information (persistence and degradability)

Bioaccumulation

1-Butene : Bioconcentration factor (BCF): 17,8
Method: QSAR modeled data
This material is not expected to bioaccumulate.

n-Butane : This material is not expected to bioaccumulate.

12.4**Mobility in soil**

Mobility

1-Butene : Medium: Air
Method: Calculation, Mackay Level I Fugacity Model
Content: 99,99 %

: Medium: Water
Method: Calculation, Mackay Level I Fugacity Model
Content: 0,01 %

n-Butane : The product evaporates readily.

12.5**Results of PBT and vPvB assessment**

Results of PBT assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6**Endocrine disrupting properties**

Endocrine disrupting properties : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7**Other adverse effects**

Additional ecological information : No data available

12.8**Additional Information****Ecotoxicology Assessment**

Short-term (acute) aquatic hazard : No data available
Long-term (chronic) aquatic hazard : No data available

SECTION 13: Disposal considerations**13.1**

SDS Number:100000068452

14/21

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

Waste treatment methods

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

- Product : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information**14.1 - 14.7****Transport information**

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1012, BUTYLENE, 2.1
NON- ODORIZED

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1012, BUTYLENE, 2.1, (-80 °C c.c.)
NON- ODORIZED

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1012, BUTYLENE, 2.1
NON- ODORIZED

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1012, BUTYLENE, 2.1, (B/D)
NON- ODORIZED

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

23, UN1012, BUTYLENE, 2.1
NON- ODORIZED

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

OF DANGEROUS GOODS BY INLAND WATERWAYS)
 UN1012, BUTYLENE, 2.1
 NON- ODORIZED

Other information	:	Butylenes (all isomers), 2G/2PG
--------------------------	----------	--

Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information**15.1**

Safety, health and environmental regulations/legislation specific for the substance or mixture
National legislation

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Water hazard class (Germany) : WGK 1 slightly water endangering

15.2**Chemical Safety Assessment**

Components : but-1-ene A Chemical Safety Assessment 203-449-2 has been carried out for this substance.

Major Accident Hazard Legislation : ZEU_SEVES3 Update:
 FLAMMABLE GASES
 P2
 Quantity 1: 10 t
 Quantity 2: 50 t

Notification status

Europe REACH : This product is in full compliance according to REACH regulation 1907/2006/EC.
 Switzerland CH INV : On the inventory, or in compliance with the inventory
 United States of America (USA) TSCA : On or in compliance with the active portion of the TSCA inventory
 Canada DSL : All components of this product are on the Canadian DSL
 Australia AIIC : On the inventory, or in compliance with the inventory
 New Zealand NZIoC : Not in compliance with the inventory
 Japan ENCS : On the inventory, or in compliance with the inventory
 Philippines PICCS : On the inventory, or in compliance with the inventory
 Taiwan TCSI : On the inventory, or in compliance with the inventory
 China IECSC : On the inventory, or in compliance with the inventory


AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

SECTION 16: Other information

NFPA Classification : Health Hazard: 1
Fire Hazard: 4
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : PE0015

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and	TSCA	Toxic Substance Control Act

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

	New Chemical Substances		
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate

Full text of H-Statements referred to under sections 2 and 3.

H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

Annex**1. Short title of Exposure Scenario: Manufacture**

Main User Groups	:	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	:	SU3: Industrial Manufacturing (all)
Process category	:	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC15: Use as laboratory reagent
Environmental release category	:	ERC1, ERC4: Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for:ERC1, ERC4: Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles**Technical conditions and measures / Organizational measures**

Remarks : Not applicable

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process (synthesis) where opportunity for exposure arises, Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Use as laboratory reagent**Amount used**

Remarks : Not applicable

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

3. Exposure estimation and reference to its source

Remarks: Not applicable

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Not applicable

1. Short title of Exposure Scenario: Manufacture and use as an intermediate

Main User Groups	:	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	:	SU3: Industrial Manufacturing (all)
Process category	:	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC15: Use as laboratory reagent
Environmental release category	:	ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)

2.1 Contributing scenario controlling environmental exposure for:ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)**Technical conditions and measures / Organizational measures**

Remarks : Not applicable

2.2 Contributing scenario controlling worker exposure for: , PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15: Transfer of substance or preparation into small containers (dedicated filling line, including weighing), Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process (synthesis) where opportunity for exposure arises, Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Use as laboratory reagent

AlphaPlus® 1-BUTENE

Version 3.4

Revision Date 2023-11-09

Amount used

Remarks : Not applicable

3. Exposure estimation and reference to its source

Remarks: Not applicable

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Not applicable