

Version 4.3 Revision Date 2024-01-29

According to Regulation (EC) No. 1907/2006, Regulation (EC) No. 2020/878

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### **Product information**

Product Name : Scentinel® A Gas Odorant

Material : 1017907, 1017909, 1119674, 1119564, 1106807, 1098462,

1102596, 1086453, 1098407, 1086452, 1102264, 1072060, 1098463, 1103512, 1070006, 1024777, 1024776, 1024775, 1024774, 1029441, 1029442, 1029443, 1029444, 1029445

### EC-No.Registration number

Chemical name	CAS-No. EC-No. Index No.	Legal Entity Registration number
Ethyl Mercaptan	75-08-1 200-837-3 016-022-00-9	Chevron Phillips Chemicals International NV 01-2119491286-30-0000

#### 1.2

### Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified Uses : Manufacture of Ethanethiol used under Strictly Controlled

Supported Conditions

Use at Industrial Site - Intermediate

Injection as odorant in Liquified Petroleum Gas under

Strictly Controlled Conditions - Industrial

Injection as odorant in Liquified Petroleum Gas under

Strictly Controlled Conditions - Consumer

#### 1.3

#### Details of the supplier of the safety data sheet

Company : Chevron Phillips Chemical Company LP

10001 Six Pines Drive The Woodlands, TX 77380

Local : Chevron Phillips Chemicals International N.V.

Airport Plaza (Stockholm Building)

Leonardo Da Vincilaan 19

1831 Diegem Belgium

SDS Number:100000068741 1/21

Version 4.3 Revision Date 2024-01-29

SDS Requests: (800) 852-5530

Responsible Party: Product Safety Group

Email:sds@cpchem.com

# 1.4

#### **Emergency telephone:**

#### Health:

866.442.9628 (North America) 1.832.813.4984 (International)

#### Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212 Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week) Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico "Agostino Gemelli", Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico "Umberto I" Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera "Antonio Cardarelli" Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera "Papa Giovanni XXIII" Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011 858;

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000 Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606 Slovakia: +421 2 5477 4166 Slovenia: Phone number: 112

Version 4.3 Revision Date 2024-01-29

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24

hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group

E-mail address : SDS@CPChem.com Website : www.CPChem.com

#### **ODOR-FADE WARNING**

A GAS LEAK CAN CAUSE A FIRE OR EXPLOSION RESULTING IN SERIOUS INJURY OR DEATH.

Be aware that the stenching chemical added to gas to make it detectable may not warn of a gas leak or the presence of propane or natural gas to all persons in every instance.

Instances where the odorant in an odorized gas may be undetectable include:

- Odor intensity may fade or be eliminated for a variety of chemical and physical causes, including the oxidation of rusting pipes, adsorption into or sticking onto the interior of pipes or appliances, or absorption into liquids.
- Contact with soil in underground leaks may de-odorize or remove odorant from the gas.
- Some people have a diminished ability, or inability to smell the stench. Factors that negatively affect a person's sense of smell include age, gender, medical conditions, and alcohol/tobacco usage.
- The stench of odorized gas may not awaken sleeping persons.
- · Other odors may mask or hide the stench.
- Exposure to the odor for even a short period of time, may cause nasal fatigue, where a person can no longer smell the stench.

Gas detectors listed by the Underwriters Laboratories (UL) can be used as an extra measure of safety for detecting gas leaks, especially under conditions where the odorant alone may not provide an adequate warning. Gas detectors emit a loud, shrill sound when gas is present and do not depend on sense of smell. Because the odor intensity can fade or people may have problems with their sense of smell, we recommend installing, per manufacturer's instructions, one or more combustible gas detectors, in suitable locations to ensure adequate coverage to detect gas leaks.

Educate yourself, your employees, and your customers with the content of this warning and other important facts associated with the so-called "odor-fade phenomenon."

#### **SECTION 2: Hazards identification**

#### 2.1

# Classification of the substance or mixture REGULATION (EC) No 1272/2008

Flammable liquids, Category 1 H224:

Extremely flammable liquid and vapor.

Acute toxicity, Category 4 H302:

Harmful if swallowed.

Acute toxicity, Category 4 H332:

Harmful if inhaled.

Serious eye damage, Category 1 H318:

Causes serious eye damage.

Skin sensitization, Category 1 H317:

May cause an allergic skin reaction.

Short-term (acute) aquatic hazard, H400:

Category 1 Very toxic to aquatic life.

SDS Number:100000068741 3/21

Version 4.3 Revision Date 2024-01-29

Long-term (chronic) aquatic hazard, H410:

Category 1 Very toxic to aquatic life with long lasting effects.

2.2

# Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :









Signal Word : Danger

Hazard Statements : H224 Extremely flammable liquid and vapor.

H302 + H332 Harmful if swallowed or if inhaled.
H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H410 Very toxic to aquatic life with long lasting

effects.

Precautionary Statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.
P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection/ hearing

protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/ doctor.

P370 + P378 In case of fire: Use dry sand, dry chemical

or alcohol-resistant foam to extinguish.

P391 Collect spillage.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Hazardous ingredients which must be listed on the label:

• 75-08-1 Ethyl Mercaptan

2.3

Other hazards

Results of PBT and vPvB

assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1%

or higher.

Endocrine disrupting

properties

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

SDS Number:100000068741

Version 4.3 Revision Date 2024-01-29

levels of 0.1% or higher.

#### **SECTION 3: Composition/information on ingredients**

#### 3.1 - 3.2

**Substance or Mixture** 

Synonyms : ETSH

Ethanethiol Ethyl Mercaptan

Molecular formula : C2H6S

#### **Hazardous ingredients**

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]	Specific Conc. Limits, M-factors and ATEs
	75-08-1 200-837-3 016-022-00-9	Flam. Liq. 1; H224 Flam. Liq. 2; H225 Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	99 - 100	M [Acute]=10 M [Chronic]=10

For the full text of the H-Statements mentioned in this Section, see Section 16.

# **SECTION 4: First aid measures**

#### 4.1

# **Description of first-aid measures**

General advice : Move out of dangerous area. Consult a physician. Show this

material safety data sheet to the doctor in attendance. Material

may produce a serious, potentially fatal pneumonia if

swallowed or vomited.

If inhaled : If unconscious, place in recovery position and seek medical

advice. If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a

specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to

an unconscious person. If symptoms persist, call a physician.

Take victim immediately to hospital.

# 4.2 Most important symptoms and effects, both acute and delayed Notes to physician

SDS Number:100000068741 5/21

# Scentinel® A Gas Odorant

Version 4.3 Revision Date 2024-01-29

**Symptoms** No data available.

: No data available. Risks

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No data available.

### **SECTION 5: Firefighting measures**

Flash point -48°C (-54°F)

Method: ASTM D 93

Autoignition temperature : 295°C (563°F)

5.1

**Extinguishing media** 

Suitable extinguishing

media

: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing

media

: High volume water jet.

5.2

Special hazards arising from the substance or mixture

fighting

Specific hazards during fire : Do not allow run-off from fire fighting to enter drains or water

courses.

5.3

Advice for firefighters

Special protective

equipment for fire-fighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

> must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case

of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed

containers.

Fire and explosion

protection

Do not spray on a naked flame or any incandescent material.

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot

surfaces and sources of ignition.

Hazardous decomposition

products

: Carbon oxides. Sulfur oxides.

#### **SECTION 6: Accidental release measures**

# 6.1

#### Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Ensure adequate Personal precautions ventilation. Remove all sources of ignition. Evacuate

personnel to safe areas. Beware of vapors accumulating to

SDS Number:100000068741 6/21

Version 4.3 Revision Date 2024-01-29

form explosive concentrations. Vapors can accumulate in low

areas.

6.2

#### **Environmental precautions**

Environmental precautions : Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

6.3

#### Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

6.4

#### Reference to other sections

Reference to other sections : For personal protection see section 8. For disposal

considerations see section 13.

#### **SECTION 7: Handling and storage**

7.1

# Precautions for safe handling Handling

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid

exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any

process in which this mixture is being used.

Advice on protection against fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot

surfaces and sources of ignition.

7.2

#### Conditions for safe storage, including any incompatibilities

#### **Storage**

Requirements for storage areas and containers

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SDS Number:100000068741 7/21

Version 4.3 Revision Date 2024-01-29

# **SECTION 8: Exposure controls/personal protection**

0	4
o	·T

# Control parameters Ingredients with workplace control parameters

SK				
Zložky	Podstata	Hodnota	Kontrolné parametre	Poznámka
Ethyl Mercaptan	SK OEL	NPEL priemerný	0,5 ppm, 1,3 mg/m3	
, , , , , , , , , , , , , , , , , , , ,	SK OEL	NPEL krátkodobý	1 ppm, 2,6 mg/m3	
Sestavine	Ognova	Vradpast	Doromotri nodzoro	Drinamba
Ethyl Mercaptan	Osnova SI OEL	Vrednost MV	Parametri nadzora 0,5 ppm, 1,3 mg/m3	Pripomba
Ethyl Mercaptan	SI OEL	KTV	1 ppm, 2,6 mg/m3	
	OFFE	IXIV	1 ppm, 2,0 mg/mo	1
RO	1 -	T		T
Componente	Sursă	Valoare	Parametri de control	Notă
Ethyl Mercaptan	RO OEL	STEL	1 mg/m3	
T				
Componentes	Bases	Valor	Parâmetros de	Nota
·			controlo	
Ethyl Mercaptan	PT OEL	VLE-MP	0,5 ppm,	
·L				
Składniki	Podstawa	Wartość	Parametry dotyczące	Uwaga
	· Justawa		kontroli	Juaga
Ethyl Mercaptan	PL NDS	NDS	1 mg/m3	
, ,	PL NDS	NDSch	2 mg/m3	
10				
Komponenter	Grunnlag	Verdi	Kontrollparametrer	Nota
•	FOR-2011-12-06-		'	Nota
Ethyl Mercaptan	1358	GV	0,5 ppm, 1 mg/m3	
A LZ				
<b>ИК</b> Съставки	Основа	Стойност	Параметри на	Бележка
CBCIABRA	Основа	CTOVINOCT	контрол	Бележка
Ethyl Mercaptan	MK OEL	MV	0,5 ppm, 1,3 mg/m3	
	-	· I	-1-	
.V	T =-	T	T =	1
Sastāvdaļas	Bāze	Vērtība	Pārvaldības parametri	Piezīme
Ethyl Mercaptan	LV OEL	AER 8 st	1 mg/m3	
т				
Komponentai	Šaltinis	Vertė	Kontrolės parametrai	Pastaba
Ethyl Mercaptan	LT OEL	IPRD	1 mg/m3	Ο,
O patekimas per ne	epažeistą odą	•		
S				
Komponenter	Grunnlag	Verdi	Kontrollparametrer	Nota
Ethyl Mercaptan	IS OEL	TWA	0.5 ppm. 1 mg/m3	Nota
Lary Wordaptan	10 022	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	o,o ppiii, i iiig/iiio	ı
E				
Components	Basis	Value	Control parameters	Note
Ethyl Mercaptan	IE OEL	OELV - 8 hrs (TWA)	0,5 ppm,	
IU				
Komponensek	Bázis	Érték	Ellenőrzési	Megjegyzés
. temporiorioon	Dazio		paraméterek	
Ethyl Mercaptan	HU OEL	AK-érték	1 mg/m3	N, i,
, ,	HU OEL	CK-érték	2 mg/m3	N, i,
	gatja a bőrt, nyálkahártyát, szem			
N Irritáló anyagok, o	egyszerű fojtógázok, csekély egé	eszségkárosító hatással bí	ró anyagok. Korrekció NEM sz	ükséges.
<del>I</del> R				

HR				
Sastojci	Temelj	Vrijednost	Nadzorni parametri	Bilješka
Ethyl Mercaptan	HR OEL	GVI	0,5 ppm, 1,3 mg/m3	
	HR OEL	KGVI	2 ppm, 5,2 mg/m3	

GR				
Συστατικά	Βάση	Τιμή	Παράμετροι ελέγχου	Σημείωση
SDS Number:100000068741			8/21	

			SAF	ETY DATA SHEET
Scentinel® A Gas	Odorant			
Version 4.3			Revisio	n Date 2024-01-29
Ethyl Mercaptan	GR OEL	TWA	10 ppm, 25 mg/m3	I
	GR OEL	STEL	10 ppm, 25 mg/m3	
GB				
Components	Basis	Value	Control parameters	Note
Ethyl Mercaptan	GB EH40	TWA	0,5 ppm, 1,3 mg/m3	
	GB EH40	STEL	2 ppm, 5,2 mg/m3	
FR		T.v.		T.v.
Composants	Base	Valeur	Paramètres de contrôle	Note
Ethyl Mercaptan	FR VLE	VME	0,5 ppm, 1 mg/m3	Valeurs limites
Valeurs limites Valeurs limites ind		*****	o,o ppin, i mg/mo	indicatives,
indicatives	iodiivoo			
FI				
Aineosat	Peruste	Arvo	Valvontaa koskevat	Huomautus
			muuttujat	
Ethyl Mercaptan	FI OEL	HTP-arvot 15 min	0,5 ppm, 1,3 mg/m3	
ES				
Componentes	Base	Valor	Parámetros de control	Nota
Ethyl Mercaptan	ES VLA	VLA-ED	0,5 ppm, 1,3 mg/m3	
EE				
Komponendid, osad	Alused	Väärtus	Kontrolliparameetrid	Märkused
Ethyl Mercaptan	EE OEL	Piirnorm	0,5 ppm, 1 mg/m3	C,
C Kantserogeensed	ained			
DK				
Komponenter	Basis	Værdi	Kontrolparametre	Note
Ethyl Mercaptan	DK OEL	GV	0,5 ppm, 1 mg/m3	
DE				
Inhaltsstoffe	Grundlage	Wert	Zu überwachende	Bemerkung
50.184			Parameter	
Ethyl Mercaptan  H Hautresorptiv	DE TRGS 900	AGW	0,5 ppm, 1,3 mg/m3	Н,
•				
CH Inhaltsstoffe	Grundlage	Wert	Zu überwachende	Bemerkung
Illianssone	Grundlage	vvert	Parameter	Demerkung
Ethyl Mercaptan	CH SUVA	MAK-Wert	0,5 ppm, 1,3 mg/m3	
	CH SUVA	KZGW	1 ppm, 2,6 mg/m3	
BG				
Съставки	Основа	Стойност	Параметри на	Бележка
			контрол	
Ethyl Mercaptan	BG OEL	TWA	1 mg/m3	
BE				
Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
Ethyl Mercaptan	BE OEL	TGG 8 hr	0,5 ppm, 1,3 mg/m3	
AT				
Inhaltsstoffe	Grundlage	Wert	Zu überwachende	Bemerkung
			Parameter	
Ethyl Mercaptan	AT OEL AT OEL	MAK-KZW MAK-TMW	0,5 ppm, 1,3 mg/m3	
	ATOEL	MAK-TIVIVV	0,5 ppm, 1,3 mg/m3	
DNEL	Routes Potent	se: Workers s of exposure: Inhial health effects: 14,5 mg/m3	nalation Chronic effects, Syster	mic effects
DNEL	Routes Potent Value:	2,06 mg/kg	in contact Chronic effects, Syster	mic effects
DNEL	: End Us	se: Workers		

9/21

SDS Number:100000068741

Version 4.3 Revision Date 2024-01-29

Routes of exposure: Inhalation

Potential health effects: Chronic effects, Local effects

Value: 18,6 mg/m3

PNEC : Fresh water

Value: 0,0001 mg/l

PNEC : Marine water

Value: 0,00001 mg/l

PNEC : Fresh water sediment

Value: 0,00049 mg/kg

PNEC : Marine sediment

Value: 0,000049 mg/kg

PNEC : Soil

Value: 0,000039 mg/kg

8.2

## Exposure controls Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

#### Personal protective equipment

Respiratory protection : If ventilation or other engineering controls are not adequate to

maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. Full-Face Air-Purifying

Respirator for Organic Vapors. Tuli-1 ace All-1 drilying Respirator for Organic Vapors, Dusts and Mists. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

is any indication of degradation of chemical breaking

Eye protection : Eye wash bottle with pure water.

SDS Number:100000068741 10/21

Version 4.3 Revision Date 2024-01-29

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Remove and wash contaminated clothing before re-use. Skin should be washed after contact. Complete head face and neck protection. Rubber apron. Footwear protecting against chemicals.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

For additional details, see the Exposure Scenario in the Annex portion

#### **SECTION 9: Physical and chemical properties**

9.1

### Information on basic physical and chemical properties

**Appearance** 

Form : liquid
Physical state : liquid
Color : Colorless
Odor : Repulsive

Safety data

Flash point : -48°C (-54°F)

Method: ASTM D 93

Lower explosion limit : 2,8 %(V)

Upper explosion limit : 18 %(V)

Oxidizing properties : No

Autoignition temperature : 295°C (563°F)

Molecular formula : C2H6S

Molecular weight : 62,14 g/mol

pH : Not applicable

Pour point : No data available

Initial boiling point and boiling : 35°C (95°F)

range

Vapor pressure : 16,20 PSI

at 37,8°C (100,0°F)

Relative density : 0,84

at 15,6 °C (60,1 °F)

Water solubility : negligible

Partition coefficient: n- : No data available

octanol/water

Viscosity, kinematic : No data available

SDS Number:100000068741 11/21

# Scentinel® A Gas Odorant

Version 4.3 Revision Date 2024-01-29

Relative vapor density : 2,1

(Air = 1.0)

Evaporation rate : 1

Percent volatile : > 99 %

9.2

Other information

Conductivity : No data available

# **SECTION 10: Stability and reactivity**

10.1

**Reactivity** : Stable under recommended storage conditions.

10.2

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature

and pressure.

10.3

Possibility of hazardous reactions

**Hazardous reactions** : Hazardous reactions: Hazardous polymerization does not

occur.

Hazardous reactions: Vapors may form explosive mixture with

air.

10.4

Conditions to avoid : Heat, flames and sparks.

10.5

Materials to avoid : May react with oxygen and strong oxidizing agents, such as

chlorates, nitrates, peroxides, etc.

10.6

Hazardous decomposition

products

: Carbon oxides Sulfur oxides

Canar Oxidoo

Other data : No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

11.1

Information on toxicological effects

**Acute oral toxicity** 

Ethyl Mercaptan : LD50: 682 mg/kg

Species: Rat

SDS Number:100000068741 12/21

Version 4.3 Revision Date 2024-01-29

Sex: male

Method: Fixed Dose Method

Acute inhalation toxicity

Ethyl Mercaptan : LC50: 11,23 mg/l

Exposure time: 4 h Species: Rat Sex: male

Test atmosphere: vapor

Skin irritation

Ethyl Mercaptan : slight irritation.

Eye irritation

Ethyl Mercaptan : Risk of serious damage to eyes.

Sensitization

Ethyl Mercaptan : The product is a skin sensitizer, sub-category 1B.

Information given is based on data obtained from similar

substances.

Repeated dose toxicity

Ethyl Mercaptan : Species: Rat, Male and female

Sex: Male and female Application Route: Inhalation Dose: 25, 100, 400 ppm Exposure time: 13 wks

Number of exposures: 6 hr/d, 5 d/wk

NOEL: 100 ppm

Lowest observable effect level: 400 ppm

Method: OECD Guideline 413

Information given is based on data obtained from similar

13/21

substances.

SDS Number:100000068741

Version 4.3 Revision Date 2024-01-29

Species: Rat, Male and female

Sex: Male and female Application Route: Oral Dose: 0, 10, 50, 200 mg/kg Exposure time: 42-53 days

NOEL: 50 mg/kg

Method: OECD Guideline 422

Information given is based on data obtained from similar

substances.

Species: Rat, Male and female

Sex: Male and female Application Route: Inhalation Dose: 9, 97, 196 ppm Exposure time: 13 wks

Number of exposures: 6 hr/d, 5 d/wk

NOEL: >=196 ppm

Method: OECD Guideline 413

Information given is based on data obtained from similar

substances.

Species: Rat, Male and female

Sex: Male and female Application Route: Inhalation Dose: 0.03, 0.26, 0.55 mg/L Exposure time: 13 wks

Number of exposures: 6 hr/d, 5 d/wk

NOEL: 0,03 mg/l

Method: OECD Test Guideline 413

Information given is based on data obtained from similar

substances.

#### Genotoxicity in vitro

Ethyl Mercaptan : Test Type: Ames test

Metabolic activation: with and without metabolic activation Method: Mutagenicity (Escherichia coli - reverse mutation

assay)

Result: negative

Test Type: Mouse lymphoma assay Method: OECD Guideline 476

Result: Ambiguous

Test Type: Sister Chromatid Exchange Assay

Metabolic activation: with and without metabolic activation

Result: positive

Test Type: Micronucleus test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative

#### Genotoxicity in vivo

Ethyl Mercaptan : Test Type: Micronucleus test

Species: Mouse

Method: Mutagenicity (micronucleus test)

Result: negative

SDS Number:100000068741 14/21

Version 4.3 Revision Date 2024-01-29

#### Reproductive toxicity

Ethyl Mercaptan : Species: Rat

Sex: male and female Application Route: Oral diet Dose: 0, 10, 50, 200 mg/kg Exposure time: 42-53 days Number of exposures: once daily Method: OECD Guideline 422 NOAEL Parent: 200 mg/kg NOAEL F1: 50 mg/kg

Information given is based on data obtained from similar

substances.

#### **Developmental Toxicity**

Ethyl Mercaptan : Species: Rat

Application Route: Inhalation Dose: 0, 0.037, 0.28, or 0.56 mg/L Number of exposures: 6 hrs/d

Test period: GD 6-19

Method: OECD Guideline 414 NOAEL Teratogenicity: > 0,56 mg/l

Information given is based on data obtained from similar

substances.

Species: Rat

Application Route: Inhalation Dose: 0, 10, 100, 200 ppm Number of exposures: 6 hrs/d

Test period: GD 6-19

Method: OECD Guideline 414 NOAEL Teratogenicity: > 200 ppm NOAEL Maternal: > 200 ppm

Information given is based on data obtained from similar

substances.

#### **Aspiration toxicity**

Ethyl Mercaptan : May be harmful if swallowed and enters airways.

**CMR** effects

Ethyl Mercaptan : Carcinogenicity: Not available

Mutagenicity: Not mutagenic in Ames Test.

Teratogenicity: Animal testing did not show any effects on

fetal development.

Reproductive toxicity: Animal testing did not show any effects

on fertility.

11.2

Information on other hazards

Scentinel® A Gas Odorant

**Further information** : Solvents may degrease the skin. Inhalation of high vapor

concentrations may cause symptoms like headache,

15/21

dizziness, tiredness, nausea and vomiting.

SDS Number:100000068741

Version 4.3 Revision Date 2024-01-29

Endocrine disrupting

properties

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### **SECTION 12: Ecological information**

# 12.1

# **Toxicity**

## Toxicity to fish

Ethyl Mercaptan : 2,4 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 203

# Toxicity to daphnia and other aquatic invertebrates

Ethyl Mercaptan : EC50: < 0,1 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea) static test Method: OECD Test Guideline 202

#### Toxicity to algae

Ethyl Mercaptan : EC50: 3 mg/l

Exposure time: 72 h

Species: Pseudokirchneriella subcapitata (green algae)

Method: OECD Test Guideline 201

M-Factor

ethanethiol : M-Factor (Acute Aquat. Tox.) 10

M-Factor (Chron. Aquat. Tox.) 10

## 12.2

# Persistence and degradability

Biodegradability

Ethyl Mercaptan : aerobic

Result: Not readily biodegradable.

0 %

Testing period: 29 d

Method: OECD Test Guideline 301F

#### 12.3

# **Bioaccumulative potential**

Elimination information (persistence and degradability)

Bioaccumulation : This material is not expected to bioaccumulate.

SDS Number:100000068741 16/21

Version 4.3 Revision Date 2024-01-29

#### 12.4

# Mobility in soil

Mobility

Ethyl Mercaptan : The product will be dispersed amongst the various environmental compartments (soil/ water/ air).

#### 12.5

#### Results of PBT and vPvB assessment

Results of PBT assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6

#### **Endocrine disrupting properties**

Endocrine disrupting

properties

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7

#### Other adverse effects

Additional ecological

information

: Very toxic to aquatic life with long lasting effects.

#### 12.8

#### **Additional Information**

# **Ecotoxicology Assessment**

Short-term (acute) aquatic hazard

Ethyl Mercaptan : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard

Ethyl Mercaptan : Very toxic to aquatic life with long lasting effects.

# **SECTION 13: Disposal considerations**

#### 13.1

#### Waste treatment methods

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water

courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed

SDS Number:100000068741 17/21

# Scentinel® A Gas Odorant

Version 4.3 Revision Date 2024-01-29

waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

Do not re-use empty containers. Do not burn, or use a cutting

torch on, the empty drum.

For additional details, see the Exposure Scenario in the Annex portion

#### **SECTION 14: Transport information**

#### 14.1 - 14.7

#### **Transport information**

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

#### **US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

UN2363, ETHYL MERCAPTAN, 3, I, MARINE POLLUTANT, (ETHYL MERCAPTAN)

#### **IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

UN2363, ETHYL MERCAPTAN, 3, I, (-48 °C c.c.), MARINE POLLUTANT, (ETHYL MERCAPTAN)

### IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN2363, ETHYL MERCAPTAN, 3, I

# ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN2363, ETHYL MERCAPTAN, 3, I, (D/E), ENVIRONMENTALLY HAZARDOUS, (ETHYL MERCAPTAN)

# RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

33,UN2363,ETHYL MERCAPTAN, 3, I, ENVIRONMENTALLY HAZARDOUS, (ETHYL MERCAPTAN)

# ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN2363, ETHYL MERCAPTAN, 3, I, ENVIRONMENTALLY HAZARDOUS, (ETHYL MERCAPTAN)

# Maritime transport in bulk according to IMO instruments

SDS Number:100000068741 18/21

Version 4.3 Revision Date 2024-01-29

#### **SECTION 15: Regulatory information**

#### 15.1

#### Safety, health and environmental regulations/legislation specific for the substance or mixture **National legislation**

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Water hazard class

(Germany)

: WGK 3 highly water endangering

#### 15.2

#### **Chemical Safety Assessment**

Components : ethanethiol A Chemical Safety Assessment 200-837-3

has been carried out for this

substance.

**Major Accident Hazard** 

Legislation

Update: 2003 : 96/82/EC

Highly flammable

Quantity 1: 5.000 t Quantity 2: 50.000 t

96/82/EC Update: 2003 Dangerous for the environment

Quantity 1: 100 t Quantity 2: 200 t

: ZEU\_SEVES3 Update: FLAMMABLE LIQUIDS

P5a

Quantity 1: 10 t Quantity 2: 50 t

: ZEU SEVES3 Update:

**ENVIRONMENTAL HAZARDS** 

E1

Quantity 1: 100 t Quantity 2: 200 t

#### **Notification status**

Other AICS

Europe REACH This product is in full compliance according to REACH

regulation 1907/2006/EC.

Switzerland CH INV On the inventory, or in compliance with the inventory

United States of America (USA) On or in compliance with the active portion of the

**TSCA** TSCA inventory

Canada DSL All components of this product are on the Canadian

On the inventory, or in compliance with the inventory New Zealand NZIoC On the inventory, or in compliance with the inventory Japan ENCS On the inventory, or in compliance with the inventory Korea KECI All substances in this product were registered, notified

> to be registered, or exempted from registration by CPChem through an Only Representative according to K-REACH regulations. Importation of this product is

SDS Number:100000068741 19/21

# Scentinel® A Gas Odorant

Version 4.3 Revision Date 2024-01-29

permitted if the Korean Importer of Record was

included on CPChem's notifications or if the Importer of

Record themselves notified the substances.

Philippines PICCS : On the inventory, or in compliance with the inventory China IECSC : On the inventory, or in compliance with the inventory Taiwan TCSI : On the inventory, or in compliance with the inventory

#### **SECTION 16: Other information**

NFPA Classification : Health Hazard: 3

Fire Hazard: 4 Reactivity Hazard: 0



#### **Further information**

Legacy SDS Number : 25580

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery

SDS Number:100000068741 20/21

# Scentinel® A Gas Odorant

Version 4.3 Revision Date 2024-01-29

			Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate

# Full text of H-Statements referred to under sections 2 and 3.

H224	Extremely flammable liquid and vapor.
H225	Highly flammable liquid and vapor.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

SDS Number:100000068741 21/21