### SAFETY DATA SHEET



## Marlex® 9118 Polyethylene

Version 1.2

Revision Date 2024-06-23

CTION 1: Identification of	the substance/mixture and of the company/undertaking
<b>Product information</b> Product Name Material	: Marlex® 9118 Polyethylene : 1125138
Company	: Chevron Phillips Chemical Company LP 10001 Six Pines Drive The Woodlands, TX 77380
Emergency telephone:	
Asia: CHEMWATCH ( Mexico CHEMTREC ( South America SOS-C Argentina: +(54)-1159 EUROPE: BIG +32.14 Austria: VIZ +43 1 406 Belgium: 070 245 245 Bulgaria: +359 2 9154 Croatia: +359 2 9154 Croatia: +3851 2348 3 Cyprus: 1401 Czech Republic: Toxic Denmark: Danish Pois Estonia: BIG +32.14.5 Finland: 0800 147 111 France: ORFILA numb Germany: BIG +32.14 Greece: (0030) 21077 Hungary: +36-80-201- Iceland: 543 2222 (24	national) 9300 or 703.527.3887(int'l) +612 9186 1132) China: 0532 8388 9090 01-800-681-9531 (24 hours) Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600 839431 .584545 (phone) or +32.14583516 (telefax) 5 43 43 (24 hours/day, 7 days/week) (24 hours/day, 7 days/week)
Number:100000104516	1/12

SAFETY DATA SHEET

Version 1.2

Revision Date 2024-06-23

Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME - Policlinico "Agostino Gemelli", Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME - Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico "Umberto I" Tel. +39 06 4997 8000; POISON CENTER FOGGIA - Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera "Antonio Cardarelli" Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA - IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO - Azienda Ospedaliera "Papa Giovanni XXIII" Tel. 800 883 300; POISON CENTER VERONA - Azienda Ospedaliera Universitaria integrata Tel. 800 011 858: Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.) Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Lithuania: +370 (85) 2362052 Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week) Malta: +356 2395 2000 The Netherlands: NVIC: +31 (0)88 755 8000 Norway: 22 59 13 00 (24 hours/day, 7 days/week) Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Portugal: CIAV phone number: +351 800 250 250 Romania: +40213183606 Slovakia: +421 2 5477 4166 Slovenia: Phone number: 112 Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week) Sweden: 112 - ask for Poisons Information : Product Safety and Toxicology Group Responsible Department SDS@CPChem.com E-mail address Website www.CPChem.com : MEDICAL APPLICATION CAUTION: Do not use this material in medical applications involving permanent implantation in the human body or permanent contact with internal body fluids or tissues fluids or tissues.

Do not use this material in medical applications involving brief or temporary implantation in the human body or contact with internal body fluids or tissues unless the material has been provided directly from Chevron Phillips Chemical Company LP or its legal affiliates under an agreement which expressly acknowledges the contemplated use.

Chevron Phillips Chemical Company LP and its legal affiliates makes no representation, promise, express warranty or implied warranty concerning the suitability of this material for use in implantation in the human body or in contact with internal body fluids or tissues.

#### **SECTION 2: Hazards identification**

•	ubstance or mixture classified in accordance with the hazard communication standard 29 CFR d labels contain all the information as required by the standard.
Classification	: Combustible dust
Labeling	

SDS Number:100000104516

SAFETY DATA SHEET

## Marlex® 9118 Polyethylene

Marlex <sup>®</sup> 9118 Polyet	hylene			
Version 1.2			Revision Date 2024-06-23	
Signal Word	: Warni	ng		
Hazard Statements	Whil furth	e this product may	dust concentrations in air. not be a combustible dust as sold, andling may form combustible dust	
Potential Health Effects				
Physical Hazards	Mechai concen	nical processing m	azard on hard surfaces. ay form combustible dust hermal processing at elevated te formaldebyde	
Inhalation	: Repeat respira Fumes	ted exposure to duation to the total to the total tota	st from this material may cause hermal processing may cause	
Skin	: Contac signific Contac respon If this n Therma	t with the skin is no ant irritation. t with the skin is no se. naterial is heated, t al burns may incluo	ot expected to cause prolonged or ot expected to cause an allergic hermal burns may result from contact. le pain or feeling of heat,	
Eyes	: Contac action. Not exp	pected to cause pro	of bistering. y cause irritation due to the abrasive blonged or significant eye irritation. if heated material contacts eye.	
Ingestion			s not a likely route of exposure.	
Carcinogenicity:				
IARC	equal to		ct present at levels greater than or as probable, possible or confirmed 2.	
NTP	No ingre equal to	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.		
SECTION 3: Composition/inf	ormation on	ingredients		
		_		
Component		CAS-No.	Weight %	
Polyethylene Hexene Cop	olymer	25213-02-9	99 - 100	
SECTION 4: First aid measur	res			
If inhaled	fumes		of accidental inhalation of dust or or combustion. If symptoms persist,	
In case of skin contact		: If the molten material gets on skin, quickly cool in water. Seek immediate medical attention. Do not try to peel the solidified		
SDS Number:100000104516			3/12	

rlav@ 0119 Dalvath	40	SAFETY DATA SH
rlex® 9118 Polyethy sion 1.2	yie	Revision Date 2024-0
5011 1.2		material from the skin or use solvents or thinners to dissolve it.
In anno of ave contact	:	
In case of eye contact	•	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
If swallowed	:	Do not induce vomiting without medical advice.
TION 5: Firefighting measu	res	
Flash point	:	No data available
Autoignition temperature	:	No data available
Suitable extinguishing media	:	Water. Water mist. Dry chemical. Carbon dioxide (CO2). Foam. If possible, water should be applied as a spray from a fogging nozzle since this is a surface burning material. The application of high velocity water will spread the burning surface layer. Avoid the use of straight streams that may create a dust cloud and the risk of a dust explosion. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Specific hazards during fire fighting	:	Risks of ignition followed by flame propagation or secondary explosions can be caused by the accumulation of dust, e.g. on floors and ledges.
Special protective equipment for fire-fighters	:	Use personal protective equipment. Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	This material will burn although it is not easily ignited.
Fire and explosion protection	:	Treat as a solid that can burn. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Hazardous decomposition products	:	Normal combustion forms carbon dioxide, water vapor and may produce carbon monoxide, other hydrocarbons and hydrocarbon oxidation products (ketones, aldehydes, organic acids) depending on temperature and air availability. Incomplete combustion can also produce formaldehyde.
TION 6: Accidental release	me	asures
Personal precautions	:	Sweep up to prevent slipping hazard. Avoid breathing dust. Avoid dust formation.
Environmental precautions	:	Do not contaminate surface water. Prevent product from entering drains.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum.
Additional advice	:	Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid
Number:100000104516		4/12

SAFETY DATA SHEET

Version 1.2

Revision Date 2024-06-23

dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).

#### **SECTION 7: Handling and storage**

Handling		
Advice on safe handling	:	Use good housekeeping for safe handling of the product. Keep out of water sources and sewers. Spilled pellets may create a slipping hazard. Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient. At elevated temperatures (>350°F, >177°C), polyethylene can release vapors and gases, which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. These substances may include acetaldehyde, acetone, acetic acid, formic acid, formaldehyde and acrolein. Based on animal data and limited epidemiological evidence, formaldehyde has been listed as a carcinogen. Following all recommendations within this SDS should minimize exposure to thermal processing emissions.
Advice on protection against fire and explosion	:	Treat as a solid that can burn. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Storage		
Requirements for storage areas and containers	:	Keep in a dry place. Keep in a well-ventilated place.
Advice on common storage	:	Do not store together with oxidizing and self-igniting products.

#### **SECTION 8: Exposure controls/personal protection**

#### Ingredients with workplace control parameters

#### US

Components	Basis	Value	Control parameters	Note
Nuisance Dust	OSHA Z-3	TWA	15 mg/m3	Total dust
	OSHA Z-3	TWA	5 mg/m3	(respirable dust)

Control as Particulate Not Otherwise Classified (PNOC). The ACGIH Guideline\* for respirable dust is 3.0 mg/m3 and 10.0 mg/m3 for total dust. The OSHA PEL for respirable dust is 5.0 mg/m3 and 15.0 mg/m3 for total dust.

\* This value is for inhalable (total) particulate matter containing no asbestos and < 1.0% crystalline silica.

#### **Engineering measures**

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

SDS Number:100000104516

SAFETY DATA SHEET

Version 1.2

Revision Date 2024-06-23

Respiratory protection	<ul> <li>No respiratory protection is normally required. If heated material generates vapor or fumes that are not adequately controlled by ventilation, wear an appropriate respirator. Use the following elements for air-purifying respirators: Organic Vapor and Formaldehyde. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.</li> <li>Dust safety masks are recommended when the dust concentration is excessive.</li> </ul>
Eye protection	: Use of safety glasses with side shields for solid handling is good industrial practice. If this material is heated, wear chemical goggles or safety glasses with side shields or a face shield. If there is potential for dust, use chemical goggles.
Skin and body protection	: At ambient temperatures use of clean and protective clothing is good industrial practice. If the material is heated or molten, wear thermally insulated, heat-resistant gloves that are able to withstand the temperature of the molten product. If this
	material is heated, wear insulated clothing to prevent skin contact if engineering controls or work practices are not adequate.
TION 9: Physical and cher	contact if engineering controls or work practices are not adequate.
-	contact if engineering controls or work practices are not adequate.
	contact if engineering controls or work practices are not adequate.
Information on basic phys Appearance	contact if engineering controls or work practices are not adequate. mical properties sical and chemical properties
Information on basic phys Appearance Form	contact if engineering controls or work practices are not adequate.
Information on basic phys Appearance Form Physical state Color	contact if engineering controls or work practices are not adequate. mical properties sical and chemical properties : Pellets : solid : Opaque
Information on basic phys Appearance Form Physical state Color Odor	contact if engineering controls or work practices are not adequate. mical properties sical and chemical properties : Pellets : solid : Opaque : Mild to no odor
Information on basic phys Appearance Form Physical state Color	contact if engineering controls or work practices are not adequate. mical properties sical and chemical properties : Pellets : solid : Opaque
Information on basic phys Appearance Form Physical state Color Odor	contact if engineering controls or work practices are not adequate. mical properties sical and chemical properties : Pellets : solid : Opaque : Mild to no odor
Information on basic phys Appearance Form Physical state Color Odor Odor Threshold	contact if engineering controls or work practices are not adequate. mical properties sical and chemical properties : Pellets : solid : Opaque : Mild to no odor
Information on basic phys Appearance Form Physical state Color Odor Odor Threshold Safety data	contact if engineering controls or work practices are not adequate. mical properties sical and chemical properties : Pellets : Solid : Opaque : Mild to no odor : No data available
Information on basic phys Appearance Form Physical state Color Odor Odor Threshold Safety data Flash point	contact if engineering controls or work practices are not adequate. mical properties sical and chemical properties : Pellets : solid : Opaque : Mild to no odor : No data available : No data available
Information on basic phys Appearance Form Physical state Color Odor Odor Threshold Safety data Flash point Lower explosion limit	contact if engineering controls or work practices are not adequate. mical properties sical and chemical properties : Pellets : solid : Opaque : Mild to no odor : No data available : No data available : Not applicable
Information on basic phys Appearance Form Physical state Color Odor Odor Threshold Safety data Flash point Lower explosion limit Upper explosion limit	contact if engineering controls or work practices are not adequate. mical properties sical and chemical properties : Pellets : solid : Opaque : Mild to no odor : No data available : No data available : Not applicable : Not applicable
Information on basic phys Appearance Form Physical state Color Odor Odor Threshold Safety data Flash point Lower explosion limit Upper explosion limit Autoignition temperature	contact if engineering controls or work practices are not adequate. mical properties sical and chemical properties : Pellets : solid : Opaque : Mild to no odor : No data available : Not data available : Not applicable : Not applicable : No data available : Low molecular weight hydrocarbons, alcohols, aldehydes,

rlex® 9118 Polyethyl	SAFETY DATA SH
sion 1.2	Revision Date 2024-0
Melting point/range	: 90-140°C (194-284°F)
Freezing point	Not applicable
Initial boiling point and boiling range	: Not applicable
Vapor pressure	: Not applicable
Relative density	: Not applicable
Density	: 0.91 - 0.97 g/cm3 Please refer to the Technical Data Sheet (TDS) for more detailed information relating to the nominal physical properties, including density, of this polyethylene resin grade.
Water solubility	: negligible
Partition coefficient: n- octanol/water	: No data available
Solubility in other solvents	: No data available
Viscosity, dynamic	: Not applicable
Viscosity, kinematic	: Not applicable
Relative vapor density	: Not applicable
Evaporation rate	: Not applicable
TION 10: Stability and reactiv	/ity
Reactivity	: This material is considered non-reactive under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous rea	ctions
Conditions to avoid	: Avoid prolonged storage at elevated temperature.
Materials to avoid	: Avoid contact with strong oxidizing agents.
	: Low molecular weight hydrocarbons, alcohols, aldehydes, acids and ketones can be formed during thermal processing.
Thermal decomposition	

rlex <sup>®</sup> 9118 Polyethy	lene
sion 1.2	Revision Date 2024-00
	acids) depending on temperature and air availability. Incomplete combustion can also produce formaldehyde.
Other data	: No decomposition if stored and applied as directed.
CTION 11: Toxicological infor	mation
Marlex® 9118 Polyethylene Acute oral toxicity	: Presumed Not Toxic
Marlex® 9118 Polyethylene Acute inhalation toxicity	: Presumed Not Toxic
Marlex® 9118 Polyethylene Acute dermal toxicity	: Presumed Not Toxic
Marlex® 9118 Polyethylene Skin irritation	: No skin irritation
Marlex® 9118 Polyethylene Eye irritation	: No eye irritation
Marlex® 9118 Polyethylene Sensitization	: Did not cause sensitization on laboratory animals.
Marlex® 9118 Polyethylene Further information	: This product contains POLYMERIZED OLEFINS. During thermal processing (>350°F, >177°C) polyolefins can release vapors and gases (aldehydes,ketones and organic acids) which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. Generally these irritant effects are all transitory. However, prolonged exposure to irritating off-gases can lead to pulmonary edema. Formaldehyde (an aldehyde) has been classified as a carcinogen based on animal data and limited epidemiological evidence.
CTION 12: Ecological informa	tion
Ecotoxicity effects	
Biodegradability	: This material is not expected to be readily biodegradable.
Elimination information (persis	stence and degradability)
Bioaccumulation	: Does not bioaccumulate.
S Number:100000104516	8/12

	lene
arlex® 9118 Polyethy rsion 1.2	Revision Date 2024-06-
Mobility	: The product is insoluble and floats on water.
Additional ecological information	<ul> <li>This material is not expected to be harmful to aquatic organisms., Fish or birds may eat pellets which may obstruct their digestive tracts.</li> </ul>
Ecotoxicology Assessment	
Short-term (acute) aquatic	: This product has no known ecotoxicological effects.
hazard Long-term (chronic) aquatic hazard	: This product has no known ecotoxicological effects.
CTION 13: Disposal consider	ations
The information in this SDS p	pertains only to the product as shipped.
may meet the criteria of a haz other State and local regulation regulated components may be	purpose or recycle if possible. This material, if it must be discarded, zardous waste as defined by US EPA under RCRA (40 CFR 261) or ons. Measurement of certain physical properties and analysis for the necessary to make a correct determination. If this material is ste, federal law requires disposal at a licensed hazardous waste
CTION 14: Transport information	tion
	shown here are for bulk shipments only, and may not apply to kages (see regulatory definition).
Goods Regulations for additionetc.) Therefore, the information	estic or international mode-specific and quantity-specific Dangerous onal shipping description requirements (e.g., technical name or name on shown here, may not always agree with the bill of lading shipping Flashpoints for the material may vary slightly between the SDS and th
	<b>DEPARTMENT OF TRANSPORTATION)</b> HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR THIS AGENCY.
	<b>AL MARITIME DANGEROUS GOODS)</b> HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR THIS AGENCY.
	R TRANSPORT ASSOCIATION) HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR THIS AGENCY.
	<b>NGEROUS GOODS BY ROAD (EUROPE))</b> HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR THIS AGENCY.
RID (REGULATIONS CONCI DANGEROUS GOODS (EUR	ERNING THE INTERNATIONAL TRANSPORT OF ROPE))
(	

### Marlex® 9118 Polyethylene Version 1.2 Revision Date 2024-06-23 NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY. ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS) NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY. Maritime transport in bulk according to IMO instruments **SECTION 15: Regulatory information** National legislation SARA 311/312 Hazards : Combustible dust CERCLA Reportable : This material does not contain any components with a CERCLA Quantity RQ. SARA 302 Reportable : This material does not contain any components with a SARA 302 RQ. Quantity SARA 302 Threshold : No chemicals in this material are subject to the reporting Planning Quantity requirements of SARA Title III, Section 302. : This material does not contain any components with a section SARA 304 Reportable Quantity 304 EHS RQ. SARA 313 Components : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313. **Clean Air Act** Ozone-Depletion : This product neither contains, nor was manufactured with a Class I or Potential Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61). This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F). SDS Number:100000104516 10/12

orlav® 0119 Dalvathyla	SAFETY DATA SHEE
arlex® 9118 Polyethyle rsion 1.2	Revision Date 2024-06-
	ny chemicals listed under the U.S. Clean Air Act Section 111 SOC
US State Regulations	
Pennsylvania Right To Know :	No components are subject to the Pennsylvania Right to Know Act.
California Prop. 65 : Components	This product, as shipped, does not contain any carcinogens or reproductive toxins presently known by the State of California to cause cancer or reproductive toxicity at a level of exposure subject to the requirements of California Proposition 65.
Notification status Europe REACH Switzerland CH INV United States of America (USA) TSCA Canada DSL Other AIIC New Zealand NZIoC Japan ENCS Korea KECI	<ul> <li>This product is in full compliance according to REACH regulation 1907/2006/EC.</li> <li>On the inventory, or in compliance with the inventory</li> <li>On or in compliance with the active portion of the TSCA inventory</li> <li>All components of this product are on the Canadian DSL</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>Description of this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s).</li> </ul>
Philippines PICCS China IECSC Taiwan TCSI	<ul> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> <li>On the inventory, or in compliance with the inventory</li> </ul>
CTION 16: Other information	
NFPA Classification :	Health Hazard: 0 Fire Hazard: 1 Reactivity Hazard: 0
Further information	· ·
S Number:100000104516	11/12

#### Version 1.2

Revision Date 2024-06-23

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Ke	ey or legend to abbreviations and a	cronyms used i	n the safety data sheet
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate