

**Toluene Standardization Fuel 85.2**

Version 1.2

Revision Date 2024-10-01

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : Toluene Standardization Fuel 85.2
Material : 1024335, 1024338, 1024337, 1024336

Use : Reference Fuel

Company : Chevron Phillips Chemical Company LP
Specialty Chemicals
10001 Six Pines Drive
The Woodlands, TX 77380

Emergency telephone:**Health:**

866.442.9628 (North America)
1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)
Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090
Mexico CHEMTREC 01-800-681-9531 (24 hours)
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600
Argentina: +(54)-1159839431
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)
Belgium: 070 245 245 (24 hours/day, 7 days/week)
Bulgaria: +359 2 9154 233
Croatia: +3851 2348 342 (24 hours/day, 7 days/week)
Cyprus: 1401
Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402
Denmark: Danish Poison Center (Gifftlinjen): +45 8212 1212
Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Finland: 0800 147 111 09 471 977 (24 hours/day)
France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)
Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Greece: (0030) 2107793777 (24 hours/day, 7 days/week)
Hungary: +36-80-201-199 (24 hours/day, 7 days/week)
Iceland: 543 2222 (24 hours/day, 7 days/week)
Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico “Agostino Gemelli”, Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico “Umberto I” Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera “Antonio Cardarelli” Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera “Papa Giovanni XXIII” Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011 858;

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000

Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606

Slovakia: +421 2 5477 4166

Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Classification

: Flammable liquids, Category 2
 Skin irritation, Category 2
 Reproductive toxicity, Category 2
 Specific target organ toxicity - single exposure, Category 3,
 Central nervous system
 Specific target organ toxicity - repeated exposure, Category 2,
 Inhalation, Auditory organs, color vision
 Aspiration hazard, Category 1

Labeling

Symbol(s) :



Signal Word :

: Danger

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

Hazard Statements : H225: Highly flammable liquid and vapor.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H336: May cause drowsiness or dizziness.
 H361d: Suspected of damaging the unborn child.
 H373: May cause damage to organs (Auditory organs, color vision) through prolonged or repeated exposure if inhaled.

Precautionary Statements : **Prevention:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity:**IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

by NTP.

SECTION 3: Composition/information on ingredients

Synonyms : Reference Fuel

Molecular formula : Mixture

Component	CAS-No.	Weight %
Toluene	108-88-3	65.7 - 66.3
n-Heptane	142-82-5	33.7 - 34.3
Benzene	71-43-2	0 - 0.04

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5: Firefighting measures

Flash point : -4°C (25°F)
estimated

Autoignition temperature : 204-408°C (399-766°F)
estimated

Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.

Unsuitable extinguishing media : High volume water jet.

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hazardous decomposition products : Carbon oxides.

SECTION 6: Accidental release measures

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

- Advice on safe handling : Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient. Review all operations, which have the potential to generating and accumulation of electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106 "Flammable and Combustible Liquids"; National Fire Protection Association (NFPA 77), "Recommended Practice on Static Electricity"; and/or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising Out of Static, Lightning, and stray Currents". Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Use : Reference Fuel

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****US**

Components	Basis	Value	Control parameters	Note
Toluene	ACGIH	TWA	20 ppm,	A4,
	OSHA Z-2	TWA	200 ppm,	
	OSHA Z-2	CEIL	300 ppm,	
	OSHA Z-2	Peak	500 ppm,	
	OSHA Z-1-A	TWA	100 ppm, 375 mg/m3	
n-Heptane	OSHA Z-1-A	STEL	150 ppm, 560 mg/m3	
	OSHA Z-1	TWA	500 ppm, 2,000 mg/m3	
	OSHA Z-1-A	TWA	400 ppm, 1,600 mg/m3	
	OSHA Z-1-A	STEL	500 ppm, 2,000 mg/m3	
	ACGIH	TWA	400 ppm,	
	ACGIH	STEL	500 ppm,	

A4 Not classifiable as a human carcinogen

Immediately Dangerous to Life or Health Concentrations (IDLH)

Substance name	CAS-No.	Control parameters	Update
Toluene	108-88-3	Immediately Dangerous to Life or Health Concentration Value 500 parts per million	1995-03-01
n-Heptane	142-82-5	Immediately Dangerous to Life or Health Concentration Value 750 parts per million	1995-03-01
Benzene	71-43-2	Immediately Dangerous to Life or Health Concentration Value 500 parts per million	1995-03-01
Toluene	108-88-3	Immediately Dangerous to Life or Health Concentration Value 500 parts per million	1995-03-01
n-Heptane	142-82-5	Immediately Dangerous to Life or Health Concentration Value 750 parts per million	1995-03-01

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

Biological exposure indices**US**

Substance name	CAS-No.	Control parameters	Sampling time	Update
Toluene	108-88-3	Toluene: 0.02 mg/l (In blood)	Prior to last shift of workweek	2010-03-01
		Toluene: 0.03 mg/l (Urine)	End of shift (As soon as possible after exposure ceases)	2010-03-01
		o-Cresol: 0.3 mg/g Creatinine Background (Urine) With hydrolyses ()	End of shift (As soon as possible after exposure ceases)	2010-03-01
Benzene	71-43-2	S-Phenylmercapturic acid: 25 µg/g creatinine Background (Urine)	End of shift (As soon as possible after exposure ceases)	2010-03-01
		t,t-Muconic acid: 500 µg/g creatinine Background (Urine)	End of shift (As soon as possible after exposure ceases)	2010-03-01
Toluene	108-88-3	Toluene: 0.02 mg/l (In blood)	Prior to last shift of workweek	2010-03-01
		Toluene: 0.03 mg/l (Urine)	End of shift (As soon as possible after exposure ceases)	2010-03-01
		o-Cresol: 0.3 mg/g Creatinine Background (Urine) With hydrolyses ()	End of shift (As soon as possible after exposure ceases)	2010-03-01

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

	is any indication of degradation or chemical breakthrough.
Eye protection	: Eye wash bottle with pure water. Tightly fitting safety goggles.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

Form	: Non-viscous
Physical state	: liquid
Color	: clear
Odor	: Strong gasoline

Safety data

Flash point	: -4°C (25°F) estimated
Lower explosion limit	: 1 %(V)
Upper explosion limit	: 7.1 %(V)
Oxidizing properties	: No
Autoignition temperature	: 204-408°C (399-766°F) estimated
Molecular formula	: Mixture
Molecular weight	: No data available
pH	: Not applicable
Freezing point	: No data available
Pour point	: No data available
Boiling point/boiling range	: 98-111°C (208-232°F) estimated
Vapor pressure	: No data available
Relative density	: 0.808 at 15.6 °C (60.1 °F)
Water solubility	: negligible

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Relative vapor density	: No data available
Evaporation rate	: No data available
Percent volatile	: > 99 %

SECTION 10: Stability and reactivity

Reactivity	: Stable under recommended storage conditions.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions	
Hazardous reactions	: Hazardous reactions: Hazardous polymerization does not occur. Hazardous reactions: Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Hazardous decomposition products	: Carbon oxides
Other data	: No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Toluene Standardization Fuel 85.2	
Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Toluene Standardization Fuel 85.2	
Acute inhalation toxicity	: Acute toxicity estimate: 37.88 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
	Acute toxicity estimate: 25 mg/l Exposure time: 4 h

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

Test atmosphere: vapor
Method: Calculation method

Acute toxicity estimate: 25 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Toluene Standardization Fuel 85.2

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Toluene Standardization Fuel 85.2

Skin irritation : Skin irritation
largely based on animal evidence.
May cause skin irritation in susceptible persons.

Toluene Standardization Fuel 85.2

Eye irritation : Vapors may cause irritation to the eyes, respiratory system
and the skin.

Toluene Standardization Fuel 85.2

Sensitization : Did not cause sensitization on laboratory animals.

Repeated dose toxicity

Toluene : Species: Rat
Application Route: Inhalation
Dose: 0, 100, 625, 1250, 3000 ppm
Exposure time: 15 wk
Number of exposures: 6.5 h/d, 5 d/wk
NOEL: 625 ppm

Species: Mouse
Application Route: Inhalation
Dose: 0, 100, 625, 1250, 3000 ppm
Exposure time: 14 wk
Number of exposures: 6.5 h/d, 5 d/wk
NOEL: 100 ppm

n-Heptane : Species: Rat, male
Sex: male
Application Route: Inhalation
Dose: 12.47 mg/l
Exposure time: 16 wk
Number of exposures: 12 h/d, 7 d/wk
NOEL: 12.47 mg/l
No adverse effect has been observed in chronic toxicity tests.

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

Species: Rat, Male and female
 Sex: Male and female
 Application Route: Inhalation
 Dose: 12.35 mg/l
 Exposure time: 26 wk
 Number of exposures: 6 h/d, 5 d/wk
 Method: OECD Test Guideline 413
 No adverse effect has been observed in chronic toxicity tests.

Benzene

Species: Rat, female
 Sex: female
 Application Route: oral gavage
 Dose: 0, 25, 50, 100 mg/kg
 Exposure time: 103 wk
 Number of exposures: 5 d/wk
 NOEL: < 25 mg/kg
 Lowest observable effect level: 25 mg/kg

Species: Rat, male
 Sex: male
 Application Route: oral gavage
 Dose: 0, 50, 100, 200 mg/kg
 Exposure time: 103 wk
 Number of exposures: 5 d/wk
 NOEL: < 50 mg/kg
 Lowest observable effect level: 50 mg/kg

Species: Mouse
 Application Route: oral gavage
 Dose: 0, 25, 50, 100 mg/kg
 Exposure time: 103 wk
 NOEL: < 25 mg/kg

Genotoxicity in vitro**Toluene**

: Test Type: Ames test
 Result: negative

Test Type: Sister Chromatid Exchange Assay
 Result: negative

Test Type: Mouse lymphoma assay
 Result: negative

Test Type: Cytogenetic assay
 Result: negative

n-Heptane

Test Type: Ames test
 Method: Mutagenicity (Escherichia coli - reverse mutation assay)
 Result: negative

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

Benzene

Test Type: Mammalian cell gene mutation assay
Method: OECD Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Guideline 473
Result: negative

Test Type: Mitotic recombination
Result: negative

Test Type: Ames test
Result: negative

Test Type: Cytogenetic assay
Result: positive

Test Type: Mouse lymphoma assay
Result: positive

Test Type: Sister Chromatid Exchange Assay
Result: negative

Genotoxicity in vivo

Toluene : Test Type: Cytogenetic assay
Result: negative

Test Type: Mouse micronucleus assay
Result: negative

Benzene : Test Type: Mouse micronucleus assay
Result: positive

Carcinogenicity

Toluene : Species: Rat
Dose: 0, 600, 1200 ppm
Exposure time: 2 yrs
Number of exposures: 6.5 h/d, 5 d/wk
Remarks: No evidence of carcinogenicity

Species: Mouse
Dose: 0, 600, 1200 ppm
Exposure time: 2 yrs
Number of exposures: 6.5 h/d, 5 d/wk
Remarks: No evidence of carcinogenicity

Benzene : Species: Rat
Sex: female
Dose: 0, 25, 50, 250 mg/kg
Exposure time: 103 wks
Number of exposures: daily, 5 days/week
Test substance: yes
Remarks: zymbal gland carcinomas, squamous cell papillomas

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

Species: Rat
 Sex: male
 Dose: 0, 50, 100, 200 mg/kg
 Exposure time: 103 wks
 Number of exposures: daily, 5 days/week
 Test substance: yes
 Remarks: zymbal gland carcinomas, squamous cell papillomas

Species: Mouse
 Sex: male and female
 Dose: 25, 50, 100 mg/kg
 Exposure time: 103 wks
 Number of exposures: daily, 5 days/week
 Test substance: yes
 Remarks: Clear evidence of multiple organ carcinogenicity.

Reproductive toxicity

Toluene : Species: Rat
 Application Route: Inhalation
 Dose: 0, 100, 500, 2000 ppm
 Test period: 95 d
 NOAEL Parent: 2000 ppm

n-Heptane : Species: Rat
 Sex: male and female
 Application Route: Inhalation
 Dose: 0, 900, 3000, 9000 ppm
 Number of exposures: 6 hr/d, 5 d/wk
 Test period: 13 wk
 Method: OECD Test Guideline 416
 NOAEL Parent: 3000ppm
 NOAEL F1: 3000 ppm
 NOAEL F2: 3000 ppm
 Information given is based on data obtained from similar substances.

Developmental Toxicity

Toluene : Species: Rat
 Application Route: Inhalation
 Dose: 0, 100, 500, 2000 ppm
 Test period: 95 d
 NOAEL Teratogenicity: 400-750 ppm

n-Heptane : Species: Rat
 Application Route: Inhalation
 Dose: 0, 900, 3000, 9000 ppm
 Exposure time: GD6-15
 Number of exposures: 6 hrs/d
 NOAEL Teratogenicity: 9000 ppm
 NOAEL Maternal: 3000 ppm

Toluene Standardization Fuel 85.2

Aspiration toxicity : May be fatal if swallowed and enters airways.

CMR effects

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

Toluene	: Carcinogenicity: Not classifiable as a human carcinogen. Mutagenicity: Animal testing did not show any mutagenic effects. Teratogenicity: Some evidence of adverse effects on development, based on animal experiments. Reproductive toxicity: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.
n-Heptane	Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects. Teratogenicity: Animal testing did not show any effects on fetal development. Reproductive toxicity: No toxicity to reproduction
Benzene	Carcinogenicity: Human carcinogen. Mutagenicity: In vivo tests showed mutagenic effects Teratogenicity: Did not show teratogenic effects in animal experiments. Reproductive toxicity: Animal testing did not show any effects on fertility.
Toluene Standardization Fuel 85.2 Further information	: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

SECTION 12: Ecological information**Ecotoxicity effects****Toxicity to fish**

Toluene	: LC50: 18 - 36 mg/l Exposure time: 96 h Species: Pimephales promelas (fathead minnow)
n-Heptane	LL50: 5.738 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) Method: QSAR modeled data
Benzene	LC50: 5.3 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) flow-through test Test substance: yes Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

Toluene	: EC50: 3.78 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)
n-Heptane	EC50: 1.5 mg/l Exposure time: 48 h

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

Species: *Daphnia magna* (Water flea)
static test Toxic to aquatic organisms.

LC50: 0.1 mg/l
Exposure time: 96 h
Species: *Mysidopsis bahia* (mysid shrimp)
semi-static test Very toxic to aquatic organisms.

Benzene
EC50: 10 mg/l
Exposure time: 48 h
Species: *Daphnia magna* (Water flea)
static test Test substance: yes
Method: OECD Test Guideline 202

Toxicity to algae

Toluene : EC50: 134 mg/l
Exposure time: 72 h
Species: *Chlamydomonas angulosa* (Green algae)

n-Heptane
EL50: 4.338 mg/l
Exposure time: 72 h
Species: *Pseudokirchneriella subcapitata* (microalgae)
Method: QSAR

Benzene
ErC50: 100 mg/l
Exposure time: 72 h
Species: *Pseudokirchneriella subcapitata* (green algae)
Test substance: yes
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity)

n-Heptane : NOELR: 1.284 mg/l
Exposure time: 28 d
Species: *Oncorhynchus mykiss* (rainbow trout)
Method: QSAR modeled data

Biodegradability : This material is expected to be readily biodegradable.

Elimination information (persistence and degradability)

Bioaccumulation : This material is not expected to bioaccumulate.

Mobility : The product evaporates readily.

Results of PBT assessment
Toluene : Non-classified vPvB substance, Non-classified PBT substance

n-Heptane : Non-classified PBT substance, Non-classified vPvB substance

Benzene : Substance is not persistent, bioaccumulative, and toxic (PBT)., Substance is not very persistent and very bioaccumulative (vPvB).

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

Additional ecological information : Very toxic to aquatic life with long lasting effects.

Ecotoxicology Assessment

Short-term (acute) aquatic hazard
Toluene : Toxic to aquatic life.

n-Heptane : Very toxic to aquatic life.

Benzene : Toxic to aquatic life.

Long-term (chronic) aquatic hazard
Toluene : Harmful to aquatic life with long lasting effects.

n-Heptane : Very toxic to aquatic life with long lasting effects.

Benzene : Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, MARINE POLLUTANT, (N-HEPTANE)

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, (-4 °C c.c.), MARINE POLLUTANT, (N-HEPTANE)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (N-HEPTANE)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

33, UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (N-HEPTANE)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (N-HEPTANE)

Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information**National legislation**

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Skin corrosion or irritation

CERCLA Reportable Quantity : 1515 lbs
Toluene

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : This material does not contain any components with a section 302 EHS TPQ.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

SARA 313 Components : The following components are subject to reporting levels established by SARA Title III, Section 313:
: Toluene - 108-88-3

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):
: Toluene - 108-88-3

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):
: Toluene - 108-88-3

US State Regulations

Pennsylvania Right To Know
: Toluene - 108-88-3
n-Heptane - 142-82-5
Benzene - 71-43-2

California Prop. 65 Components : WARNING: This product can expose you to chemicals including [listed below], which is [are] known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov/food.

Benzene 71-43-2

WARNING: This product can expose you to chemicals including [listed below], which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Toluene 108-88-3
Benzene 71-43-2

Toluene Standardization Fuel 85.2

Version 1.2


Revision Date 2024-10-01

Notification status

Europe REACH	:	This product is in full compliance according to REACH regulation 1907/2006/EC.
United States of America (USA) TSCA	:	On or in compliance with the active portion of the TSCA inventory
Switzerland CH INV	:	On the inventory, or in compliance with the inventory
Canada DSL	:	All components of this product are on the Canadian DSL
Australia AIIC	:	On the inventory, or in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	On the inventory, or in compliance with the inventory
Korea KECI	:	A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s).
Philippines PICCS	:	On the inventory, or in compliance with the inventory
Taiwan TCSI	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 708420

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial	LOAEL	Lowest Observed Adverse Effect

Toluene Standardization Fuel 85.2

Version 1.2

Revision Date 2024-10-01

	Chemicals		Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate